



Conventional Fire Systems

Sounders & VADs

ROLP Wall Sounder

[◀ Back to Search results for "BF430C/F/11" \(2 other results\)](#)



ROLP Wall Sounder

Part No. **BF430C/F/11**

- Certified to EN54 Parts 3 (BRE) and 13 (BSI).
- 102dB(A) sound output.
- 12mA alarm current depending on setting.
- 32 tones.
- Ideal for general signalling and fire use.



Technical Specifications



Approvals/certifications	Certified to EN54-3 by BRE and EN54-13 by the BSI.
Protocol/compatibility	Can be used on the conventional sounder circuits of most conventional fire panels including C-TEC's FP, MFP, CFP & EP203. Can also be used on the conventional sounder circuits provided on CTEC's XFP and ZFP addressable panels.
Application/operation	Designed to be wall mounted. Suitable for indoor areas only.
Supply/operating voltage	18-28V DC.
Quiescent current	TBC.
Nominal SPL (Sound Pressure Level)	102dB(A) when set to tone 3.
Alarm current	12mA when set to tone 3.
Product dimensions (mm)	93mm diameter x 95mm deep.
Construction & finish	ABS FR & polycarbonate.
IP Rating	IP54
Weight	0.25Kg.
Operating conditions/temperature	-25°C to +70°C.

Approval Certificates



EN54-13 System Approval Certificate (BSI)

 Download

7 other products in the same category:



Solista LX Wall VAD



Solista LX Ceiling VAD



RoLPLX Wall Sounder VAD



Symphoni LX Wall Sounder VAD



Askari Bedhead Sounder



Symphoni LX Wall Sounder



Verso Base Sounder

CONTACT US

 C-TEC , Challenge Way, Wigan, WN5 0LD, UK Opening times: 08:30 - 17:00 GMT.

 **+44 (0) 1942 322744**

 sales@c-tec.co.uk
