

LoadCentre KQ - residual current circuit breakers (RCCB's)

Residual current circuit breakers (RCCB's)

All residual current circuit breakers are suitable for use as main incomers in LoadCentre KQ distribution boards.

- Comply with BS EN 61008. Specification for residual current operated circuit breakers
- Rated voltage 240/415V AC 50/60 Hz
- Test button enables RCCB to be tested periodically
- 30mA device suitable for use as additional protection on final sub circuits
e.g. equipment outside equipotential zone or items requiring 2/4 pole protection
i.e. switched neutral applications

Residual current circuit breakers

Reference number	Description	Cable capacity mm ²	Dimensions (mm)			Weight (Kg)
			Height	Width	Depth	
SED25032	25A RCCB 30mA trip 2 pole	35	81	36	75	0.227
SED25302	25A RCCB 300mA trip 2 pole	35	81	36	75	0.227
SED40032	40A RCCB 30mA trip 2 pole 3	35	81	36	75	0.227
SED40102	40A RCCB 100mA trip 2 pole	35	81	36	75	0.227
SED40302	40A RCCB 300mA trip 2 pole	35	81	36	75	0.227
SED63032	63A RCCB 30mA trip 2 pole 3	35	81	36	75	0.227
SED63102	63A RCCB 100mA trip 2 pole	35	81	36	75	0.227
SED63302	63A RCCB 300mA trip 2 pole	35	81	36	75	0.227
SED80032	80A RCCB 30mA trip 2 pole	50	81	36	75	0.227
SED100032	100A RCCB 30mA trip 2 pole	50	81	36	75	0.227
SED100102	100A RCCB 100mA trip 2 pole	50	81	36	75	0.227
SED25034	25A RCCB 30mA trip 4 pole	35	81	72	75	0.428
SED25304	25A RCCB 300mA trip 4 pole	35	81	72	75	0.428
SED40034	40A RCCB 30mA trip 4 pole	35	81	72	75	0.428
SED40104	40A RCCB 100mA trip 4 pole	35	81	72	75	0.428
SED40304	40A RCCB 300mA trip 4 pole	35	81	72	75	0.428
SED63034	63A RCCB 30mA trip 4 pole	35	81	72	75	0.428
SED63104	63A RCCB 100mA trip 4 pole	35	81	72	75	0.428
SED63304	63A RCCB 300mA trip 4 pole	35	81	72	75	0.428
SED80034	80A RCCB 30mA trip 4 pole	35	81	72	75	0.500
SED100304	100A RCCB 300mA trip 4 pole	50	81	72	75	0.500
SED100304S	100A RCCB 300mA trip 4 pole + TD	50	81	72	75	0.500

Individual RCCB insulated enclosure

Reference number	Description	Dimensions (mm)			Weight (Kg)
		Height	Width	Depth	
RSD4IP54	4 x 18mm module IP54 protection	200	110	112	0.35

RSD insulated enclosures are also suitable for any DIN rail mounted product including time clocks, timers, contactors, switches and relays.

