



PRW049/PRW050



PRW051



PRW052



PRW053

Fused Connection Units With Optional Flex Outlet

- PRW049** 3A Fused Connection Unit
- PRW050** 13A Fused Connection Unit
- PRW051** 13A Switched Fused Connection Unit
- PRW052** 13A Switched Fused Connection Unit With Neon
- PRW053** 13A Fused Connection Unit With Neon

Standards: BS 1363 and BS 1362 (fuse)
Back Box Depth: 25mm Minimum **Cable Size:** 3 x 2.5mm² or 2 x 4mm²
Dimensions: **1 Gang:** (86mm x 86mm x 11mm), **2 Gang:** (146mm x 86mm x 11mm)



PRW020



PRW021



PRW022



PRW290



PRW291



PRW023



PRW024



PRW040



PRW042

20A Control Switches with Optional Flex Outlet

- PRW022** 20A DP Switch
- PRW023** 20A DP Switch With Neon
- PRW040** 20A DP 'Water Heater' Switch
- PRW042** 20A DP 'Water Heater' Switch With Neon

20A DP Sink/Bath Switch

- PRW024** 20A DP Sink/Bath Switch With Neon

Fan Isolation Switch

- PRW020** 10A 3 Pole Fan Isolation Switch
- PRW021** 10A 3 Pole Isolation Switch

Control Switch Plates

- PRW290** 3A FCU With DP Switch (Linked)
- PRW291** 3A FCU With DP Switch & DP Fan Switch (Linked)

Standards: BS EN 60669
Back Box Depth: 25mm Minimum **Cable Size:** 20A DP: 4 x 2.5mm² 10A 3P: 1 x 2.5mm² / 2 x 1.5mm²
Dimensions: **1 Gang:** (86mm x 86mm x 11mm)