



401



402



403



404



406



426



140



152



153



154

**Switch Plates (Unfurnished)**

401	1 Gang Plate Single Aperture
402	1 Gang Plate Twin Aperture
403	1 Gang Plate Triple Aperture
404	2 Gang Plate (2+2) Aperture
406	2 Gang Plate (3+3) Aperture
426	2 Gang Plate 6 In-line Aperture

**Dimmer Switches For Tungsten, Halogen & Low Voltage**

140	1 Gang 2 Way 400W/Va Resistive/Inductive Dimmer Switch
152	2 Gang 2 Way 400W/Va Resistive/Inductive Dimmer Switch
153	3 Gang 2 Way 400W/Va Resistive/Inductive Dimmer Switch
154	4 Gang 2 Way 400W/Va Resistive/Inductive Dimmer Switch

Switch modules interchangeable with MiniGrid® Modules.

We recommend the use of branded halogen lamps with all DEFINE® dimmers. The use of inferior, non-branded lamps may require the nominal rating of the dimmer to be reduced. These dimmer switches have not been designed for use with LED lamps. However, they may be suitable for some good quality LED lamps. For further information please contact the Click® Technical support team.

**Cable Size:** Dependant on module used

**Dimensions:** 1 Gang (88mm x 88mm x 1.3mm\*), 2 Gang (146mm x 88mm x 1.3mm\*) \*Excluding gasket

**Standards:** BS EN 60669, BS EN 55015 **Type:** Leading Edge

**Back Box Depth:** 35mm Minimum **Cable Size:** 2 x 1.5mm²

**Dimensions:** 1 Gang (88mm x 88mm x 1.3mm\*), 2 Gang (146mm x 88mm x 1.3mm\*) \*Excluding gasket