


CMA030 CMA630



CMA035 CMA635



CMA035PWRD



CMA034



CMA038



CMA039



CMA036



CMA037



CMA935
Non-standard socket



CMA936
Non-standard socket



CMA836



CMA840



PA380WH
Non-standard plug

13A UK Socket Outlets

- CMA030 13A 1 Gang Socket Outlet
- CMA032 13A 2 Gang Socket Outlet Twin Earth
- CMA035 13A 1 Gang DP Switched Socket Outlet
- CMA036 13A 2 Gang DP Switched Socket Outlet (Twin Earth)
- CMA037 13A 2 Gang DP Switched Socket Outlet (Twin Earth, Clean Earth)
- CMA630 13A 1 Gang Socket Outlet (Twin Earth)
- CMA635 13A 1 Gang DP Switched Socket Outlet (Twin Earth)

13A UK Socket Outlets (Outboard Rockers)

- CMA836 13A 2 Gang DP Outboard Switched Socket (Twin Earth)
- CMA840 13A 2 Gang DP Outboard Switched Socket & Neons (Twin Earth)

13A UK Socket Outlets (Red Rockers)

- CMA035PWRD 13A 1 Gang DP Switched Socket (Twin Earth)
- CMA836PWRD 13A 2 Gang DP Outboard Switched Socket (Twin Earth)

Round Pin Power Socket Outlets

- CMA034 15A Round Pin Switched Socket Outlet
- CMA038 5A Round Pin Socket Outlet
- CMA039 2A Round Pin Socket Outlet

13A Switched Non-Standard Socket Outlets

- CMA935 13A 1 Gang DP Switched Non-Standard Socket Outlet
- CMA936 13A 2 Gang DP Switched Non-Standard Socket Outlet

13A Fused Non-Standard Plug - Resilient

- PA380WH 13A Fused Non-Standard Plug White
 - PA380RD 13A Fused Non-Standard Plug Red
- For use with non-standard Click® Mode sockets CMA935 and CMA936

Standards: BS 1363

Back Box Depth: 25mm Minimum Cable Size: 4 x 2.5mm²

Dimensions: 1 Gang (86mm x 86mm x 9.5mm), 2 Gang (146mm x 86mm x 9.5mm)

Standards: BS 546, BS 1363

Back Box Depth: 25mm Minimum Cable Size: 2A: 2 x 2.5mm² / 3 x 1.5mm² 5A: 2 x 2.5mm² / 3 x 1.5mm² 13A: 4 x 2.5mm²

Dimensions: 1 Gang (86mm x 86mm x 9.5mm), 2 Gang (146mm x 86mm x 9.5mm)