## essentials IP66 Weatherproof Sockets



# Metal Clad Accessories

10AX Switches | Unfurnished Switch Plates | 20A Switches | 13A Socket Outlets | Fused Connection Units | 45A Switches | Telephone & Coaxial Socket Outlets | New Media Plates | Mounting Boxes & Blank Plates

A comprehensive selection of metal clad electrical accessory products are featured in the following pages. Electrophoretically coated plates and back boxes provide a durable and long lasting heavy duty finish to this attractive range of products.

All switch products are of modular construction allowing the installer total freedom in designing customised switching solutions according to on-site needs.

All socket outlets and spurs are tested and approved to BS1363. Unfurnished plates and mounting boxes are available for use in conjunction with our extensive range of MINIGRID® and NEW MEDIA™ modules.







The products illustrated in this section of the catalogue are finished plates and unfurnished mounting plates.

For comprehensive information on the full range of modules available please refer to our CLICK® MINIGRID® product brochure.

### IP66 Weatherproof Sockets (Furnished)

OA035AG 1 Gang Weatherproof Socket Fitted with a 1 gang Mode™ switched socket

#### IP66 Weatherproof Enclosure (Unfurnished)

OA501AG 1 Gang Weatherproof Enclosure Sockets supplied separately

IP66 Weatherproof Sockets (Furnished)

OA036AG 2 Gang Weatherproof Socket Fitted with a 2 gang Mode™ switched socket

#### IP66 Weatherproof Enclosure (Unfurnished)

OA502AG 2 Gang Weatherproof Enclosure Sockets supplied separately

Standards: BS EN 60529 (Enclosure), BS 1363 (Socket) Knock-outs: 20mm Cable Size: 4 x 2.5mm² Dimensions: 1 Gang: From Front: 155mm (Height) x 100mm (Width) x 95mm (Depth - with Gasket) From Rear: 130mm (Height) x 105mm (Width). 2 Gang: From Front: 155mm (Height) x 158mm (Width) x 95mm (Depth - with Gasket) From Rear: 130mm (Height) x 165mm (Width) Back Box Depth: 25mm - 47mm