



CL010/011



CL012



CL013



CL019



CL105

10AX Plate Switches (Modular)

CL010	10AX 1 Gang 1 Way Plate Switch
CL011	10AX 1 Gang 2 Way Plate Switch
CL025	10AX 1 Gang Intermediate Switch
CL012	10AX 2 Gang 2 Way Plate Switch
CL013	10AX 3 Gang 2 Way Plate Switch
CL019	10AX 4 Gang 2 Way Plate Switch
CL105	10AX 6 Gang 2 Way Plate Switch

10AX Switches (No Knockouts In Back Box)

CL011B	10AX 1 Gang 2 Way Plate Switch
CL012B	10AX 2 Gang 2 Way Plate Switch

Standards: BS EN 60669

Cable Size: 4 x 1.5mm² / 2 x 2.5mm² / 1 x 6mm² Maximum **Back Box Depth:** 40mm

Dimensions: 1 Gang (80mm x 80mm), 2 Gang (140mm x 80mm) **Knock-outs:** 20mm



CL401



CL402



CL403



CL404



CL406



CL426

Switch Plates (Unfurnished)

CL401	Single Plate Single Aperture
CL402	Single Plate Twin Aperture
CL403	Single Plate Triple Aperture
CL404	Double Plate 2 X 2 Aperture
CL406	Double Plate 2 X 3 Aperture
CL426	Double Plate 6 In-Line Aperture

CL plates should be used with WH coloured modules.
See MiniGrid® modules catalogue.

Knock-outs: 20mm **Dimensions:** 1 Gang (80mm x 80mm), 2 Gang (140mm x 80mm) **Back Box Depth:** 40mm