



CMA500



CMA501



CMA502



CMA504



CMA505



CMA503



PRW208

PRW210/
PRW211

PRC009



PRC210



PRW213



PRC216

45A Plate Switches (White Rockers)

- CMA500** 45A 1 Gang Single Cooker Switch
CMA501 45A 1 Gang Single Cooker Switch with Neon
CMA502 45A 2 Gang Single Cooker Switch
CMA503 45A 2 Gang Single Cooker Switch with Neon
CMA504 45A Cooker Switch with 13A Switched Socket Outlet
CMA505 45A Cooker Switch with 13A Switched Socket Outlet and Neons

Pullcord Switches - POLAR White

- PRC009** 10AX 2 Way Pull Switch
PRC210 10AX 2 Way Pull Switch
PRC216 16A DP Pull Switch with Neon

Decorative covers available for PRC210/216, see Essentials™ page k25

Pullcord Switches - POLAR White

- PRW208** 10A 3 Pole Pullcord Fan Isolation Switch with Neon
PRW210 45A DP Pullcord Switch with Mechanical 'ON/OFF' and Neon
PRW211 50A DP Pullcord Switch with Mechanical 'ON/OFF' and Neon (Twin Terminal Screws)
PRW213 50A Round DP Pull Switch with Mechanical 'ON/OFF' and Neon (Twin Terminal Screws) C/W Pattress

Standards: BS EN 60669, BS 4177**Back Box Depth:** 35mm Minimum **Cable Size:** 45A: 1x16mm²**Dimensions:** 1 Gang (86mm x 86mm x 9.5mm), 2 Gang (146mm x 86mm x 9.5mm)**Standards:** BS EN 60669**Cable Size:** 009, 208, 210: 3x 2.5mm² / 1x 6mm² 211: 2x 6mm² / 1x 25mm² 213: 2x 6mm² / 1x 25mm² 216: 3x 1.5mm² / 2x 2.5mm²**Dimensions:** PRC009: 75.5mm Dia. x 43.5mm PRC210/216: 70mm Dia. x 42mm PRW208: 86mm x 86mm x 43mm

PRW210/211: 86mm x 86mm x 43mm PRW213: 100mm Dia. x 77mm