



RJ11 Data Outlets

115 Single RJ11 Flush Socket - Ireland/USA

UK Telephone Outlets

120 Single Telephone Socket - Master
121 Twin Telephone Socket - Master
125 Single Telephone Socket - Secondary
126 Twin Telephone Socket - Secondary

Twin outlets are 2 separate sockets and not internally linked together.

Satellite Socket Outlets (Unshielded)

156 Non-Isolated Single Satellite Socket
157 Isolated Satellite & Isolated Coaxial Socket
170 Non-Isolated Satellite & Non-Isolated Coaxial Socket

Isolated outlets will filter out any interference, if a 2 way signal is required, i.e. for use with satellite hard wire extensions, then a non-isolated outlet is required.

Non-Isolated Coaxial Socket (Unshielded)

065 Single Non-Isolated Coaxial Socket
066 Twin Non-Isolated Coaxial Socket

Isolated Coaxial Socket (Unshielded)

158 Single Isolated Coaxial Socket
159 Twin Isolated Coaxial Socket

Back Box Depth: 16mm Minimum **Termination Type:** IDC

Dimensions: 1 Gang (88mm x 88mm x 8mm), 2 Gang (146mm x 88mm x 8mm)

Back Box Depth: 16mm Minimum

Dimensions: 1 Gang (88mm x 88mm x 8mm), 2 Gang (146mm x 88mm x 8mm)

Deco® plates are manufactured from stainless steel, available in the following finishes: Antique Brass (AB), Polished Brass (BR), Satin Brass (SB), Polished Chrome (CH), Satin Chrome (SC), Black Nickel (BN), Pearl Nickel (PN) and Stainless Steel (SS). Georgian Style (GCBR) plates are manufactured from cast brass. Please note: Antique Brass and Black Nickel are only available with black inserts. **Understanding the code:** **VP** - Plate Style **BN** - Plate Finish **011** - Product No. **BK** - Insert Colour