





CMA115 / CMA131



CMA115 / CMA132



CMA122 / CMA127



CMA119 / CMA124



CMA065



CMA066



CMA156



CMA170



CMA157



CMA158



CMA159

RJ11 Data Outlets

CMA115 RJ11 (Irish/US) Outlet

RJ45 Data Outlets

CMA131 1 Gang Single CAT-5E Outlet

CMA132 1 Gang Double CAT-5E Outlet

UK Telephone Socket Outlets - Urea

CMA119 Single Telephone Outlet - Master

CMA122 Twin Telephone Outlet - Master

CMA124 Single Telephone Outlet - Secondary

CMA127 Twin Telephone Outlet - Secondary

Twin outlets are 2 separate sockets and not internally linked together.

Non-Isolated Coaxial & Satellite Socket Outlets (Unshielded)

CMA065 Single Non-Isolated Coaxial Socket Outlet

CMA066 Twin Non-Isolated Coaxial Socket Outlet

CMA156 Non-Isolated Satellite Outlet Plate

CMA170 Non-Isolated Satellite And Non-Isolated Coaxial Plate

Isolated Coaxial & Satellite Socket Outlets (Unshielded)

CMA157 Isolated Satellite And Isolated Coaxial Plate

CMA158 Single Isolated Coaxial Plate

CMA159 Twin Isolated Coaxial Plate

Isolated outlets will filter out any interference, if a 2 way signal is required, i.e. for use with satellite hard wire extensions, then a non-isolated outlet is required.

Back Box Depth: 16mm Minimum **Termination Type:** IDC

Dimensions: 1 Gang (86mm x 86mm x 9.5mm)

Back Box Depth: 16mm Minimum

Dimensions: 1 Gang (86mm x 86mm x 9.5mm)