

Metallic Systems Conduit, Fittings & Accessories

Range Overview

Adaptaflex have a choice of fifteen individual metallic conduit systems manufactured either in galvanized steel or stainless steel.

A range of 3 different conduit types provide a solution for liquid resistant specifications with a further 3 conduit options in liquid tight covered steel conduit for especially demanding environments. Conduit ranges are offered in nominal conduit size from 3mm for CCTV/roller shutter doors and for protecting fibre optics cables right up to 75mm for larger cable carrying capacity.

Overbraided conduits are particularly suitable for installation in abrasive environments. Where applications call for enhanced low fire hazard properties or EMI screening then there is the option of high specification tinned copper overbraided for greater EMI protection levels.

In addition a range of fittings are specifically designed to maintain system integrity including fixed and swivel fittings, straights, 90°, 45°, and a host of accessories including locknuts, enlargers, reducers and converters.

Many of our conduit systems have industry recognised approvals including British Kitemark, CE Approval, UL Listing, NF, LUL and Lloyds Register amongst others.

Advantages

- High compression/crush strength
- Tensile strength - pull off load under tension
- Impact resistance
- Inherent fire protection on uncoated versions
- Corrosion resistant - stainless steel options
- Braided - High level EMI screening with tinned copper overbraided
- Greater temperature tolerances

Approvals & Standards



Product Ranges

ADAPTASTEEL
SYSTEM

