



NEW

PRODUCT FOCUS

GuardCam ^{WF}

Wire free external area protection system



CCTV

EAP

Access
Control

Fire
Protection

www.espuk.com

GuardCam^{WF}

Wire free external area protection system



- Wire free transmission of images
- Accepts up to four combined camera PIR LED floodlights
- SD card video recording in receiver unit
- Wireless video transmission of up to 150m in open field
- Built in motion detection with area masking facility
- Time date stamping of recordings
- Warning alert of motion detection
- Easy transmitter receiver pairing
- CE FCC approved



Digital Wirefree Technology




LED Low Energy Floodlight



Internal SD Card Recording



Sound Alert



On Screen Motion Detection



Time and Date Stamping

GuardCam WF is the ideal system for surveillance and protection of external areas around homes, offices or industrial and agricultural units. Up to four combined CCTV camera, PIR, LED floodlights can transmit images using stable FHSS digital wire free technology to a choice of indoor receivers with built in recording and comprehensive user controls. Activity can be continuously monitored and recorded or triggered automatically via on screen movement with selectable audio alert for occupants. Captured images can be transferred to a PC or laptop for distribution if required.



GuardCam WF-M

- GuardCam WF-T - Combined camera PIR Transmitter
- GuardCam WF-MR - 7" Monitor Receiver with power supply
- Mini SD Converter
- SD-USB adapter
- 2Gb mini SD card
- AV lead



GuardCam WF-SA

- GuardCam WF-T - Combined camera PIR Transmitter
- GuardCam WF-SAR - Stand Alone Receiver with power supply
- Remote control
- Mini SD Converter
- SD-USB adapter
- 2Gb mini SD card
- AV lead



GuardCam WF-T

- GuardCam WF-T - Combined camera PIR Transmitter

All prices nett of VAT.
E&OE - Errors & omissions excepted

Place your order now - sales hotline 01527 515150

GuardCam^{WF}



Up to four transmitters (GuardCam WF-T) can be paired to a single receiver (either GuardCam WF-MR or GuardCam WF-SAR). The receivers can be directly connected to a television with AV inputs.

TECHNICAL SPECIFICATIONS

GuardCam WF-T

| | |
|-------------------------------|--------------------------------|
| Detection Method | Passive Infrared |
| Sensor Range | 12m x 140° |
| Camera Resolution | 640 X 480 |
| LED Floodlight output | 8 Pcs 1W Nichia High Power LED |
| Lumen output | 1100 |
| Time adjustment | 5 secs ~ 10 mins |
| Lux adjustment | Dark - daylight |
| Transmitter signal technology | 2.4 GHz FHSS Technology |
| Transmitter output | 16dBm |
| Transmission Range | 150m open field |
| Voltage | 100-240V 50Hz/60Hz |
| Current drain | 225±20mA |
| IP rating | IP55 |
| Operating Temp. | -10°C ~ 40°C |
| Dimensions | 160 x 176 x 260MM |
| Weight | 1400g |

GuardCam WF-MR

| | |
|---------------------|-------------------------|
| Channels | 4 |
| Reception Range | 150m in open field |
| Receiver Resolution | 800 X 480 |
| Screen size | 7" Screen (16:9) |
| Max. SD card size | 32Gb |
| Receiver technology | 2.4 GHz FHSS Technology |
| Video Output | 1.2±0.2Vp-p/75ohm |
| Operating Voltage | DC 5V / 1A |
| Current Consump. | 860mA(max) |
| Operating Temp. | -10°C ~ 50°C |
| Video Output | 1.2±0.2Vp-p/75ohm |
| Audio output | 75±10dB |
| Record time | 2 / 5 / 10 mins |
| Dimension | 200 x 122 x 26 mm |
| Weight | 400g |

GuardCam WF-SAR

| | |
|---------------------|------------------------|
| Channels | 4 |
| Reception Range | 150m in open field |
| Receiver Resolution | 800 X 480 |
| Max. SD card size | 32Gb |
| Receiver technology | 2.4GHz FHSS Technology |
| Video Output | 1.2±0.2Vp-p/75ohm |
| Operating Voltage | DC 5V / 1A |
| Current Consump. | 250mA(max) |
| Operating Temp. | -10°C ~ 50°C |
| Dimensions | 122 x 113 x 25 mm |
| Weight | 335g |

Elite Security Products

Unit 7, Target Park, Shawbank Rd
Lakeside, Redditch B98 8YN

All prices nett of VAT



Telephone: 01527 515150

email: info@espuk.com

www.espuk.com

E&OE - Errors and omissions excepted