

SPECIFICATION SHEET

Product Code

DP*414#


Description

10AX 4 Gang 2 Way Switch 'Ingot' (Modular)



General Information	
Dimensions	148mm x 88mm x 8mm (Excluding Gasket)
Finishes Available	Replace * with: AB (Antique Brass), BN (Black Nickel), BR (Polished Brass), CH (Polished Chrome), SB (Satin Brass), SC (Satin Chrome) or SS (Stainless Steel)
Inserts Available	Replace # with: WH (White) or BK (Black). Black or White gasket supplied to match appropriate insert. (Antique Brass and Black Nickel are only available with black inserts)
Material composition	Front Plate: Stainless Steel Rear Housing: Nylon Terminals: Brass Earth Strap: Mild Steel Terminal Screws: Steel and Yellow Passivated Silver "on-lay" copper/brass contacts.
Voltage	250V~ 50Hz
Load Rating	10AX (Suitable for Inductive loads)
Terminal Size	3.5mm Ø
Torque Value	0.4Nm
Cable Size	4 x 1.5mm ² or 2 x 2.5mm ²
Back Box Depth	16mm – 47mm
Modular	Yes
Gang	4
2 Way	Yes
Operational Temperature	-5°C – +40°C
Warranty	10 Years

Standards	BS EN 60669
-----------	-------------

Additional Information	<p>Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram supplied with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.</p> <p>Interchangeable with switches in the MiniGrid system.</p> 
------------------------	--

Errors & Omissions excluded. Specification is subject to change without notice.

V1.0