

## SPECIFICATION SHEET

**Product Code** DP\*038#

**Description** 5A Round Pin Socket



General Information	
Dimensions	88mm x 88mm x 8mm (Excluding Gasket)
Finishes Available	Replace * with: AB (Antique Brass), BN (Black Nickel), BR (Polished Brass), CH (Polished Chrome), SB (Satin Brass), SC (Satin Chrome) or SS (Stainless Steel)
Inserts Available	Replace # with: WH (White) or BK (Black). Black or White gasket supplied to match appropriate insert. (Antique Brass and Black Nickel are only available with black inserts)
Material composition	Front Plate: Stainless Steel Rear Housing: Urea Terminals: Brass Earth Strap: Mild Steel Terminal Screws: Steel and Yellow Passivated Silver "on-lay" copper/brass contacts.
Voltage	250V~ 50Hz
Load Rating	5A
Terminal Size	5mm $\phi$
Torque Value	1.2Nm
Cable Size	2 x 2.5mm <sup>2</sup> or 3 x 1.5mm <sup>2</sup>
Back Box Depth	25mm – 47mm
Switched	No
Double Pole	No
Twin Earth Terminals	No
Clean Earth Terminals	No
Operational Temperature	-5°C – +40°C
Warranty	10 Years

<b>Standards</b>	BS 546: 1950
------------------	--------------

<b>Additional Information</b>	Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram supplied with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
-------------------------------	---

Errors & Omissions excluded. Specification is subject to change without notice.

V1.0