



SPECIFICATION SHEET

Product Code

DP*065#

Description

Single Non Isolated Coaxial Socket





General Information	
Dimensions	88mm x 88mm x 8mm (Excluding Gasket)
Finishes Available	Replace * with: AB (Antique Brass), BN (Black Nickel), BR (Polished Brass),
	CH (Polished Chrome), SB (Satin Brass), SC (Satin Chrome) or
	SS (Stainless Steel)
Inserts Available	Replace # with: WH (White) or BK (Black).
	Black or White gasket supplied to match appropriate inserts.
	(Antique Brass and Black Nickel are only available with black inserts).
Material composition	Front Plate: Stainless Steel
Back Box Depth	16mm – 47mm
Termination Type	Screw Terminals
Isolated	No
Shielded	No
Operational Temperature	-5°C -+40°C
Warranty	10 Years

Standards	BS 3041-7:1996
	BS 5733:1995 (where applicable)
Additional Information	Isolated socket will filter out any interference, if a 2 way signal is required,
	i.e. for use with satellite hard wire extensions, then a non-isolated outlet
	is required.
	Ensure that the mains supply is isolated before commencing installation
	and refer to the circuit diagram supplied with the relevant product.
	Bare earth cables must always be covered with appropriate sleeving and
	wired to the earth terminal.

V1.0

Staffordshire, B79 7XB.