

SPECIFICATION SHEET


Product Code DP*422#

Description 10AX 2 Gang 2 Way Toggle Switch



General Information	
Dimensions	88mm x 88mm x 8mm (Excluding Gasket)
Finishes Available	Replace * with: AB (Antique Brass), BN (Black Nickel), BR (Polished Brass), CH (Polished Chrome), SB (Satin Brass), SC (Satin Chrome) or SS (Stainless Steel) (Supplied with both Black and White gaskets)
Material composition	Front Plate: Stainless Steel Rear Housing: Nylon Terminals: Brass Earth Strap: Mild Steel Terminal Screws: Steel and Yellow Passivated Silver "on-lay" copper/brass contacts.
Voltage	250V~ 50Hz
Load Rating	10AX (Suitable for Inductive loads)
Terminal Size	4.9mm x 4.1mm
Torque Value	1.2Nm
Cable Size	4 x 1.5mm ² or 2 x 2.5mm ²
Back Box Depth	25mm – 47mm
Modular	Yes (Toggle switch modules only)
Gang	2
2 Way	Yes
Operational Temperature	-5°C – +40°C
Warranty	10 Years

Standards	BS EN 60669
-----------	-------------

Additional Information	<p>Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram supplied with the relevant product.</p> <p>Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.</p> <p>Interchangeable with toggle switches in the MiniGrid system.</p> 
------------------------	--

Errors & Omissions excluded. Specification is subject to change without notice.

V1.0