

- Complies with BS 6972 and BS 5733.
- CR64AX comprises of; Plug Cat ref. P64AXR Socket Cat ref. S64AX and Cover Cat. ref. A1.
- **CR64AX/R** Plug Cat ref. P64AXR Socket Cat ref. S64AX and Cover Cat ref. A1/R.
- 6 Amp 250V A.C.
- Sockets have 5 terminations: line, neutral, earth, auxiliary and loop-in.
- Plugs have 4 terminations: line, neutral, earth and auxiliary.
- Static loading when load suspended by flexible cord - 5kg maximum.

For wiring diagrams see page 33.  
For product standards see page 32.

#### 6 Amp 4 Pin Ceiling Rose and Cover

Description	Pack qty.	Cat ref.
White Cover with 75mm Diameter x 44mm, 7mm Back Projection	10	<b>CR64AX</b>
Red Cover with 75mm Diameter x 44mm, 7mm Back Projection	10	<b>CR64AX/R</b>



CR64AX



CR64AX/R

#### 6 Amp 3 Pin Ceiling Rose Cover

Description	Pack qty.	White Cover Cat ref.	Red Cover Cat ref.
75mm Diameter x 44mm Snap Fits to S27 & S64AX Sockets	10	<b>A1</b>	<b>A1/R</b>



A1/R