

- Complies with BS EN 60669-2-4
- Rated conditional short circuit current (Inc) 1500A tested with Hager MTN110 6kA B curve MCB.
- Capacity of each terminal 2 x 4.0mm² conductors.
- For mounting boxes see selection chart on page 65.
- Supplied with M3.5 x 20mm long fixing screws.



WMPS3PIF

1 Gang 3 Pole Isolator Switches

Description	Cat ref.
3 Pole Isolator Switch	WMPS3PI
3 Pole Isolator Switch with Fan Symbol	WMPS3PIF

Socket Outlets

- Unique patented 3 part safety shutter.
- Complies with BS 1363-2, a.c only.
- Double pole switching mechanism on switched sockets.
- Twin socket comes with twin earth as standard.
- All terminal screws grouped in-line and upward facing for ease of installation.
- Clear printed and engraved terminal markings.
- Capacity of each terminal: 5 x 2.5mm² conductors switched; 4 x 2.5mm² unswitched (for other sized conductors see terminal capacities on page 64).
- For mounting boxes see selection chart on page 65.
- Supplied with M3.5 x 30mm long fixing screws.



WMSS82O

13A Switched Sockets

Description	Cat ref.
1 Gang Double Pole Switched Socket	WMSS81
2 Gang Double Pole Switched Socket Dual Earth	WMSS82
2 Gang Double Pole Switched Socket Dual Earth Outboard Rockers	WMSS82O
1 Gang Double Pole Switched Socket with LED Indicator	WMSS81N
2 Gang Double Pole Switched Socket Dual Earth with LED Indicator	WMSS82N
2 Gang Double Pole Switched Socket Dual Earth Outboard Rockers with LED Indicator	WMSS82ON



WMS51

5A / 13A Unswitched Socket

Description	Cat ref.
5A 1 Gang Unswitched Socket	WMS51
13A 1 Gang Unswitched Socket	WMS81
13A 2 Gang Unswitched Socket Dual Earth	WMS82