

- Complies with BS 6972 and BS 5733
- The klik lighting S26/TC socket is an S26 architrave socket pre-assembled with a trunking clamp
- Fast and easy installation of sockets, that have been prewired at bench level, into return edge trunking
- Designed to fit 50mm x 50mm return edge trunking profiles
- This product may not be suitable for all installations. Suitability should be checked prior to commencing work

#### 6 Amp Lighting Trunking Socket with Clamp



S26/TC

Dimensions (mm)	Fixing	Pack qty.	Cat ref.
86 x 33 x 6 7mm Back Projection	Via Integral Trunking Clamp	10	<b>S26/TC</b>

## 6 Amp Plugs

- Complies with BS 6972 and BS 5733
- Suitable for use with any klik lighting or klik AX socket and klik LDS
- 3 pins and cord grip enable up to a 5kg load to be suspended by a flexible cord
- P22 plug is supplied in plug-in Ceiling Rose, Cat No. PCR2000
- Luminaire plugs are designed for incorporation by OEM's.
- Plugs have 3 terminations: live, neutral and earth
- Static loading when load suspended by flexible cord - 5kg maximum

#### Warning

Plugs must not be fitted on the supply side of any installation - they must be connected to the load / fitting / appliance side of the installation.

#### 3 Pin Plug



P22

Description	Fixing	Pack qty.	Cat ref.
With Cord Grip and Cover, 57mm x 25mm x 25mm	Lead	10	<b>P22</b>