

IN STOCK NOW
LOWER WATTAGE • HIGHER LUMEN

More Than Just A Panel



up to 102lm/W

Advanced, seamless, LED Flat
Panel range delivering maximum
brightness with minimal glare.

High output dimmable LEDs Provide superior lighting performance
High Transmission Diffuser Excellent glare control - UGR19
Light Guide Unique Aurora optical pattern for improved uniformity
Ultra Slim Aluminium Frame Sleek, lightweight design
Steel Heatsink Large surface area for rapid heat dissipation
Front of panel is IP44 rated



AURORA®
LED Lighting Specialists

NEW




scan or visit
go.aurora.co/sc-versatile



5 year
warranty



Specification	600 x 600mm	625 x 625mm	500 x 500mm	600 x 600mm Colour Xchange	1200 x 600mm	1200 x 300mm	1200 x 150mm Interconnectable	1200 x 300mm Up/Down
Wattage	38W	38W	38W	30W	65W	38W	40W	40W
Lumens	up to 3900lm	up to 3900lm	up to 3900lm	2000-2125lm	5500lm	up to 3900lm	3200lm	3300-3500lm
lm/W	up to 102lm/W	up to 102lm/W	up to 102lm/W	70lm/W	85lm/W	up to 102lm/W	80lm/W	80lm/W - 87lm/W
Colour Temperature	3000K - 3600lm 4000K - 3900lm	3000K - 3600lm 4000K - 3900lm	3000K - 3600lm 4000K - 3900lm	3000-6500K 4000-6500K	3000K 4000K	3000K - 3600lm 4000K - 3900lm	4000K	3000K 4000K
Colour Rendering (Ra)	>80	>80	>80	>80	>80	>80	>80	>80
Options	1-10V Dimmable Emergency DALI DALI Emergency	1-10V Dimmable Emergency DALI DALI Emergency	1-10V Dimmable Emergency DALI DALI Emergency	Full Colour Exchange Step Colour Exchange	1-10V Dimmable Emergency DALI DALI Emergency	1-10V Dimmable Emergency DALI DALI Emergency	1-10V Dimmable DALI	1-10V Dimmable DALI
Dimensions	595 x 595 x 12mm	622 x 622 x 12mm	498 x 498 x 12mm	595 x 595 x 12mm	1195 x 595 x 12mm	1195 x 295 x 12mm	1200 x 150 x 10mm	1195 x 295 x 15mm
Non-Dimmable	AU-LP100B/30 AU-LP100B/40 AU-LP100B/30EM AU-LP100B/40EM	AU-LP300B/30 AU-LP300B/40 AU-LP300B/30EM AU-LP300B/40EM	AU-LP200B/30 AU-LP200B/40 AU-LP200B/30EM AU-LP200B/40EM	AU-LP102BSD	AU-LP103B/30 AU-LP103B/40 AU-LP103B/30EM AU-LP103B/40EM	AU-LP104B/30 AU-LP104B/40 AU-LP104B/30EM AU-LP104B/40EM	AU-LP107A/40	-
Dimmable	AU-LP101B/30 AU-LP101B/40 AU-LP101B/30EM AU-LP101B/40EM	AU-LP301B/30 AU-LP301B/40 AU-LP301B/30EM AU-LP301B/40EM	AU-LP201B/30 AU-LP201B/40 AU-LP201B/30EM AU-LP201B/40EM	AU-LP102BCX	AU-LP105B/30 AU-LP105B/40 AU-LP105B/30EM AU-LP105B/40EM	AU-LP106B/30 AU-LP106B/40 AU-LP106B/30EM AU-LP106B/40EM	AU-LP109A/40	AU-SU101A/30 AU-SU101A/40
DALI Dimmable	AU-LP100B/30D AU-LP100B/40D AU-LP100B/30DEM AU-LP100B/40DEM	AU-LP300B/30D AU-LP300B/40D AU-LP300B/30DEM AU-LP300B/40DEM	AU-LP200B/30D AU-LP200B/40D AU-LP200B/30DEM AU-LP200B/40DEM	-	AU-LP103B/30D AU-LP103B/40D AU-LP103B/30DEM AU-LP103B/40DEM	AU-LP104B/30D AU-LP104B/40D AU-LP104B/30DEM AU-LP104B/40DEM	AU-LP107A/40D	AU-SU101A/30D AU-SU101A/40D
Surface Mount Box	AU-SM103A	AU-SM104A	AU-SM105A	AU-SM103A	AU-SM106A	AU-SM107A	-	-

- Edge lit design provides superior light performance and uniformity ideal for offices and commercial lighting
- High transmission diffuser drastically reduces uncomfortable glare
- Heatsink rapidly dissipates heat through rear of fitting
- Dimmable and CX colour exchange version available to set the desired light environment
- IP44 from below – suitable for use in commercial kitchens, clean rooms, health care and similar environments
- Suitable for installation in 15 & 24mm T-bar ceilings

- Panel frame RAL9016 White
- High colour rendering index (Ra) 80
- SDCM <4 providing consistent light colour quality
- DALI and Emergency options available
- (L70) at a 40,000 hour lifetime
- 5 Year Warranty - see www.auroralighting.com for details

AURORA®
LED Lighting Specialists

auroralighting.com     