LED Retrofit For Linear Fluorescent LINEARLED LINEARLEDX

IN STOCK NOW

The cost-effective LINEARLED makes the decision to convert old linear fluorescent to LED a lot easier. With performance as high as 97lm/W, LINEARLED is designed as the affordable retrofit solution.



LINEARLED



scan or visit go.aurora.co/sc-linearled

LINEARLEDX



Specification	LinearLED Single 1200mm	LinearLED Twin 1200mm	LinearLED Single 1500mm	LinearLED Twin 1500mm	LinearLEDX Wide Distribution Twin 1500mm
Wattage	25W	50W	30W	60W	65W
Lumens	up to 2040Im	up to 4180lm	up to 2850lm	up to 5810lm	6100lm
lm/W	up to 82lm/W	up to 84lm/W	up to 95lm/W	up to 97lm/W	up to 94lm/W
Colour Temperature	4000K 6000K	4000K 6000K	4000K 6000K	4000K 6000K	4000K
Colour Rendering (Ra)	>80	>80	>80	>80	>80
Dimensions	1274 x 90 x 90mm	1274 x 140 x 90mm	1574 x 90 x 90mm	1574 x 140 x 90mm	1570 x 160 x 110mm
Options	Emergency	Emergency	Emergency	Emergency	Emergency
T8 Equivalent	Single T8 36W	Twin T8 36W	Single T8 58W	Twin T8 58W	Twin T8 58W
L70 Hours	25,000	25,000	25,000	25,000	40.000
Warranty	3	3	3	3	5
Non-Dimmable	AU-ANT1203A/40 AU-ANT1203A/60*	AU-ANT1204A/40 AU-ANT1204A/60*	AU-ANT1503A/40 AU-ANT1503A/60*	AU-ANT1504A/40 AU-ANT1504A/60*	AU-ANT1507A/40
Emergency	AU-ANT1203A/40EM AU-ANT1203A/60EM*	AU-ANT1204A/40EM AU-ANT1204A/60EM*	AU-ANT1503A/40EM AU-ANT1503A/60EM*	AU-ANT1504A/40EM AU-ANT1504A/60EM*	AU-ANT1507A/40EM

* 6000K available to special order

- IP65 vandal resistant polycarbonate body and diffuser ideal for carparks and food preparation areas
- Diffuser permanently attached by two clips for ease of installation
- Gear tray restraints for ease of installation and maintenance
- Optional mounting brackets (included) allow for ceiling, wall or suspended mounting
- Anti-tamper stainless steel clips supplied as standard

- Multiple conduit entry points at the back and ends of housing
- IK08 impact rating
- Replacement gear trays available contact sales office for details
- Emergency versions available
- (L70) at a 25,000 & 40,000 hour lifetime
- 3 & 5 Year Warranty see www.auroralighting.com for details



ENGINEERED TO MAXIMISE

auroralighting.com 🗹 f 🖇 🛅 in