## IN STOCK NOW **Driverless** LED, CFL Retrofit series

**AU-DL10019BW SHOWN WITH AU-BF150W BEZEL** 









13W # **700lm** 19W# 1450lm



19W ₩ **14<u>50lm</u>** 



The driverless series range of dimmable integrated LED downlights is a high performance, high power replacement for CFL. Featuring HVLED™, icDOB™ and CrystalCool™ technologies.



CrystalCool™ higher quality, brighter light for longer™



**HVLED™** superior colour rendering

















Specification	13W Integrated LED Downlight	19W Integrated LED Downlight	19W Integrated LED Downlight	32W Integrated LED Downlight
Wattage	13W	19W	19W	32W
Lumens	up to 700lm	up to 1450lm	up to 1450lm	up to 2250lm
Colour Temperature	3000K 4000K	3000K 4000K	3000K 4000K	3000K 4000K
Colour Rendering (Ra)	>80	>80	>80	>80
Diameter	116mm	178mm	230mm	230mm
Cut Out	90mm	150mm	210mm	210mm
Recess	73mm	80mm	83mm	83mm
Options	Emergency Baffle Accessory	Emergency Baffle Accessory	Emergency Baffle Accessory	Emergency Baffle Accessory
CFL Equivalent	1 x 18W CFL	1 x 26W CFL	2 x 18W CFL	2 x 26W CFL
Dimmable	AU-DL10013BW/30* AU-DL10013BW/40*	AU-DL10019BW/30* AU-DL10019BW/40*	AU-DL20019BW/30* AU-DL20019BW/40*	AU-DL10032BW/30* AU-DL10032BW/40*
Baffle Accessory	AU-BF90W	AU-BF150W	AU-BF210W	AU-BF210W

\*Add Suffix **EM** to catalogue number for emergency option

- icDOB<sup>TM</sup> (Driver on Board) for maximum reliability and lifetime - NO SEPARATE DRIVER REQUIRED
- CrystalCool<sup>™</sup> next generation thermal management offers brighter light for longer
- Reduced heatsink due to CrystalCool<sup>™</sup> Technology allows installation in shallow ceiling voids
- IP44 Rated

- Lightweight polycarbonate bezel
- Optional baffle bezel available in white finish
- Smooth and linear dimming on most leading / trailing edge dimmers
- Emergency options available
- (L70) at a 40,000 hour lifetime
- 5 Year Warranty see www.auroralighting.com for details

