

GEWISS

DOMOTICS

POWER

BUILDING

LIGHTING

IB Range - COMBIBLOC and 44IB Compact socket outlets IP44 and IP55

Industrial socket-outlet system with interlocked switch, for energy distribution in commercial and industrial applications.

COMBIBLOC—compact socket-outlets

The COMBIBLOC range establishes new smaller dimensions for interlocked switched socket-outlets with 16-32A versions in a single size. They can be fixed to a flush mounted 3-gang box from Gewiss' domestic ranges.

The vertically-operated lever is easy to use and can be fitted with a safety lock. The tilted socket-outlet makes it easy to insert the plug and keeps the power cable at the correct angle for safety.



44 IB—range of horizontal versions

Versions from 110V to 500V, from 16-32A are ideal for use in light industry and tertiary sector applications. Their shape and compact dimensions mean that a large number of socket-outlets can be installed in a small space.



Tel: 01954 712757

Email: customerservice@gewiss.co.uk

Fax: 01954 712753

GEWISS

IB RANGE Product Overview

The **IB Range** includes other voltages and many more configurations. For the complete offer please visit our website www.gewiss.co.uk, see our latest **Building catalogue**, or scan the QR barcode:



COMBIBLOC COMPACT SOCKET-OUTLETS

HORIZONTAL SOCKET-OUTLETS 44IB

Rated Current (A)	Rated Voltage Un (V)	No. Poles	Ref H	Compact socket-outlet with rotary switch, with back-box IP 44	Compact socket-outlet, with rotary switch, with back-box IP 55	Horizontal socket-outlets with rotary switch, with back-box IP44
16A	100-130V	2P+E	4	GW66401	GW66445	GW66001
16A	200-250V	2P+E	6	GW66404	GW66448	GW66004
16A	380-415V	3P+E	6	GW66408	GW66452	GW66008
16A	380-415V	3P+N+E	6	GW66409	GW66453	GW66009
32A	100-130V	2P+E	4	GW66412	GW66456	GW66012
32A	200-250V	2P+E	6	GW66415	GW66459	GW66015
32A	380-415V	3P+E	6	GW66419	GW66463	GW66019
32A	380-415V	3P+N+E	6	GW66420	GW66464	GW66020