

09

Undershelf & Cabinet



185
SKYBLADE®



186
LED TAPE



187
LED TAPE
ACCESSORIES



188
T5
UNDERSHELF



189
LV
UNDERSHELF

Skyblade®

Unique edge lit LED undershelf lighting

UP TO

100 LPCW

LUMENS PER CIRCUIT WATT

UP TO

800

LUMENS

EXTENDED

10 YEAR

WARRANTY



Strong, even light distribution

Skyblade's patented design uses Light Guide Board technology to throw the light on to the wall, the work surface and even further down the counter. Alongside one another, the beams from Skyblade® seamlessly blend into one, avoiding 'pools' of light and shadows that other light sources and even some LED fixtures create. All of this creates a clean, consistent level of light across the surface that not only enhances the appearance of any kitchen, but is also perfect for preparation areas.



Skyblade® 8W



Fluorescent tube



Halogen spotlights

CLASSIFICATION

Class 2 (Driver) 

IP20 | 240V

Maximum load per driver 48W

LED



Warm white (3000K) | CRI: Ra (80)

Cool white (4000K) | CRI: Ra (80)

FINISH

White



CONSTRUCTION

Body - Polycarbonate


PATENT PENDING




ON/OFF DIMMING SWITCH

JC83113


DRIVER (JC83114)



SKYBLADE® 8W



SKYBLADE® 4W



Skyblade

The direct 8W & 14W T5 fluorescent replacement



10 year

Extended warranty*

- Designed for use with 500mm (single) & 1200mm (double) wall cabinets
- Provides up to 50% energy saving against T5 fluorescent
- Designed for even light distribution on the work surface
- Simple and easy two point screw fit installation
- Zero maintenance, no need to relamp
- Skyblade® on/off dimmer switch available (JC83113)
- **NEW** 48W LED driver (JC83114)

✓ JC83100



✓ JC83101



CODE	DESCRIPTION	COLOUR TEMP.	WATT	LUMENS
JC83100	Skyblade® undershelf LED c/w 750mm cable	Cool white	4W	385
JC83102	Skyblade® undershelf LED c/w 750mm cable	Warm White	4W	350
JC83101	Skyblade® undershelf LED c/w 900mm cable	Cool white	8W	800
JC83103	Skyblade® undershelf LED c/w 900mm cable	Warm White	8W	740
JC83108	350mm cable + 2 x cable clips	-	-	-
JC83109	1200mm cable + 4 x cable clips	-	-	-
JC83110	1500mm cable + 5 x cable clips	-	-	-
JC83111	Cable adaptor female - female	-	-	-
JC83113	On/off dimming switch accessory	-	-	-
JC83114	48W 2amp 24V DC driver (Available Oct '16)	-	-	-

*10 year for domestic dwellings, 5 year for commercial properties. Requires online registration.

LED Tape & Drivers

High efficiency LED tape

✓ **5 year**
Extended warranty*

- Ultra efficient, up to 96 lumens per circuit Watt
- Available in warm and cool white colour variants
- 5M lengths as standard (10mm wide)
- IP65 tape as standard
- Dimmable variants available
- Cuttable and connectable
- Low output LED tape starter kits include 36W Triac dimmable driver and accessories
- 75W driver for medium output tape and 100W driver for high output tape

✓ JC83205



NEW
PRODUCT

Available Nov '16

CLASSIFICATION

- Class 2 (Driver)
- ⬢ Class 3 (Tape)
- IP65 (tape) | 240V

LED



Warm white (3000K) | CRI: Ra (85)
Cool white (4000K) | CRI: Ra (85)



COMPATIBLE LED DIMMER

Starter kit only - See page 238

CODE	DESCRIPTION	COL. TEMP	WATT	LUMENS
JC83201	Low output LED tape & driver	3000K	5.2W (per metre)	500 (per metre)
JC83202	Low output LED tape & driver	4000K	5.2W (per metre)	500 (per metre)
JC83203	Medium output LED tape	3000K	13W (per metre)	1100 (per metre)
JC83204	Medium output LED tape	4000K	13W (per metre)	1100 (per metre)
JC83205	High output LED tape	3000K	20W (per metre)	1700 (per metre)
JC83206	High output LED tape	4000K	20W (per metre)	1700 (per metre)
JC83208	LED driver IP20 - Non-dimmable	-	75W	-
JC83208DIM	LED driver IP65 - 1-10V dimmable	-	75W	-
JC83209	LED driver IP20 - Non-dimmable	-	100W	-
JC83209DIM	LED driver IP65- 1-10V dimmable	-	100W	-

*Requires online registration.

FINISH
Silver



CONSTRUCTION

Profile - Extruded aluminium
Diffuser - Opal polycarbonate

LED Tape Accessories

NEW
PRODUCT

Available Nov '16




5 year
Extended warranty*

- Linkable LED tape lighting extrusions
- High output LED tape variants require aluminium profile
- Connectors available to link tape inside profile and around corners
- Heat shrink sleeve available for maintaining IP rating when cutting tape


✓ JC83210

✓ JC83212


JC83211



JC83210



JC83212



CODE

DESCRIPTION

JC83210	Aluminium surface mount flat profile 1m - Opal diffuser
JC83211	Aluminium recessed flat profile 1m - Opal diffuser
JC83212	Aluminium surface corner profile 1m - Opal diffuser
JC83213	Internal tape to DC cable linking accessory (10 pack)
JC83214	Internal L-type quick connector (5 pack)
JC83215	Internal 2-end tape connector with 15cm cable (5 pack)
JC83216	IP65 2-end tape connector (10 pack)
JC83217	PCB retaining clips (10 pack)
JC83218	DC cable retaining clips (10 pack)

*Requires online registration.

T5 Undershef

Linkable fluorescent undershef lighting

LED equivalents
See pages 185

- Luminaires may be continuously joined together using the in-line adaptor as supplied up to a maximum of 10 units
- Luminaires are supplied with a full fixing kit for vertical and horizontal installation
- Slim line profile
- Individually switched
- Rota style safety lamp holders
- Non-dimmable

CLASSIFICATION

Class 2
IP20 | 240V

LAMP (INCLUDED)

T5 8-28W

FINISH

White




CONSTRUCTION

Body - Extruded polycarbonate profile





JC83022

JC83023



JC83020

JC83021



CODE	DESCRIPTION	LAMP
JC83020	T5 8W low energy fluorescent striplight	T5 8W
JC83021	T5 14W low energy fluorescent striplight	T5 14W
JC83022	T5 21W low energy fluorescent striplight	T5 21W
JC83023	T5 28W low energy fluorescent striplight	T5 28W
JC83024	250mm link lead	-
JC83025	500mm link lead	-
JC83026	1000mm link lead	-

CLASSIFICATION

Class 3 
IP20 | 12V

LAMP (INCLUDED)

20W G4

FINISH

Chrome



CONSTRUCTION

Body - Pressed steel
Diffuser - Clear heat resistant glass


Downlights are pre-wired with
1M cable

CUTOUT SIZES

ø60mm when recessed



JC4030 - TRANSFORMER



Low Voltage Undershef

Low profile undershef lighting

- Can be recessed into shelves or surface mounted
- Lamps included
- Sold individually

✓ JC3014CH
Surface adaptor supplied



CODE	DESCRIPTION	LAMP
JC3014	Low voltage undershef downlight	G4 20W
JC4030	10-60VA transformer for JC3014	-