

06

Emergency



118
IP65 LED
EXIT BULKHEAD



119
LED EXIT
BLADE



120
LED
EXIT BOX



121
LED
TWIN SPOT



122
RECESSED LED
DOWNLIGHT



123
SURFACE LED
DOWNLIGHT

IP65 Exit Bulkhead

Direct 8W T5 retrofit LED exit bulkhead

5 year
Extended warranty*

- IP65, ideal for all commercial and industrial applications
- Supplied with up/down/left/right running man legends as standard
- Self test as standard (7W version only)
- 100% maintained and non-maintained modes
- Hinged LED gear tray for fast installation
- Side and rear conduit entry points

JC50301



CODE	DESCRIPTION	WATT	LUMENS (DC)	LUMENS (AC)
JC50301	Exit bulkhead - Self test	7W	190	430
JC50321	Exit bulkhead	3W	120	122

*Requires online registration.

CLASSIFICATION

Class 1
IP65 | 240V

LED

6000K

JC50301 - 6000K | CRI: Ra (80)

JC50321 - 6000K | CRI: Ra (85)

FINISH

White

CONSTRUCTION

Body - Polycarbonate


Diffuser - Prismatic polycarbonate

LED gear tray - White painted steel

JC50321



JC50301



CLASSIFICATION

Class 1 
IP20 | 240V

LED



6000K | CRI: Ra (78)


FINISH

White




CONSTRUCTION

Body - Polycarbonate frame
Legend - Acrylic



Exit Blade

Contemporary LED exit wall blade

 **5 year**
Extended warranty*

- Hinged frame for wall and ceiling mounting applications
- Visible from a distance of 24 metres
- Supplied without running man legend
- Running man legend kits bought separately

 JC50302
(Shown with JC50308)



CODE	DESCRIPTION	WATT	LUMENS (DC)	LUMENS (AC)
JC50302	Exit bulkhead	3W	50	50
JC50308	Running man kit - Arrow left & right	-	-	-
JC50310	Running man kit - Arrow down (x2)	-	-	-
JC50311	Running man kit - Arrow up (x2)	-	-	-

*Requires online registration.

Exit Box

Direct 8W T5 retrofit LED exit box


 **5 year**
Extended warranty*

- Visible from a distance of 24 metres
- Supplied as standard with down running man legend
- Left/right or up running man bought separately
- Top and rear conduit entry knock out points

 JC50303



CLASSIFICATION

 Class 1
IP20 | 240V

LED



6000K | CRI: Ra (48)

FINISH

White




CONSTRUCTION


Body - White painted steel
Diffuser - Polycarbonate

CODE	DESCRIPTION	WATT	LUMENS (DC)	LUMENS (AC)
JC50303	Exit box with down arrow legend	6W	50	95
JC50304	Left and right running man legend	-	-	-
JC50314	Up running man legend	-	-	-

*Requires online registration.



CLASSIFICATION

Class 1 
IP65 | 240V

LED



6000K

FINISH

White



CONSTRUCTION

Body - Polycarbonate
Lamp head - Polycarbonate

Twin Spot


IP65 emergency LED twin spot



5 year
Extended warranty*

- Durable construction
- Ideal for commercial and industrial applications
- Twin side conduit entry
- Lightweight design for quick and simple installation

✓ JC50305



CODE	DESCRIPTION
------	-------------

JC50305	Exit bulkhead
---------	---------------

*Requires online registration.

WATT	LUMENS
------	--------

7W	470
----	-----

Recessed LED Downlight

Discreet 3W remote LED downlight


 **5 year**
Extended warranty*

- Non-maintained 3W recessed downlight
- Ideal for emergency lighting in offices and corridors

 JC50306



CLASSIFICATION

 Class 2
IP20 | 240V

LED



6000K

FINISH

White



CONSTRUCTION


Body - Polycarbonate control gear
in a fire retardant bag

CUTOUT SIZES

Ø34mm

CODE	DESCRIPTION
JC50306	Emergency recessed LED downlight
*Requires online registration.	

WATT	LUMENS (DC)
3W	103



CLASSIFICATION

Class 2 
IP20 | 240V

LED



6000K


FINISH

White



CONSTRUCTION

Body - Polycarbonate housing,
aluminium LED body



Surface LED Downlight

Surface mount 3W LED downlight

 **5 year**
Extended warranty*

- Non-maintained
- Quick and simple surface mount installation
- Stylish design ideal for contemporary commercial applications

✓ JC50307



CODE	DESCRIPTION	WATT	LUMENS (DC)
JC50307	Emergency surface mounted LED downlight	3W	103

*Requires online registration.