



Economy LED




Professional LED

**LED
LIGHTING
AND
FIXTURES
2016/17**



LED Fixtures



Tubes





MEGAMAN TECHNOLOGIES

4-7




LED PROFESSIONAL SERIES

8-41



LED ECONOMY SERIES

42-79



TUBES 80-85



LED FIXTURES 86-148



TECOH® MODULES

149-155



EMERGENCY PACKS

156-157

Megaman (UK) Limited
Megaman House
2 Quadrant Park
Mundells
Welwyn Garden City
Herts AL7 1FS

T: +44 (0)1707 386000
F: +44 (0)1707 386001
E: sales@megamanuk.com
W: www.megamanuk.com

Follow us @megamanukltd

Hybrid Reflector

Excellent Optics. High Efficiency. Precise Beam Control.



Introducing Megaman's new Hybrid Reflector - providing excellent optics, high efficiency and precise beam control.


Combining the best features of Megaman's popular faceted reflector with the total internal reflection of our optical reflector - minimising

spill light, reducing glare and almost indistinguishable from a halogen reflector.

Hybrid Reflector Technology currently features on our new 7W LED GU10 and Rico HR integrated fixtures - all of which come with U-DIM™ Technology as standard too.


How does it work?

MEGAMAN® Hybrid Reflector



Beam Control with Total Internal Reflection

Legacy Reflector



Spill Light of Conventional Reflector

NEW TECHNOLOGY '16

MEGAMAN®

U-DIM™

Leading-Edge or Trailing-Edge?

Now, there's no need to worry.



by

MEGAMAN®



Megaman's new U-DIM™ technology is a breakthrough in dimming technology - making our lamps compatible with the widest possible range of existing dimmers, whether they are leading-edge or trailing-edge.

Megaman's U-DIM™ technology now features on several of our new lamps and integrated fixtures - allowing flicker-free dimming from 100% right down to 5%.

Dim to Warm

Improved dimming performance with the warmth of Halogen.

Megaman's Dim to Warm range of LEDs emit a warmer light when they are dimmed, from 2800K to 1800K, simulating the characteristics of incandescent and halogen lamps.

Available on a selection of Megaman LED lamps and integrated fixtures.



INGENIUM® BLU

Megaman's INGENIUM® BLU, a range of Bluetooth enabled LED lamps which use Bluetooth technology to connect to and control lighting in homes and commercial spaces.

With INGENIUM® BLU you can enjoy the benefits of smart lighting with instant and easy set-up.

Currently available in a PAR16 GU10 and Classic shape LED.



Turn Ordinary Lighting into Smart Lighting

-  **Easy Installation**
Can be set up without wiring, making it accessible and cost-effective for everyone
-  **Mobile Control**
Control the latest Megaman® LED via a smart device
-  **Scene Setting**
Set lighting routines that fit your lifestyle
-  **Energy-savings**
High energy savings when dimming function is used



Perfect White



Brings whites to life

Megaman's Perfect White technology is a solution that offers retailers a distinct advantage enhancing textiles by bringing whites to life, while offering superb energy efficiency.

The Perfect White range produces a high quality light that mimics the effect of daylight on white objects, giving them a natural vibrancy that makes them stand out from the crowd.

Available on a selection of Megaman LED lamps and fixtures.



How it works

1. Download the app.
2. Install the INGENIUM® BLU LED lamp.
3. Control your lighting using your smart device.



MEGAMAN®

Professional Series

| | |
|--------------------|-------|
| GU10 | 10-13 |
| MR16 | 14-16 |
| MR11 | 17 |
| AR111 | 18-22 |
| R7s | 23-24 |
| LED Strip | 25 |
| Candle | 26-28 |
| Classic | 29-35 |
| Golf Ball | 36-37 |
| Crown Silver/Brass | 38-40 |
| Tube | 41 |

Extendable warranty. Increased lamp life. Professional quality.

The Megaman LED Professional Series of reflectors and decorative lamps comprise of a number of unique features and benefits including new technologies U-DIM™, Hybrid Reflector, Dim to Warm, Perfect White and *INGENIUM*® BLU.

Suitable for commercial and high-end interior applications, the Professional Series delivers high quality light sources and excellent

colour rendering. The patented design of these lamps allow them to deliver superior performance of up to 50,000hours, fantastic lumen output and low power consumption.

The majority of Professional Series lamps are dimmable. Megaman exhaustively test all dimming LED lamps with the key dimming manufacturers on the market. To download a compatible list of dimmers

for a specific lamp, please visit the website www.megamanuk.com/products/dimming-compatibility

This range of lamps come with a 3 year warranty as standard, which you can extend to 5 years through online registration, by visiting www.megamanuk.com/products/warranty





Professional
5.5W
GU10 Dimming


LR4605.5dDG-WFL

Features



PARI16 GU10, perfect for retrofit applications such as showrooms, reception areas, meeting rooms, offices, restaurants, lounges and kitchens. This lamp features Megaman's new U-DIM™ Technology, offering an enhanced dimming range from 100% down to 5% with the widest range of dimmers, whether they are leading-edge or trailing-edge.

141724/141726/141728



Specification

| UK Order Code > | 141724 | 141726 | 141728 |
|-------------------------|-----------|-----------|-----------|
| Watts | 5.5W | 5.5W | 5.5W |
| Colour Temp (K)/CRI | 2800 / 82 | 4000 / 85 | 6500 / 85 |
| Lumens (lm) | 500 | 500 | 500 |
| Candelas (cd) | 540 | 540 | 540 |
| Dimmable | Y | Y | Y |
| Lamp Base | GU10 | GU10 | GU10 |
| Hrs Lamp Life (L70) | 50,000 | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 | 25,000 |
| Beam Angle | 35° | 35° | 35° |
| Weight (g) | 61 | 61 | 61 |
| Dimensions (L x Dia mm) | 57x50 | 57x50 | 57x50 |

Please visit our website for a full list of compatible dimmers - www.megamanuk.com/products/dimming-compatibility

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature: -30°C to +40°C



Professional
6W
GU10 Dim to Warm


LR5006wDG-WFL

Features



The Dim to Warm range of Megaman LEDs emit a warmer light when they are dimmed, from 2800K to 1800K, simulating the characteristics of incandescent and halogen lamps.

141806




Specification

| UK Order Code > | 141806 |
|-------------------------|----------------|
| Watts | 6W |
| Colour Temp (K)/CRI | 2800-1800 / 82 |
| Lumens (lm) | 400 |
| Candelas (cd) | 480 |
| Dimmable | Y |
| Lamp Base | GU10 |
| Hrs Lamp Life (L70) | 50,000 |
| Hrs Lamp Life (L90) | 25,000 |
| Beam Angle | 35° |
| Weight (g) | 64 |
| Dimensions (L x Dia mm) | 57x50 |

Please visit our website for a full list of compatible dimmers - www.megamanuk.com/products/dimming-compatibility

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature: -30°C to +40°C



Professional
7W
GU10 Dimming


LR5907dHR

Features



PARI16 GU10, perfect for retrofit applications such as showrooms, reception areas, meeting rooms, offices, restaurants, lounges and kitchens. This lamp features Megaman's new Hybrid Reflector which provides excellent optics, high efficiency and precise beam control. Also featuring Megaman's new U-DIM™ Technology, offering an enhanced dimming range from 100% down to 5% with the widest range of dimmers, whether they are leading-edge or trailing-edge.

142200/142202/142204



Specification

| UK Order Code > | 142200 | 142202 | 142204 |
|-------------------------|-----------|-----------|-----------|
| Watts | 7W | 7W | 7W |
| Colour Temp (K) /CRI | 2800 / 82 | 4000 / 85 | 6500 / 85 |
| Lumens (lm) | 550 | 550 | 550 |
| Candelas (cd) | 1400 | 1400 | 1400 |
| Dimmable | Y | Y | Y |
| Lamp Base | GU10 | GU10 | GU10 |
| Hrs Lamp Life (L70) | 50,000 | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 | 25,000 |
| Beam Angle | 35° | 35° | 35° |
| Weight (g) | 68 | 68 | 68 |
| Dimensions (L x Dia mm) | 57x50 | 57x50 | 57x50 |

Please visit our website for a full list of compatible dimmers - www.megamanuk.com/products/dimming-compatibility

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Professional
8W
GU10 *INGENIUM*® BLU Dimming


LR3808dBT-WFL

Features



INGENIUM® BLU is a brand new series of Bluetooth enabled LED lamps which use Bluetooth technology to connect to and control lighting. With the *INGENIUM*® BLU solution's integrated Bluetooth technology, you can enjoy the benefits of smart lighting with instant and easy set-up. App available on Apple App Store and Google Play Store.

142406/142408



Specification

| UK Order Code > | 142406 | 142408 |
|-------------------------|-----------|-----------|
| Watts | 8W | 8W |
| Colour Temp (K) /CRI | 2800 / 82 | 4000 / 85 |
| Lumens (lm) | 540 | 540 |
| Candelas (cd) | 750 | 750 |
| Dimmable | Y* | Y* |
| Lamp Base | GU10 | GU10 |
| Hrs Lamp Life (L70) | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 |
| Beam Angle | 35° | 35° |
| Weight (g) | 62 | 62 |
| Dimensions (L x Dia mm) | 65x50 | 65x50 |

*Operating characteristics for best performance - Please note *INGENIUM*® BLU lamps need a power supply to energise the Bluetooth connection, this means the wall control needs a standard wall switch and not a dimmer. To dim lamp, leave wall switch turned on and dim via the app.

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Professional

ER3306w-50H36D


6W GU5.3 MR16 Dim to Warm 18V 350mA

Features



The Dim to Warm range of Megaman LEDs emit a warmer light when they are dimmed, from 2800K to 1800K, simulating the characteristics of incandescent and halogen lamps.

144627



Specification

| UK Order Code > | 144627 |
|-------------------------|----------------|
| Watts | 6W |
| Colour Temp (K) /CRI | 2800-1800 / 82 |
| Lumens (lm) | 500 |
| Candelas (cd) | 1100 |
| Dimmable | Y |
| Lamp Base | GU5.3 |
| Hrs Lamp Life (L70) | 50,000 |
| Hrs Lamp Life (L90) | 40,000 |
| Beam Angle | 36° |
| Weight (g) | 49 |
| Dimensions (L x Dia mm) | 45x50 |

Megaman recommends the **144650** driver, sold separately.

Please visit our website for a full list of compatible dimmers - www.megamanuk.com/products/dimming-compatibility

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Professional

ER1908d-SP


8W MR16 Dimming 12V

Features



This new MR16 LED lamp from Megaman offers a narrow beam angle of 12° and is perfect for accent lighting in galleries, restaurants and museums.

144850



Specification

| UK Order Code > | 144850 |
|-------------------------|-----------|
| Watts | 8W |
| Colour Temp (K) /CRI | 2800 / 82 |
| Lumens (lm) | 400 |
| Candelas (cd) | 3500 |
| Dimmable | Y |
| Lamp Base | GU5.3 |
| Hrs Lamp Life (L70) | 50,000 |
| Hrs Lamp Life (L90) | 25,000 |
| Beam Angle | 12° |
| Weight (g) | 96 |
| Dimensions (L x Dia mm) | 73x50 |

Please visit our website for a list of compatible transformers/DC drivers.

Please visit our website for a full list of compatible dimmers - www.megamanuk.com/products/dimming-compatibility

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Professional

8W GU5.3 MR16 Dimming 12V


ER2508dLN-FL
ER2508dLN-WFL

Features




The Megaman LED MR16 reflector is the eco-conscious alternative to halogen MR16's with the same compact profile.

144805/144826



144846/144816



Specification

| UK Order Code > | 144805 | 144826 | 144846 | 144816 |
|-------------------------|-----------|-----------|-----------|-----------|
| Watts | 8W | 8W | 8W | 8W |
| Colour Temp (K) /CRI | 2800 / 82 | 4000 / 85 | 2800 / 82 | 4000 / 85 |
| Lumens (lm) | 450 | 450 | 450 | 450 |
| Candelas (cd) | 2900 | 2900 | 1600 | 1600 |
| Dimmable | Y | Y | Y | Y |
| Lamp Base | GU5.3 | GU5.3 | GU5.3 | GU5.3 |
| Hrs Lamp Life (L70) | 50,000 | 50,000 | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 | 25,000 | 25,000 |
| Beam Angle | 24° | 24° | 36° | 36° |
| Weight (g) | 54 | 54 | 54 | 54 |
| Dimensions (L x Dia mm) | 51x50 | 51x50 | 51x50 | 51x50 |

Please visit our website for a full list of compatible transformers/DC drivers.

Please visit our website for a full list of compatible dimmers - www.megamanuk.com/products/dimming-compatibility

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature: -30°C to +40°C



Professional

4W GU4 MR11 12V


ER2304-20H36D

Features



The Megaman LED MR11 is an ideal replacement for halogen, providing significant energy savings and much less heat output. Excellent for use in display cabinets.

141178/141159



Specification

| UK Order Code > | 141178 | 141159 |
|-------------------------|-----------|-----------|
| Watts | 4W | 4W |
| Colour Temp (K) /CRI | 2800 / 80 | 4000 / 80 |
| Lumens (lm) | 230 | 230 |
| Candelas (cd) | 600 | 600 |
| Dimmable | N | N |
| Lamp Base | GU4 | GU4 |
| Hrs Lamp Life (L70) | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 |
| Beam Angle | 36° | 36° |
| Weight (g) | 19 | 19 |
| Dimensions (L x Dia mm) | 42x35 | 42x35 |

Please visit our website for a full list of compatible transformers.

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature: -30°C to +40°C



Professional

10W G53 AR111 1-10V Dimming 20V 500mA


ERO210-50H08D
ERO110-50H24D
ERO310-50H45D

Features




The Megaman LED AR111 is the perfect low energy replacement for halogen AR111s. Less heat is emitted thanks to Megaman's patented Thermal Conductive Highway™ (TCH) which reduces energy loss through heat.


141341/141368



141352/141390



141373/141319



Specification

| UK Order Code > | 141341 | 141368 | 141352 | 141390 | 141373 | 141319 |
|-------------------------|-----------|-----------|-----------|-----------|-----------|-----------|
| Watts | 10W | 10W | 10W | 10W | 10W | 10W |
| Colour Temp (K) /CRI | 2800 / 82 | 4000 / 85 | 2800 / 82 | 4000 / 85 | 2800 / 82 | 4000 / 85 |
| Lumens (lm) | 550 | 550 | 600 | 600 | 630 | 630 |
| Candelas (cd) | 16000 | 16000 | 3600 | 3600 | 1400 | 1400 |
| Dimmable | Y | Y | Y | Y | Y | Y |
| Lamp Base | G53 | G53 | G53 | G53 | G53 | G53 |
| Hrs Lamp Life (L70) | 50,000 | 50,000 | 50,000 | 50,000 | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 40,000 | 40,000 | 40,000 | 40,000 | 40,000 | 40,000 |
| Beam Angle | 8° | 8° | 24° | 24° | 45° | 45° |
| Weight (g) | 218 | 218 | 218 | 218 | 218 | 218 |
| Dimensions (L x Dia mm) | 58x111 | 58x111 | 58x111 | 58x111 | 58x111 | 58x111 |

Use the Megaman 10W AR111 20V dimming driver, **141382**, sold separately. Converts 220-240V to DC20V 500mA. Works with DC1-10V dimmer.

Please contact our sales office for further dimming information.

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature: -30°C to +40°C



Professional

12W G53 AR111 Dimming 12V


ER2712d-75H24D
ER2912d-75H45D

Features




The Megaman LED AR111 is the perfect low energy replacement for halogen AR111s. Less heat is emitted thanks to Megaman's patented Thermal Conductive Highway™ (TCH) which reduces energy loss through heat. The 12W AR111, with reduced height and slimmer profile, replaces the 75W halogen AR111.

141280/141340



141409/141591



Specification

| UK Order Code > | 141280 | 141340 | 141409 | 141591 |
|-------------------------|-----------|-----------|-----------|-----------|
| Watts | 12W | 12W | 12W | 12W |
| Colour Temp (K) /CRI | 2800 / 82 | 4000 / 85 | 2800 / 82 | 4000 / 85 |
| Lumens (lm) | 850 | 850 | 850 | 850 |
| Candelas (cd) | 5000 | 5000 | 2000 | 2000 |
| Dimmable | Y | Y | Y | Y |
| Lamp Base | G53 | G53 | G53 | G53 |
| Hrs Lamp Life (L70) | 50,000 | 50,000 | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 35,000 | 35,000 | 35,000 | 35,000 |
| Beam Angle | 24° | 24° | 45° | 45° |
| Weight (g) | 230 | 230 | 230 | 230 |
| Dimensions (L x Dia mm) | 58x111 | 58x111 | 58x111 | 58x111 |

Megaman recommends the **140627** Megaman transformer for standard switching, sold separately.

Please contact our sales office for further dimming and transformer information.

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature: -30°C to +40°C



Professional

12W G53 AR111 Dim to Warm DC 36V 350mA


ER3712w-75H24D
ER3912w-75H45D

Features




The Dim to Warm range of Megaman LEDs emit a warmer light when they are dimmed, from 2800K to 1800K, simulating the characteristics of incandescent and halogen lamps.

141549



141582



Specification

| UK Order Code > | 141549 | 141582 |
|-------------------------|----------------|----------------|
| Watts | 12W | 12W |
| Colour Temp (K) /CRI | 2800-1800 / 82 | 2800-1800 / 82 |
| Lumens (lm) | 850 | 850 |
| Candelas (cd) | 5000 | 2000 |
| Dimmable | Y | Y |
| Lamp Base | G53 | G53 |
| Hrs Lamp Life (L70) | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 40,000 | 40,000 |
| Beam Angle | 24° | 45° |
| Weight (g) | 230 | 230 |
| Dimensions (L x Dia mm) | 58x111 | 58x111 |

Please contact our sales office for further dimming and driver information.

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature: -30°C to +40°C



Professional

12W G53 AR111 Perfect White Dimming 12V


ER2712p-75H24D
ER2912p-75H45D

Features




Introducing Megaman's Perfect White technology, which intensifies and brightens the colour white - perfect for retail lighting.

131201



131249



Specification

| UK Order Code > | 131201 | 131249 |
|-------------------------|-----------|-----------|
| Watts | 12W | 12W |
| Colour Temp (K) /CRI | 3000 / 82 | 3000 / 82 |
| Lumens (lm) | 700 | 700 |
| Candelas (cd) | 4200 | 1500 |
| Dimmable | Y | Y |
| Lamp Base | G53 | G53 |
| Hrs Lamp Life (L70) | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 35,000 | 35,000 |
| Beam Angle | 24° | 45° |
| Weight (g) | 230 | 230 |
| Dimensions (L x Dia mm) | 58x111 | 58x111 |

Megaman recommends the **140627** Megaman transformer for standard switching, sold separately.

Please contact our sales office for further dimming and transformer information.

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature: -30°C to +40°C




Professional
15W
 GU10 AR111 Dimming

LR1615d-75H24D
 LR1815d-75H45D




The Megaman LED AR111 is the perfect low energy replacement for halogen AR111s. Less heat is emitted thanks to Megaman's patented Thermal Conductive Highway™ which reduces energy loss through heat.

141824/141818



141843/141851



Specification

| UK Order Code > | 141824 | 141818 | 141843 | 141851 |
|-------------------------|-----------|-----------|-----------|-----------|
| Watts | 15W | 15W | 15W | 15W |
| Colour Temp (K) /CRI | 2800 / 82 | 4000 / 85 | 2800 / 82 | 4000 / 85 |
| Lumens (lm) | 950 | 950 | 950 | 950 |
| Candelas (cd) | 5000 | 5000 | 2000 | 2000 |
| Dimmable | Y | Y | Y | Y |
| Lamp Base | GU10 | GU10 | GU10 | GU10 |
| Hrs Lamp Life (L70) | 50,000 | 50,000 | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 40,000 | 40,000 | 40,000 | 40,000 |
| Beam Angle | 24° | 24° | 45° | 45° |
| Weight (g) | 276 | 276 | 276 | 276 |
| Dimensions (L x Dia mm) | 89x111 | 89x111 | 89x111 | 89x111 |

Please contact our sales office for further dimming information.

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature: -30°C to +40°C



Professional
7W
 R7s 78mm

LJ0107



The Megaman LED R7s generates much less heat than its halogen counterparts. Also works with PIRs. Suitable for floodlights or indoor uplighters.

Specification

| UK Order Code > | 142754 |
|-----------------------|-----------|
| Watts | 7W |
| Colour Temp (K) /CRI | 4000 / 80 |
| Lumens (lm) | 450 |
| Dimmable | N |
| Lamp Base | R7s |
| Hrs Lamp Life (L70) | 50,000 |
| Hrs Lamp Life (L90) | 25,000 |
| Weight (g) | 115 |
| Dimensions (HxWxD mm) | 30x56x78 |

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature: -30°C to +40°C



Professional
8W
R7s 118mm

LJ0408

Features



The Megaman LED R7s generates much less heat than its halogen counterparts and is suitable for floodlights and indoor uplighters. This R7s can be used in outdoor floodlights with minimum volume of W120xL160xH80mm. At an ambient temperature of 25°C, the estimated life time is 15,000 hours.

Specification

| UK Order Code > | 142740 |
|-------------------------|-----------|
| Watts | 8W |
| Colour Temp (K) /CRI | 4000 / 80 |
| Lumens (lm) | 1000 |
| Dimmable | N |
| Lamp Base | R7s |
| Hrs Lamp Life (L70) | 50,000 |
| Hrs Lamp Life (L90) | 25,000 |
| Weight (g) | 75 |
| Dimensions (L x Dia mm) | 118x25 |

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Professional
4W/24W LED Strip
24V

ST0103
 ST0118

Features



Covered with an opal diffuser, the Megaman LED strip range eliminates glare by turning hotspots into a soft light source that is perfect for cover lighting and linear illumination applications.

Specification

| UK Order Code > | 172510 | 172180 |
|-----------------------|-----------|-----------|
| Watts | 4W | 24W |
| Colour Temp (K) /CRI | 4000 / 85 | 4000 / 85 |
| Lumens (lm) | 200 | 1200 |
| Dimmable | N | N |
| Hrs Lamp Life (L70) | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 30,000 | 30,000 |
| Weight (g) | 71 | 201 |
| Dimensions (L x D mm) | 310x13 | 1810x13 |

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Professional

LC1106d

6W Opal Candle Dimming

Features



Megaman's LED opal candle caters for a wide array of applications such as chandeliers, decorative fittings and general lighting. The candle offers 330° illumination.

Specification

| UK Order Code > | 143209 | 143280 | 143408 | 143706 |
|-------------------------|-----------|-----------|-----------|-----------|
| Watts | 6W | 6W | 6W | 6W |
| Colour Temp (K) /CRI | 2800 / 80 | 2800 / 80 | 2800 / 80 | 2800 / 80 |
| Lumens (lm) | 470 | 470 | 470 | 470 |
| Dimmable | Y | Y | Y | Y |
| Lamp Base | E14 | E27 | B15 | B22 |
| Hrs Lamp Life (L70) | 50,000 | 50,000 | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 | 25,000 | 25,000 |
| Weight (g) | 45 | 58 | 46 | 58 |
| Dimensions (L x Dia mm) | 106x40 | 106x41 | 104x40 | 106x41 |



Please visit our website for a full list of compatible dimmers - www.megamanuk.com/products/dimming-compatibility

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Professional

LC1106wCS

6W Candle Dim to Warm

Features



The Dim to Warm range of Megaman LEDs emit a warmer light when they are dimmed, from 2700K to 1800K, simulating the same dimming characteristics of incandescent and halogen lamps.

Specification

| UK Order Code > | 143460 | 143629 | 143709 | 143806 |
|-------------------------|----------------|----------------|----------------|----------------|
| Watts | 6W | 6W | 6W | 6W |
| Colour Temp (K) /CRI | 2700-1800 / 80 | 2700-1800 / 80 | 2700-1800 / 80 | 2700-1800 / 80 |
| Lumens (lm) | 470 | 470 | 470 | 470 |
| Dimmable | Y | Y | Y | Y |
| Lamp Base | E14 | E27 | B15 | B22 |
| Hrs Lamp Life (L70) | 50,000 | 50,000 | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 | 25,000 | 25,000 |
| Weight (g) | 60 | 63 | 62 | 63 |
| Dimensions (L x Dia mm) | 106x40 | 106x41 | 104x40 | 104x41 |



Please visit our website for a full list of compatible dimmers - www.megamanuk.com/products/dimming-compatibility

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Incanda
LED

Professional

LC0906dCS

6W
Incanda-LED Candle Dimming

Features



The Incanda-LED range delivers a brilliant sparkling light effect with a unique lamp design that resembles that of an incandescent. The Incanda-LED range features a clear glass finish to enhance its sparkle, perfect for chandeliers and crystal light fittings.

Specification

| UK Order Code > | 143135 | 143469 | 143485 | 143508 |
|-------------------------|-----------|-----------|-----------|-----------|
| Watts | 6W | 6W | 6W | 6W |
| Colour Temp (K) /CRI | 2800 / 80 | 2800 / 80 | 2800 / 80 | 2800 / 80 |
| Lumens (lm) | 470 | 470 | 470 | 470 |
| Dimmable | Y | Y | Y | Y |
| Lamp Base | E14 | E27 | B15 | B22 |
| Hrs Lamp Life (L70) | 50,000 | 50,000 | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 | 25,000 | 25,000 |
| Weight (g) | 78 | 81 | 80 | 81 |
| Dimensions (L x Dia mm) | 106x41 | 106x41 | 104x41 | 104x41 |

Please visit our website for a full list of compatible dimmers - www.megamanuk.com/products/dimming-compatibility



| UK Order Code > | 143137 | 143139 | 143163 | 143164 |
|-----------------|---------|---------|---------|---------|
| Colour/Finish | Silver | Silver | Gold | Gold |
| For Lamp Base | E14/B15 | E27/B22 | E14/B15 | E27/B22 |



Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Incanda
LED

Professional

LG4106dCS

6W
Incanda-LED Classic Dimming

Features



The Incanda-LED range delivers a brilliant sparkling light effect with a unique lamp design that resembles that of an incandescent. The Incanda-LED range features a clear glass finish to enhance its sparkle, perfect for chandeliers and crystal light fittings.

Specification

| UK Order Code > | 148761 | 148741 |
|-------------------------|-----------|-----------|
| Watts | 6W | 6W |
| Colour Temp (K) /CRI | 2800 / 80 | 2800 / 80 |
| Lumens (lm) | 470 | 470 |
| Dimmable | Y | Y |
| Lamp Base | E27 | B22 |
| Hrs Lamp Life (L70) | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 |
| Weight (g) | 75 | 75 |
| Dimensions (L x Dia mm) | 104x55 | 102x55 |

Please visit our website for a full list of compatible dimmers - www.megamanuk.com/products/dimming-compatibility



Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Professional

LG7207d

7W Classic Dimming


Features



The Megaman LED Classic has an intelligent heat sink design for sleek classic shape and compact housing, perfect for domestic applications.

Specification

| UK Order Code > | 148362 | 148364 |
|-------------------------|-----------|-----------|
| Watts | 7W | 7W |
| Colour Temp (K) / CRI | 2800 / 80 | 2800 / 80 |
| Lumens (lm) | 470 | 470 |
| Dimmable | Y | Y |
| Lamp Base | E27 | B22 |
| Hrs Lamp Life (L70) | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 |
| Weight (g) | 78 | 78 |
| Dimensions (L x Dia mm) | 112x60 | 110x60 |



Please visit our website for a full list of compatible dimmers - www.megamanuk.com/products/dimming-compatibility

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Professional

LG2207w

7W Classic Dim to Warm

Features



The Dim to Warm range of Megaman LEDs emit a warmer light when they are dimmed, from 2700K to 1800K, simulating the same dimming characteristics of incandescent and halogen lamps.

Specification

| UK Order Code > | 148258 | 148719 |
|-------------------------|----------------|----------------|
| Watts | 7W | 7W |
| Colour Temp (K) / CRI | 2700-1800 / 80 | 2700-1800 / 80 |
| Lumens (lm) | 470 | 470 |
| Dimmable | Y | Y |
| Lamp Base | E27 | B22 |
| Hrs Lamp Life (L70) | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 |
| Weight (g) | 74 | 74 |
| Dimensions (L x Dia mm) | 104x55 | 102x55 |



Please visit our website for a full list of compatible dimmers - www.megamanuk.com/products/dimming-compatibility

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Professional

LG7310.5d

10.5W Classic Dimming


Features



The Megaman LED Classic has an intelligent heat sink design for sleek classic shape and compact housing, perfect for domestic applications.

Specification

| UK Order Code > | 148366 | 148368 |
|-------------------------|-----------|-----------|
| Watts | 10.5W | 10.5W |
| Colour Temp (K) / CRI | 2800 / 80 | 2800 / 80 |
| Lumens (lm) | 810 | 810 |
| Dimmable | Y | Y |
| Lamp Base | E27 | B22 |
| Hrs Lamp Life (L70) | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 |
| Weight (g) | 105 | 110 |
| Dimensions (L x Dia mm) | 117x60 | 115x60 |



Please visit our website for a full list of compatible dimmers - www.megamanuk.com/products/dimming-compatibility

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Professional

LG2310.5w

10.5W Classic Dim to Warm

Features



The Dim to Warm range of Megaman LEDs emit a warmer light when they are dimmed, from 2700K to 1800K, simulating the same dimming characteristics of incandescent and halogen lamps.

Specification

| UK Order Code > | 148169 | 148267 |
|-------------------------|----------------|----------------|
| Watts | 10.5W | 10.5W |
| Colour Temp (K) / CRI | 2700-1800 / 82 | 2700-1800 / 82 |
| Lumens (lm) | 810 | 810 |
| Dimmable | Y | Y |
| Lamp Base | E27 | B22 |
| Hrs Lamp Life (L70) | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 |
| Weight (g) | 122 | 122 |
| Dimensions (L x Dia mm) | 125x65 | 122x65 |



Please visit our website for a full list of compatible dimmers - www.megamanuk.com/products/dimming-compatibility

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Professional

LG2311dBT

11W Classic *INGENIUM*® BLU Dimming


Features



INGENIUM® BLU is a brand new series of Bluetooth enabled LED lamps which use Bluetooth technology to connect to and control lighting. With the *INGENIUM*® BLU solution's integrated Bluetooth technology you can enjoy the benefits of smart lighting with instant and easy set-up. App available on Apple App Store and Google Play Store.

Specification

| UK Order Code > | 142304 | 142309 |
|-------------------------|-----------|-----------|
| Watts | 11W | 11W |
| Colour Temp (K) /CRI | 2800 / 80 | 2800 / 80 |
| Lumens (lm) | 810 | 810 |
| Dimmable | Y* | Y* |
| Lamp Base | E27 | B22 |
| Hrs Lamp Life (L70) | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 |
| Weight (g) | 120 | 120 |
| Dimensions (L x Dia mm) | 125x65 | 123x65 |



*Operating characteristics for best performance - Please note *INGENIUM*® BLU lamps need a power supply to energise the Bluetooth connection, this means the wall control needs a standard wall switch and not a dimmer. To dim lamp, leave wall switch turned on and dim via the app.

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Professional

LG7813d

13W Classic Dimming

Features



The Megaman LED Classic has an intelligent heat sink design for sleek classic shape and compact housing, perfect for domestic applications.

Specification

| UK Order Code > | 148370 | 148372 |
|-------------------------|-----------|-----------|
| Watts | 13W | 13W |
| Colour Temp (K) /CRI | 2800 / 80 | 2800 / 80 |
| Lumens (lm) | 1055 | 1055 |
| Dimmable | Y | Y |
| Lamp Base | E27 | B22 |
| Hrs Lamp Life (L70) | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 |
| Weight (g) | 128 | 126 |
| Dimensions (L x Dia mm) | 125x65 | 123x65 |



Please visit our website for a full list of compatible dimmers - www.megamanuk.com/products/dimming-compatibility

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Incanda
LED

Professional

LG4003.5dCS

3.5W
Incanda-LED Golf Ball Dimming

Features



The Incanda-LED range delivers a brilliant sparkling light effect with a unique lamp design that resembles that of an incandescent. The Incanda-LED range features a clear glass finish to enhance its sparkle, perfect for chandeliers and crystal light fittings.

Specification

| UK Order Code > | 148064 | 148751 | 148927 |
|-------------------------|-----------|-----------|-----------|
| Watts | 3.5W | 3.5W | 3.5W |
| Colour Temp (K) /CRI | 2800 / 80 | 2800 / 80 | 2800 / 80 |
| Lumens (lm) | 250 | 250 | 250 |
| Dimmable | Y | Y | Y |
| Lamp Base | E14 | E27 | B22 |
| Hrs Lamp Life (L70) | 50,000 | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 | 25,000 |
| Weight (g) | 32 | 31 | 30 |
| Dimensions (L x Dia mm) | 84x45 | 77x45 | 75x45 |



Please visit our website for a full list of compatible dimmers - www.megamanuk.com/products/dimming-compatibility

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Professional

LG5206w

6W
Golf Ball Dim to Warm

Features



The Dim to Warm range of Megaman LEDs emit a warmer light when they are dimmed, from 2700K to 1800K, simulating the same dimming characteristics of incandescent and halogen lamps.

Specification

| UK Order Code > | 148197 | 148209 | 148381 |
|-------------------------|----------------|----------------|----------------|
| Watts | 6W | 6W | 6W |
| Colour Temp (K) /CRI | 2700-1800 / 80 | 2700-1800 / 80 | 2700-1800 / 80 |
| Lumens (lm) | 470 | 470 | 470 |
| Dimmable | Y | Y | Y |
| Lamp Base | E14 | E27 | B22 |
| Hrs Lamp Life (L70) | 50,000 | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 | 25,000 |
| Weight (g) | 55 | 56 | 56 |
| Dimensions (L x Dia mm) | 80x45 | 80x45 | 78x45 |



Please visit our website for a full list of compatible dimmers - www.megamanuk.com/products/dimming-compatibility

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Professional

LS0303.5d

3.5W Crown Silver Golf Ball Dimming

Features



With a unique silver plated design, the Megaman LED Crown Silver delivers low-glare lighting. Perfect for mirror frame and decorative lighting.

Specification

| | |
|---------------------------|---------------|
| UK Order Code > | 148439 |
| Watts | 3.5W |
| Colour Temp (K) / CRI | 2800 / 80 |
| Dimmable | Y |
| Lamp Base | E14 |
| Hrs Lamp Life (L70) | 50,000 |
| Hrs Lamp Life (L90) | 25,000 |
| Weight (g) | 40 |
| Dimensions (L x Dia mm) | 84x45 |



Please visit our website for a full list of compatible dimmers - www.megamanuk.com/products/dimming-compatibility

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Professional

LS0405d

5W Crown Silver Dimming

Features



With a unique silver plated design, the Megaman LED Crown Silver delivers low-glare lighting. Perfect for mirror frame and decorative lighting.

Specification

| | |
|---------------------------|---------------|
| UK Order Code > | 148420 |
| Watts | 5W |
| Colour Temp (K) / CRI | 2800 / 80 |
| Dimmable | Y |
| Lamp Base | E27 |
| Hrs Lamp Life (L70) | 50,000 |
| Hrs Lamp Life (L90) | 25,000 |
| Weight (g) | 88 |
| Dimensions (L x Dia mm) | 104x55 |



Please visit our website for a full list of compatible dimmers - www.megamanuk.com/products/dimming-compatibility

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Professional

LS0505d-Brass

5W Crown Brass Dimming

Features



With a unique brass plated design, the Megaman LED Crown Brass delivers low-glare lighting. Perfect for mirror frame and decorative lighting.

Specification

| UK Order Code > | 148510 |
|-------------------------|-----------|
| Watts | 5W |
| Colour Temp (K) / CRI | 2800 / 80 |
| Dimmable | Y |
| Lamp Base | E27 |
| Hrs Lamp Life (L70) | 50,000 |
| Hrs Lamp Life (L90) | 25,000 |
| Weight (g) | 71 |
| Dimensions (L x Dia mm) | 107x60 |



Please visit our website for a full list of compatible dimmers - www.megamanuk.com/products/dimming-compatibility

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Professional

LTO409.5
LTO518
LTO622

9.5W/18W/22W LED Tube

Features



The Megaman LED Tube is compatible with traditional magnetic ballasts making it a perfect alternative to traditional T8 fluorescent tubes.

Requires use of starter replacement, and shouldn't usually require re-wiring.

Specification

| UK Order Code > | 174100 | 174104 | 174106 |
|-------------------------|-----------|-----------|-----------|
| Watts | 9.5W | 18W | 22W |
| Colour Temp (K) / CRI | 4000 / 80 | 4000 / 80 | 4000 / 80 |
| Lumens (lm) | 880 | 1750 | 2200 |
| Dimmable | N | N | N |
| Lamp Base | G13 | G13 | G13 |
| Hrs Lamp Life (L70) | 50,000 | 50,000 | 50,000 |
| Weight (g) | 140 | 265 | 320 |
| Dimensions (L x Dia mm) | 602x27.5 | 1212x27.5 | 1513x27.5 |

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C

MEGAMAN®

Economy Series

| | |
|-----------|-------|
| GU10 | 44-46 |
| R50 | 47 |
| R63 | 48 |
| R80 | 49 |
| PAR30s | 50 |
| PAR38 | 51 |
| GX53 | 52-53 |
| Candle | 54-55 |
| Classic | 56-61 |
| Golf Ball | 62 |
| Globe | 63 |
| 360° | 64-67 |
| G4 | 68 |
| G9 | 69 |
| Pygmy | 70 |
| Filament | 71-79 |

Value high performance lamps that come with a 2 year warranty.

The Megaman LED Economy Series is the perfect alternative to CFL lamps but with a greater lamp life of up to 25,000 hours and reduced power consumption. Perfect for consumers looking for high quality lighting at affordable prices.

The Economy Series features all of Megaman's most popular lamp shapes

all of which come with a generous 2 year warranty. This range of lamps is designed to enhance any lighting scenario at a lower cost than our LED Professional Series.

Included in the Economy Series is the popular range of LED filament lamps available in clear and gold finishes. Also new to the range is 360°

decorative lamps, with a carrier free design, capable of emitting light in all directions and similar in appearance to traditional incandescent lamps.





Economy

LR4604DG-WFL


4W
GU10

Features



PARI16 GU10, perfect for retrofit applications such as showrooms, reception areas, meeting rooms, offices, restaurants, lounges and kitchens.

141730/141732



Specification

| UK Order Code > | 141730 | 141732 |
|-------------------------|-----------|-----------|
| Watts | 4W | 4W |
| Colour Temp (K)/CRI | 2800 / 80 | 4000 / 80 |
| Lumens (lm) | 250 | 250 |
| Candelas (cd) | 500 | 500 |
| Dimmable | N | N |
| Lamp Base | GU10 | GU10 |
| Hrs Lamp Life (L70) | 25,000 | 25,000 |
| Beam Angle | 35° | 35° |
| Weight (g) | 25 | 25 |
| Dimensions (L x Dia mm) | 57x50 | 57x50 |

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Economy

LR4605dLN-WFL


5W
GU10 Dimming

Features



PARI16 GU10, perfect for retrofit applications such as showrooms, reception areas, meeting rooms, offices, restaurants, lounges and kitchens. This lamp features Megaman's new U-DIM™ Technology, offering an enhanced dimming range from 100% down to 5% with the widest range of dimmers, whether they are leading-edge or trailing-edge.

141322/141324



Specification

| UK Order Code > | 141322 | 141324 |
|-------------------------|-----------|-----------|
| Watts | 5W | 5W |
| Colour Temp (K)/CRI | 2800 / 82 | 4000 / 85 |
| Lumens (lm) | 360 | 360 |
| Candelas (cd) | 600 | 600 |
| Dimmable | Y | Y |
| Lamp Base | GU10 | GU10 |
| Hrs Lamp Life (L70) | 25,000 | 25,000 |
| Beam Angle | 40° | 40° |
| Weight (g) | 60 | 60 |
| Dimensions (L x Dia mm) | 55x50 | 55x50 |

Please visit our website for a full list of compatible dimmers - www.megamanuk.com/products/dimming-compatibility

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Economy

5W
GU10 Dimming 74mm


LR4505dDG-SWFL

Features



A 74mm long neck GU10 suitable for older fire rated fittings, replacing the Megaman 11W CFL GU10 Dimming.

141510/141580



Specification

| UK Order Code > | 141510 | 141580 |
|-------------------------|-----------|-----------|
| Watts | 5W | 5W |
| Colour Temp (K) /CRI | 2800 / 80 | 4000 / 80 |
| Lumens (lm) | 330 | 330 |
| Candelas (cd) | 160 | 160 |
| Dimmable | Y | Y |
| Lamp Base | GU10 | GU10 |
| Hrs Lamp Life (L70) | 25,000 | 25,000 |
| Beam Angle | 90° | 90° |
| Weight (g) | 45 | 45 |
| Dimensions (L x Dia mm) | 74x50 | 74x50 |

Please visit our website for a full list of compatible dimmers - www.megamanuk.com/products/dimming-compatibility

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Economy

3.5W
R50


LR2603.5-SWFL

Features



Ideal for general lighting fixtures, the Megaman R50 shares the same external profile as the traditional incandescent R50.

615973



Specification

| UK Order Code > | 615973 |
|-------------------------|-----------|
| Watts | 3.5W |
| Colour Temp (K) /CRI | 2800 / 80 |
| Lumens (lm) | 250 |
| Candelas (cd) | 120 |
| Dimmable | N |
| Lamp Base | E14 |
| Hrs Lamp Life (L70) | 15,000 |
| Beam Angle | 90° |
| Weight (g) | 33 |
| Dimensions (L x Dia mm) | 87x50 |

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Economy

7.5W
R63


LR2407.5-SWFL

Features



Designed to be a perfect replacement for the traditional incandescent R63 in size and shape.

616497



Specification

| UK Order Code > | 616497 |
|-------------------------|-----------|
| Watts | 7.5W |
| Colour Temp (K) /CRI | 2800 / 80 |
| Lumens (lm) | 600 |
| Candelas (cd) | 230 |
| Dimmable | N |
| Lamp Base | E27 |
| Hrs Lamp Life (L70) | 15,000 |
| Beam Angle | 90° |
| Weight (g) | 67 |
| Dimensions (L x Dia mm) | 103x63 |

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Economy

7W
R80


LR4307-SWFL

Features



Megaman's LED R80 reflector is an energy-saving ambient lighting solution to replace traditional incandescent lamps.

617249



Specification

| UK Order Code > | 617249 |
|-------------------------|-----------|
| Watts | 7W |
| Colour Temp (K) /CRI | 2800 / 80 |
| Lumens (lm) | 520 |
| Candelas (cd) | 230 |
| Dimmable | N |
| Lamp Base | E27 |
| Hrs Lamp Life (L70) | 15,000 |
| Beam Angle | 90° |
| Weight (g) | 90 |
| Dimensions (L x Dia mm) | 112x78 |

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Economy

10.5W PAR30s


LR3010.5-WFL

Features



Megaman's PAR30s is a direct replacement for the traditional halogen PAR30s in size and shape. With diffuser glass design, it delivers even light distribution.

141825/141846



Specification

| UK Order Code > | 141825 | 141846 |
|-------------------------|-----------|-----------|
| Watts | 10.5W | 10.5W |
| Colour Temp (K) /CRI | 2800 / 80 | 4000 / 80 |
| Lumens (lm) | 700 | 700 |
| Candelas (cd) | 850 | 850 |
| Dimmable | N | N |
| Lamp Base | E27 | E27 |
| Hrs Lamp Life (L70) | 15,000 | 15,000 |
| Beam Angle | 35° | 35° |
| Weight (g) | 103 | 103 |
| Dimensions (L x Dia mm) | 88x95 | 88x95 |

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Economy

15.5W PAR38


LR3215.5-WFL

Features



Megaman's PAR38, with diffuser glass design, is an economical solution with a water resistant outdoor feature that maintains the IP rating of the light fitting (up to a maximum of IP55)

141384/141386



Specification

| UK Order Code > | 141384 | 141386 |
|-------------------------|-----------|-----------|
| Watts | 15.5W | 15.5W |
| Colour Temp (K) /CRI | 2800 / 80 | 4000 / 80 |
| Lumens (lm) | 950 | 950 |
| Candelas (cd) | 1500 | 1500 |
| Dimmable | N | N |
| Lamp Base | E27 | E27 |
| Hrs Lamp Life (L70) | 15,000 | 15,000 |
| Beam Angle | 35° | 35° |
| Weight (g) | 204 | 204 |
| Dimensions (L x Dia mm) | 132x120 | 132x120 |

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Economy

LR2205

5W
GX53

Features



The slim profile lamp is designed for surface mounted and recessed cabinet lighting.

Specification

| UK Order Code > | 147365 | 147379 |
|-------------------------|-----------|-----------|
| Watts | 5W | 5W |
| Colour Temp (K) /CRI | 2800 / 80 | 4000 / 80 |
| Lumens (lm) | 300 | 300 |
| Dimmable | N | N |
| Lamp Base | GX53 | GX53 |
| Hrs Lamp Life (L70) | 15,000 | 15,000 |
| Weight (g) | 59 | 59 |
| Dimensions (L x Dia mm) | 24x75 | 24x75 |

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Economy

LR3307

7W
GX53

Features



The slim profile lamp is designed for surface mounted and recessed cabinet lighting.

Specification

| UK Order Code > | 147961 | 147534 |
|-------------------------|-----------|-----------|
| Watts | 7W | 7W |
| Colour Temp (K) /CRI | 2800 / 80 | 4000 / 80 |
| Lumens (lm) | 520 | 520 |
| Dimmable | N | N |
| Lamp Base | GX53 | GX53 |
| Hrs Lamp Life (L70) | 15,000 | 15,000 |
| Weight (g) | 91 | 91 |
| Dimensions (L x Dia mm) | 32x75 | 32x75 |

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Economy

LC0403.5v2

3.5W Opal Candle

Features



Megaman's LED opal candle is suitable for a wide variety of applications such as chandeliers, wall lights and other decorative fittings. The new lamp has an even light distribution with 330° illumination.

Specification

| UK Order Code > | 143300 | 143302 | 143304 | 143306 |
|-------------------------|-----------|-----------|-----------|-----------|
| Watts | 3.5W | 3.5W | 3.5W | 3.5W |
| Colour Temp (K) /CRI | 2800 / 80 | 2800 / 80 | 2800 / 80 | 2800 / 80 |
| Lumens (lm) | 250 | 250 | 250 | 250 |
| Dimmable | N | N | N | N |
| Lamp Base | E14 | E27 | B15 | B22 |
| Hrs Lamp Life (L70) | 15,000 | 15,000 | 15,000 | 15,000 |
| Weight (g) | 23 | 25 | 25 | 25 |
| Dimensions (L x Dia mm) | 100x35 | 98x35 | 98x35 | 96x35 |



Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Economy

LC0405.5

5.5W Opal Candle

Features



Megaman's LED opal candle is suitable for a wide variety of applications such as chandeliers and decorative fittings. The new lamp has an even light distribution with 330° illumination.


Also available in 4000K for a cooler appearance.

Specification

| UK Order Code > | 143308 | 143310 | 143312 | 143314 |
|-------------------------|-----------|-----------|-----------|-----------|
| Watts | 5.5W | 5.5W | 5.5W | 5.5W |
| Colour Temp (K) /CRI | 2800 / 80 | 2800 / 80 | 2800 / 80 | 2800 / 80 |
| Lumens (lm) | 470 | 470 | 470 | 470 |
| Dimmable | N | N | N | N |
| Lamp Base | E14 | E27 | B15 | B22 |
| Hrs Lamp Life (L70) | 15,000 | 15,000 | 15,000 | 15,000 |
| Weight (g) | 30 | 33 | 30 | 33 |
| Dimensions (L x Dia mm) | 100x35 | 102x35 | 98x35 | 100x35 |

5.5W Opal Candle - 4000K (Note, all other spec is the same as the 2800K model.)

| UK Order Code > | 143350 | 143352 | 143354 | 143356 |
|----------------------|-----------|-----------|-----------|-----------|
| Colour Temp (K) /CRI | 4000 / 80 | 4000 / 80 | 4000 / 80 | 4000 / 80 |



Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Economy

LG7105.5

5.5W Opal Classic


Features



The Megaman LED Classic has an intelligent heat sink design for sleek classic shape. The lamp has even light distribution with 330° illumination.

Specification

| UK Order Code > | 143360 | 143362 |
|-------------------------|-----------|-----------|
| Watts | 5.5W | 5.5W |
| Colour Temp (K) /CRI | 2800 / 80 | 2800 / 80 |
| Lumens (lm) | 470 | 470 |
| Dimmable | N | N |
| Lamp Base | E27 | B22 |
| Hrs Lamp Life (L70) | 15,000 | 15,000 |
| Weight (g) | 42 | 47 |
| Dimensions (L x Dia mm) | 109x60 | 108x60 |



Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Economy

LG7209.5

9.5W Opal Classic

Features



The Megaman LED Classic has an intelligent heat sink design for sleek classic shape. The lamp has even light distribution with 330° illumination.

Now available in 4000K and 6500K colour variants. Daylight lamps are perfect for crafting and art use.

Specification

| UK Order Code > | 143316 | 143318 | 143372 | 143370 | 143374 | 143376 |
|-------------------------|-----------|-----------|-----------|-----------|-----------|-----------|
| Watts | 9.5W | 9.5W | 9.5W | 9.5W | 9.5W | 9.5W |
| Colour Temp (K) /CRI | 2800 / 80 | 2800 / 80 | 4000 / 80 | 4000 / 80 | 6500 / 80 | 6500 / 80 |
| Lumens (lm) | 810 | 810 | 810 | 810 | 810 | 810 |
| Dimmable | N | N | N | N | N | N |
| Lamp Base | E27 | B22 | E27 | B22 | E27 | B22 |
| Hrs Lamp Life (L70) | 15,000 | 15,000 | 15,000 | 15,000 | 15,000 | 15,000 |
| Weight (g) | 55 | 54 | 55 | 54 | 55 | 54 |
| Dimensions (L x Dia mm) | 112x60 | 110x60 | 112x60 | 110x60 | 112x60 | 110x60 |



Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Economy

LG7311

11W Opal Classic


Features



The Megaman LED Classic has an intelligent heat sink design for sleek classic shape. The lamp has even light distribution with 330° illumination.

Specification

| UK Order Code > | 143320 | 143322 |
|-------------------------|-----------|-----------|
| Watts | 11W | 11W |
| Colour Temp (K) /CRI | 2800 / 80 | 2800 / 80 |
| Lumens (lm) | 1055 | 1055 |
| Dimmable | N | N |
| Lamp Base | E27 | B22 |
| Hrs Lamp Life (L70) | 15,000 | 15,000 |
| Weight (g) | 67 | 67 |
| Dimensions (L x Dia mm) | 117x60 | 115x60 |



Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Economy

LG7414

14W Opal Classic

Features



The Megaman LED Classic has an intelligent heat sink design for sleek classic shape and compact housing, perfect for domestic applications.

Specification

| UK Order Code > | 148378 | 148380 |
|-------------------------|-----------|-----------|
| Watts | 14W | 14W |
| Colour Temp (K) /CRI | 2800 / 80 | 2800 / 80 |
| Lumens (lm) | 1521 | 1521 |
| Dimmable | N | N |
| Lamp Base | E27 | B22 |
| Hrs Lamp Life (L70) | 15,000 | 15,000 |
| Weight (g) | 91 | 86 |
| Dimensions (L x Dia mm) | 131x70 | 129x70 |



Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Economy
8W
Sensor Light

LG2108r

Features



Megaman's LED Sensor Light, with improved lumen output, automatically lights up in darkness and turns itself off when light is ample. Perfect for outdoor lamp fittings.

Specification

| UK Order Code > | 148463 |
|-------------------------|-----------|
| Watts | 8W |
| Colour Temp (K) / CRI | 2800 / 80 |
| Lumens (lm) | 600 |
| Dimmable | N |
| Lamp Base | E27 |
| Hrs Lamp Life (L70) | 15,000 |
| Weight (g) | 66 |
| Dimensions (L x Dia mm) | 115x60 |



Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Economy
10.5W
Opal Classic Shatterproof

LG7310.5d

Features



The Megaman shatterproof LED range features a polycarbonate cover and is the perfect solution for applications where glass covered lamps are not a suitable option.

Specification

| UK Order Code > | 148609 | 148608 |
|-------------------------|-----------|-----------|
| Watts | 10.5W | 10.5W |
| Colour Temp (K) / CRI | 2800 / 80 | 2800 / 80 |
| Lumens (lm) | 810 | 810 |
| Dimmable | Y | Y |
| Lamp Base | E27 | B22 |
| Hrs Lamp Life (L70) | 25,000 | 25,000 |
| Weight (g) | 105 | 110 |
| Dimensions (L x Dia mm) | 117x60 | 115x60 |



Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +30°C



Economy

LG2603.5v2
LG2605.5

3.5W Opal Golf Ball

Features



The Megaman LED Golf Ball delivers an even light distribution and traditional feel. Ideal for a variety of general lighting applications.

Specification

| UK Order Code > | 143390 | 143392 | 143394 | 148623 (NEW) | 148624 (NEW) |
|-------------------------|-----------|-----------|-----------|--------------|--------------|
| Watts | 3.5W | 3.5W | 3.5W | 5.5W | 5.5W |
| Colour Temp (K) /CRI | 2800 / 80 | 2800 / 80 | 2800 / 80 | 2800 / 80 | 4000 / 80 |
| Lumens (lm) | 250 | 250 | 250 | 470 | 470 |
| Dimmable | N | N | N | N | N |
| Lamp Base | E14 | E27 | B22 | E27 | E27 |
| Hrs Lamp Life (L70) | 15,000 | 15,000 | 15,000 | 15,000 | 15,000 |
| Weight (g) | 22 | 23 | 23 | 31 | 31 |
| Dimensions (L x Dia mm) | 84x45 | 77x45 | 75x45 | 77x45 | 75x45 |



Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Economy

LG7714

14W Opal Globe

Features



The Megaman LED Globe has an intelligent heat sink design for sleek globe shape. The lamp has even light distribution with 330° illumination.

Specification

| UK Order Code > | 143380 | 143382 | 143384 |
|-------------------------|-----------|-----------|-----------|
| Watts | 14W | 14W | 14W |
| Colour Temp (K) /CRI | 2800 / 80 | 4000 / 80 | 6500 / 80 |
| Lumens (lm) | 1521 | 1521 | 1521 |
| Dimmable | N | N | N |
| Lamp Base | E27 | E27 | E27 |
| Hrs Lamp Life (L70) | 15,000 | 15,000 | 15,000 |
| Weight (g) | 160 | 160 | 160 |
| Dimensions (L x Dia mm) | 155x120 | 155x120 | 155x120 |



Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Economy LC2003

3W 360° Candle


Features



Our new range of LED 360° illumination decorative lamps have a carrier free design and provide a smooth and sleek finish capable of emitting light in all directions to give the same classic look as incandescent lamps.

Specification

| UK Order Code > | 144400 | 144402 | 144404 | 144406 |
|-------------------------|-----------|-----------|-----------|-----------|
| Watts | 3W | 3W | 3W | 3W |
| Colour Temp (K)/CRI | 2800 / 80 | 4000 / 80 | 2800 / 80 | 4000 / 80 |
| Lumens (lm) | 250 | 250 | 250 | 250 |
| Dimmable | N | N | N | N |
| Lamp Base | E14 | E14 | E27 | E27 |
| Hrs Lamp Life (L70) | 15,000 | 15,000 | 15,000 | 15,000 |
| Weight (g) | 16 | 16 | 25 | 25 |
| Dimensions (L x Dia mm) | 98x35 | 98x35 | 96x35 | 96x35 |



Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Economy LG7903

3W 360° Golf Ball


Features



Our new range of LED 360° illumination decorative lamps have a carrier free design and provide a smooth and sleek finish capable of emitting light in all directions to give the same classic look as incandescent lamps.

Specification

| UK Order Code > | 144408 | 144410 | 144412 | 144414 |
|-------------------------|-----------|-----------|-----------|-----------|
| Watts | 3W | 3W | 3W | 3W |
| Colour Temp (K)/CRI | 2800 / 80 | 4000 / 80 | 2800 / 80 | 4000 / 80 |
| Lumens (lm) | 250 | 250 | 250 | 250 |
| Dimmable | N | N | N | N |
| Lamp Base | E14 | E14 | E27 | E27 |
| Hrs Lamp Life (L70) | 15,000 | 15,000 | 15,000 | 15,000 |
| Weight (g) | 14 | 14 | 21 | 21 |
| Dimensions (L x Dia mm) | 72x45 | 72x45 | 67x45 | 67x45 |



Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Economy

LG8005.5

5.5W
360° Classic

Features



Our new range of LED 360° illumination decorative lamps have an ultra compact carrier design and provide a smooth and sleek finish capable of emitting light in all directions to give the same classic look as incandescent lamps.

Specification

| UK Order Code > | 144416 | 144418 |
|-------------------------|-----------|-----------|
| Watts | 5.5W | 5.5W |
| Colour Temp (K) /CRI | 2800 / 80 | 4000 / 80 |
| Lumens (lm) | 470 | 470 |
| Dimmable | N | N |
| Lamp Base | E27 | E27 |
| Hrs Lamp Life (L70) | 15,000 | 15,000 |
| Weight (g) | 54 | 54 |
| Dimensions (L x Dia mm) | 108x60 | 108x60 |



Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Economy

LG8008.5

8.5W
360° Classic

Features



Our new range of LED 360° illumination decorative lamps have an ultra compact carrier design and provide a smooth and sleek finish capable of emitting light in all directions to give the same classic look as incandescent lamps.

Specification

| UK Order Code > | 144420 | 144422 |
|-------------------------|-----------|-----------|
| Watts | 8.5W | 8.5W |
| Colour Temp (K) /CRI | 2800 / 80 | 4000 / 80 |
| Lumens (lm) | 810 | 810 |
| Dimmable | N | N |
| Lamp Base | E27 | E27 |
| Hrs Lamp Life (L70) | 15,000 | 15,000 |
| Weight (g) | 82 | 82 |
| Dimensions (L x Dia mm) | 108x60 | 108x60 |



Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Economy

EU0401.8

1.8W
G4
12V

Features



Megaman's latest G4 LED lamp is now even smaller, which means it is now suitable for even more decorative fittings. Utilising revolutionary back to back mounted LED chips, meaning it performs exactly the same as the halogen lamp it was designed to replace.

Specification

| | |
|---------------------------|---------------|
| UK Order Code > | 142950 |
| Watts | 1.8W |
| Colour Temp (K) / CRI | 2800 / 80 |
| Lumens (lm) | 180 |
| Dimmable | N |
| Lamp Base | G4 |
| Hrs Lamp Life (L70) | 15,000 |
| Weight (g) | 2 |
| Dimensions (L x Dia mm) | 37x10 |

Please visit our website for a full list of compatible transformers.

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Economy

LU0702

2W
G9

Features



Megaman's latest G9 LED lamp is now even smaller. The 19mm lamp width means it will fit easily within most decorative fittings. Utilising revolutionary back to back mounted LED chips, meaning it performs exactly the same as the halogen lamp it was designed to replace.

Specification

| | |
|---------------------------|---------------|
| UK Order Code > | 142400 |
| Watts | 2W |
| Colour Temp (K) / CRI | 2800 / 80 |
| Lumens (lm) | 180 |
| Dimmable | N |
| Lamp Base | GU9 |
| Hrs Lamp Life (L70) | 15,000 |
| Weight (g) | 7 |
| Dimensions (L x Dia mm) | 43x19 |

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Economy

LG5502

2W Opal Pygmy

Features



The Megaman LED Pygmy consumes at least 88% less energy than its incandescent counterpart. Designed to withstand low temperatures, the Pygmy is an ideal light source for domestic refrigerators.

Specification

| | |
|---------------------------|---------------|
| UK Order Code > | 141439 |
| Watts | 2W |
| Colour Temp (K) / CRI | 2800 / 80 |
| Lumens (lm) | 145 |
| Dimmable | N |
| Lamp Base | E14 |
| Hrs Lamp Life (L70) | 15,000 |
| Weight (g) | 15 |
| Dimensions (L x Dia mm) | 57x26 |



Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Economy

LC2204TP

4W Filament Flame Tip Candle

Features



The Megaman LED filament range is designed for decorative light fittings, to create a charming and stunning visual effect when an exposed lamp is required.

Specification

| | |
|---------------------------|---------------|
| UK Order Code > | 143921 |
| Watts | 4W |
| Colour Temp (K) / CRI | 2700 / 80 |
| Lumens (lm) | 400 |
| Dimmable | N |
| Lamp Base | E14 |
| Hrs Lamp Life (L70) | 15,000 |
| Weight (g) | 14 |
| Dimensions (L x Dia mm) | 118x35 |



Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Economy

LC1403CS

3W Filament Candle


Features



The Megaman LED filament range is designed for decorative light fittings, to create a charming and stunning visual effect.

Specification

| UK Order Code > | 143175 | 143264 | 143753 | 143919 |
|-------------------------|-----------|-----------|-----------|-----------|
| Watts | 3W | 3W | 3W | 3W |
| Colour Temp (K) /CRI | 2700 / 80 | 2700 / 80 | 2700 / 80 | 2700 / 80 |
| Lumens (lm) | 250 | 250 | 250 | 250 |
| Dimmable | N | N | N | N |
| Lamp Base | E14 | E27 | B15 | B22 |
| Hrs Lamp Life (L70) | 15,000 | 15,000 | 15,000 | 15,000 |
| Weight (g) | 16 | 16 | 14 | 16 |
| Dimensions (L x Dia mm) | 101x35 | 98x35 | 100x35 | 98x35 |



Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Economy

LC1503.2dCS

3.2W Filament Candle Dimming

Features




The Megaman LED filament range is designed for decorative light fittings, to create a charming and stunning visual effect.

Specification

| UK Order Code > | 143424 | 143507 | 143641 | 143764 |
|-------------------------|-----------|-----------|-----------|-----------|
| Watts | 3.2W | 3.2W | 3.2W | 3.2W |
| Colour Temp (K) /CRI | 2700 / 80 | 2700 / 80 | 2700 / 80 | 2700 / 80 |
| Lumens (lm) | 220 | 220 | 220 | 220 |
| Dimmable | Y | Y | Y | Y |
| Lamp Base | E14 | E27 | B15 | B22 |
| Hrs Lamp Life (L70) | 15,000 | 15,000 | 15,000 | 15,000 |
| Weight (g) | 30 | 32 | 30 | 32 |
| Dimensions (L x Dia mm) | 121x35 | 113x35 | 118x36 | 113x35 |

Please visit our website for a full list of compatible dimmers - www.megamanuk.com/products/dimming-compatibility



| UK Order Code > | 143150 | 143151 | 143168 | 143169 |
|-----------------|---------|---------|---------|---------|
| Colour/Finish | Silver | Silver | Gold | Gold |
| For Lamp Base | E14/B15 | E27/B22 | E14/B15 | E27/B22 |



Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Economy

LG6104.8CS

5W Filament Classic

Features



The Megaman LED filament range is designed for decorative light fittings, to create a charming and stunning visual effect.

Specification

| UK Order Code > | 146201 | 146376 |
|-------------------------|-----------|-----------|
| Watts | 5W | 5W |
| Colour Temp (K) /CRI | 2700 / 80 | 2700 / 80 |
| Lumens (lm) | 470 | 470 |
| Dimmable | N | N |
| Lamp Base | E27 | B22 |
| Hrs Lamp Life (L70) | 15,000 | 15,000 |
| Weight (g) | 31 | 31 |
| Dimensions (L x Dia mm) | 103x60 | 101x60 |



Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Economy

LG6205.5dCS

5.5W Filament Classic Dimming

Features



The Megaman LED filament range is designed for decorative light fittings, to create a charming and stunning visual effect.


Specification

| UK Order Code > | 146520 | 146731 |
|-------------------------|-----------|-----------|
| Watts | 5.5W | 5.5W |
| Colour Temp (K) /CRI | 2700 / 80 | 2700 / 80 |
| Lumens (lm) | 470 | 470 |
| Dimmable | Y | Y |
| Lamp Base | E27 | B22 |
| Hrs Lamp Life (L70) | 15,000 | 15,000 |
| Weight (g) | 47 | 47 |
| Dimensions (L x Dia mm) | 120x60 | 118x60 |



Please visit our website for a full list of compatible dimmers - www.megamanuk.com/products/dimming-compatibility

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Economy LG6303dGD


3W Gold Filament Classic Dimming



The Megaman Gold Filament LED range is designed with a 2200K colour temperature to provide an extra warm illumination perfect for creating mood lighting. This new trendy decorative lamp range is perfect for restaurant and bar applications.


Specification

| UK Order Code > | 146109 | 146138 |
|-------------------------|-----------|-----------|
| Watts | 3W | 3W |
| Colour Temp (K) /CRI | 2200 / 80 | 2200 / 80 |
| Lumens (lm) | 210 | 210 |
| Dimmable | Y | Y |
| Lamp Base | E27 | B22 |
| Hrs Lamp Life (L70) | 15,000 | 15,000 |
| Weight (g) | 60 | 65 |
| Dimensions (L x Dia mm) | 156x75 | 154x75 |



Please visit our website for a full list of compatible dimmers - www.megamanuk.com/products/dimming-compatibility

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Economy LG6403dGD

3W Gold Filament Globe Dimming, 95mm



The Megaman Gold Filament LED range is designed with a 2200K colour temperature to provide an extra warm illumination perfect for creating mood lighting. This new trendy decorative lamp range is perfect for restaurant and bar applications.

Specification

| UK Order Code > | 146249 | 146267 |
|-------------------------|-----------|-----------|
| Watts | 3W | 3W |
| Colour Temp (K) /CRI | 2200 / 80 | 2200 / 80 |
| Lumens (lm) | 210 | 210 |
| Dimmable | Y | Y |
| Lamp Base | E27 | B22 |
| Hrs Lamp Life (L70) | 15,000 | 15,000 |
| Weight (g) | 71 | 76 |
| Dimensions (L x Dia mm) | 159x95 | 157x95 |



Please visit our website for a full list of compatible dimmers - www.megamanuk.com/products/dimming-compatibility

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Economy

LG6503dGD

3W Gold Filament Globe Dimming, 125mm


Features



The Megaman Gold Filament LED range is designed with a 2200K colour temperature to provide an extra warm illumination perfect for creating mood lighting. This new trendy decorative lamp range is perfect for restaurant and bar applications.


Specification

| UK Order Code > | 146314 | 146394 |
|-------------------------|-----------|-----------|
| Watts | 3W | 3W |
| Colour Temp (K) /CRI | 2200 / 80 | 2200 / 80 |
| Lumens (lm) | 210 | 210 |
| Dimmable | Y | Y |
| Lamp Base | E27 | B22 |
| Hrs Lamp Life (L70) | 15,000 | 15,000 |
| Weight (g) | 118 | 123 |
| Dimensions (L x Dia mm) | 196x125 | 194x125 |



Please visit our website for a full list of compatible dimmers – www.megamanuk.com/products/dimming-compatibility

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C



Economy

LG6603dGD

3W Gold Filament ST58 Dimming

Features



The Megaman Gold Filament LED range is designed with a 2200K colour temperature to provide an extra warm illumination perfect for creating mood lighting. This new trendy decorative lamp range is perfect for restaurant and bar applications.

Specification

| UK Order Code > | 146409 | 146482 |
|-------------------------|-----------|-----------|
| Watts | 3W | 3W |
| Colour Temp (K) /CRI | 2200 / 80 | 2200 / 80 |
| Lumens (lm) | 210 | 210 |
| Dimmable | Y | Y |
| Lamp Base | E27 | B22 |
| Hrs Lamp Life (L70) | 15,000 | 15,000 |
| Weight (g) | 55 | 55 |
| Dimensions (L x Dia mm) | 152x58 | 150x58 |



Please visit our website for a full list of compatible dimmers – www.megamanuk.com/products/dimming-compatibility

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -30°C to +40°C

MEGAMAN®

Tubes

| | |
|------------------|-------|
| LED Clusterlite® | 82 |
| CFL Tubes | 83-85 |

Liquid mercury-free, outstanding quality and performance.

Clusterlite® LED

Megaman's LED Clusterlite® is designed to replace mercury tungsten halogen and metal halide lamps. This range of lamps offers fantastic illumination for large scale commercial and industrial applications and comes with shatterproof finishing, protecting the user from broken glass and other components, also free of harmful UV.

Megaman Clusterlite® LED's have instant start and hot re-strike capabilities, and due to their cluster-type lamp tube design allows continuous illumination upon partial failure of lamp tubes.

CFL

Megaman CFL lamps are recognised for outstanding quality and performance, achieved through the use of premium quality materials and innovative technologies. Our CFL tube lamps contain a patented *INGENIUM*® technology which prolongs lamps life up to 8,000 hours, extends switching cycles up to 600,000 times and has a preheating time of under 1 second.





LED Clusterlite®

27/33/35W
LED Clusterlite®

LH0127
LH0133
LH0135

Features



Megaman's Clusterlite offers impressive lumen output, making it the perfect replacement for metal halide lamps. Immense illumination output for large-scale commercial and industrial applications, such as bus and train terminals, exhibition halls, shopping centres, factories and warehouses.

Specification

| UK Order Code > | 804602 | 804606 (NEW) | 804604 |
|-------------------------|-----------|--------------|-----------|
| Watts | 27W | 33W | 35W |
| Colour Temp (K) /CRI | 4000 / 80 | 4000 / 80 | 4000 / 80 |
| Lumens (lm) | 2800 | 5000 | 4000 |
| Dimmable | N | N | N |
| Lamp Base | E27 | E27 | E27 |
| Hrs Lamp Life (L70) | 50,000 | 50,000 | 50,000 |
| Weight (g) | 306 | 306 | 306 |
| Dimensions (L x Dia mm) | 188x63 | 188x63 | 188x63 |

Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -10°C to +30°C



CFL

11W
Tube

3P411

Features



Megaman CFL Tubes offer an economical lighting solution and are cost-effective in terms of energy usage and illumination intensity.

Specification

| UK Order Code > | 231729 | 231522 |
|-------------------------|-----------|-----------|
| Watts | 11W | 11W |
| Colour Temp (K) /CRI | 2700 / 80 | 2700 / 80 |
| Lumens (lm) | 600 | 600 |
| Dimmable | N | N |
| Lamp Base | E27 | B22 |
| Hrs Lamp Life (L70) | 8,000 | 8,000 |
| Weight (g) | 58 | 56 |
| Dimensions (L x Dia mm) | 122x44 | 119x44 |



Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -10°C to +40°C



CFL

3P414

14W Tube


Features



Megaman CFL Tubes offer an economical lighting solution and are cost-effective in terms of energy usage and illumination intensity.

Specification

| UK Order Code > | 231454 | 231215 |
|-------------------------|-----------|-----------|
| Watts | 14W | 14W |
| Colour Temp (K) /CRI | 2700 / 80 | 2700 / 80 |
| Lumens (lm) | 800 | 800 |
| Dimmable | N | N |
| Lamp Base | E27 | B22 |
| Hrs Lamp Life (L70) | 8,000 | 8,000 |
| Weight (g) | 64 | 62 |
| Dimensions (L x Dia mm) | 137x44 | 134x44 |



Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -10°C to +40°C



CFL

3U120

20W Tube

Features



Megaman CFL Tubes offer an economical lighting solution and are cost-effective in terms of energy usage and illumination intensity.

Specification

| UK Order Code > | 231278 | 231291 |
|-------------------------|-----------|-----------|
| Watts | 20W | 20W |
| Colour Temp (K) /CRI | 2700 / 80 | 2700 / 80 |
| Lumens (lm) | 1151 | 1151 |
| Dimmable | N | N |
| Lamp Base | E27 | B22 |
| Hrs Lamp Life (L70) | 8,000 | 8,000 |
| Weight (g) | 91 | 91 |
| Dimensions (L x Dia mm) | 132x49 | 130x49 |



Specification at a glance...



* We test our lamps to both L70 and L90 standards. Figure shown is for L70. Operating temperature -10°C to +40°C

MEGAMAN®

Fixtures

| | |
|----------------------------|---------|
| LED Batten | 88-89 |
| LED Bulkhead | 90-92 |
| LED Floodlight | 93 |
| LED Louvre | 94-95 |
| LED Panel | 96-98 |
| LED Downlight | 99-123 |
| LED High-Bay | 124-125 |
| LED TECOH® Downlight | 126-131 |
| LED TECOH® Floodlight | 132 |
| Fixture only Downlight | 133-140 |
| Fixture only Tracklight | 141-143 |
| LED TECOH® Tracklight | 144-146 |
| Track System | 147-148 |

An expanding and comprehensive range of fixtures and integrated LED luminaires.

Megaman now offers a full spectrum of fixtures for applications such as retail, hotels, restaurants, homes and offices.

Megaman's extensive range of interior and exterior light fittings are designed around LED low energy lighting.

We aim to promote energy efficiency whilst delivering high performance lighting effects in commercial and residential applications.

Whether you are looking for recessed downlights for general lighting, track lights for spot lighting or vandal

resistant battens and bulkheads for outdoor lighting, we have the right product mix for you to fulfil your ever demanding lighting needs.



Fixtures



Dino Integrated LED Batten

F50000SM
F50100SMv1
F50300SMv1
F50100SM
F50300SM
F50200SM
F50400SM

Features




The Megaman Dino is a superior, modern linear light fitting ideally suited to car parks, walkways and corridors. The time-adjustable PIR sensor model reduces the light output to 10% when there is no movement detected to save energy, while still maintaining a basic health and safety approved light level. Additional installation accessories sold separately - **Security D-Brackets (190738)** and **Suspension Clips (Wire Type Monkey Puzzle) (190740)**.


Specification

| UK Order Code > | 190191 | 190291 | 190386 | 190194 High Output | 190197 High Output | 190591 PIR Sensor | 190731 PIR Sensor |
|-----------------------|-----------|-----------|-----------|-----------------------|-----------------------|----------------------|----------------------|
| Watts | 19.5W | 22.5W | 35W | 41.5W | 63W | 41.5W | 63W |
| Colour Temp (K) /CRI | 4000 / 80 | 4000 / 80 | 4000 / 80 | 4000 / 80 | 4000 / 80 | 4000 / 80 | 4000 / 80 |
| Lumens (lm) | 1800 | 2350 | 3600 | 4300 | 6500 | 4300 | 6500 |
| Candelas (cd) | 410 | 550 | 780 | 1000 | 1400 | 1000 | 1400 |
| Dimmable | N | N | N | N | N | N | N |
| Hrs Lamp Life (L70) | 50,000 | 50,000 | 50,000 | 50,000 | 50,000 | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 | 25,000 | 25,000 | 25,000 | 25,000 | 25,000 |
| Beam Angle | 120° | 120° | 120° | 120° | 120° | 120° | 120° |
| Weight (g) | 663 | 1079 | 1243 | 1103 | 1283 | 1116 | 1296 |
| Dimensions (L x D mm) | 700x66 | 1300x66 | 1600x66 | 1300x66 | 1600x66 | 1300x66 | 1600x66 |


190191




190291




190386




190194/190591



190197/190731



Dimensions...



Operating temperature -30°C to +40°C

Dino 2
Available late 2016.
Call sales for more info

NEW!
EXPANDING OUR FIXTURES RANGE EVEN FURTHER.



Fixtures

Dino 2 Integrated LED Batten

F60900SM
F61000SM
F61100SM
F61000SMv1
F61100SMv1

Features




The new Dino 2 LED Batten now has a clear prismatic diffuser and wide beam angle of 160° for wider light distribution and a higher uniformity of light. The Dino 2 also has a thinner end cap to Dino, with the option to install an end cap accessory to conceal power cables. End cap cover sold separately. **Available late 2016.**

Specification


| UK Order Code > | 190781 | 190782 | 190783 | 190784 | 190785 |
|-----------------------|--------|---------|---------|---------|---------|
| Watts | 19.5W | 22.5W | 35W | 41.5W | 63W |
| Colour Temp (K) /CRI | 4000K | 4000K | 4000K | 4000K | 4000K |
| Lumens (lm) | 1800 | 2350 | 3600 | 4300 | 6500 |
| Candelas (cd) | 460 | 620 | 900 | 1200 | 1600 |
| Dimmable | N | N | N | N | N |
| Hrs Lamp Life (L70) | 50,000 | 50,000 | 50,000 | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 | 25,000 | 25,000 | 25,000 |
| Beam Angle | 160° | 160° | 160° | 160° | 160° |
| Weight (g) | 679 | 1194 | 1571 | 1307 | 1627 |
| Dimensions (L x D mm) | 672x62 | 1272x62 | 1572x62 | 1272x62 | 1572x62 |

Ease of installation




VS

Conventional Waterproof Batten



Dimensions...



Operating temperature -30°C to +40°C



Fixtures

F51300SM


10.5W Fonda Integrated LED Bulkhead - Oval

Features



The Megaman Fonda is a tough and stylish new integrated outdoor LED fitting from Megaman, that offers modern styling and low glare.


180317



Specification

| UK Order Code > | 180317 |
|-----------------------|------------|
| Watts | 10.5W |
| Colour Temp (K) / CRI | 4000 / 80 |
| Lumens (lm) | 800 |
| Candelas (cd) | 320 |
| Dimmable | N |
| Hrs Lamp Life (L70) | 50,000 |
| Hrs Lamp Life (L90) | 25,000 |
| Beam Angle | 110° |
| Weight (g) | 728 |
| Dimensions (LxWxD mm) | 328x235x91 |
| Colour/Finish | Silver |
| Shape | Oval |

Dimensions...



Operating temperature -30°C to +40°C



Fixtures

F51100SM


10.5W Fonda Integrated LED Bulkhead - Round

Features



The Megaman Fonda is a tough and stylish new integrated outdoor LED fitting from Megaman, that offers modern styling and low glare.


180309/180312/180314




Specification

| UK Order Code > | 180309 | 180314 | 180312 |
|-----------------------|------------|------------|------------|
| Watts | 10.5W | 10.5W | 10.5W |
| Colour Temp (K) / CRI | 4000 / 80 | 3000 / 80 | 4000 / 80 |
| Lumens (lm) | 800 | 800 | 800 |
| Candelas (cd) | 320 | 320 | 320 |
| Dimmable | N | N | N |
| Hrs Lamp Life (L70) | 50,000 | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 | 25,000 |
| Beam Angle | 110° | 110° | 110° |
| Weight (g) | 745 | 745 | 745 |
| Dimensions (LxWxD mm) | 298x298x91 | 298x298x91 | 298x298x91 |
| Colour/Finish | White | Black | Black |
| Shape | Round | Round | Round |

Dimensions...



Operating temperature -30°C to +40°C



Fixtures

Renzo Integrated LED Bulkhead


F50500SM +IP44
F50600SM +IP44
F50500SM-r +IP44
F50700SM +IP44
F50700SM-r +IP44

Features




The Megaman Renzo indoor fixture is an integrated, surface mounted, LED bulkhead and a perfect alternative to wall-mounted compact fluorescent luminaires. The opal diffuser delivers an evenly distributed lighting effect. Also available with a built in microwave motion sensor.


180160



180167/180169




180240/180283



Specification

| UK Order Code > | 180160 | 180167 | 180169 Sensor | 180240 | 180283 Sensor |
|-----------------------|-------------|-------------|------------------|-------------|------------------|
| Watts | 10.5W | 14.5W | 15.5W | 18.5W | 19.5W |
| Colour Temp (K) /CRI | 4000 / 80 | 4000 / 80 | 4000 / 80 | 4000 / 80 | 4000 / 80 |
| Lumens (lm) | 800 | 1100 | 1100 | 1400 | 1400 |
| Candelas (cd) | 250 | 320 | 320 | 450 | 450 |
| Dimmable | N | N | N | N | N |
| Hrs Lamp Life (L70) | 50,000 | 50,000 | 50,000 | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 | 25,000 | 25,000 | 25,000 |
| Beam Angle | 110° | 110° | 110° | 110° | 110° |
| Weight (g) | 374 | 560 | 570 | 700 | 770 |
| Dimensions (LxWxD mm) | 280x280x100 | 340x340x105 | 340x340x105 | 390x390x110 | 390x390x110 |
| Colour/Finish | White | White | White | White | White |
| Shape | Round | Round | Round | Round | Round |

Dimensions...



Operating temperature -30°C to +40°C



Fixtures

29.5W Kara Integrated LED Tilt Floodlight


F51800RC

Features



The Megaman Kara integrated LED floodlight delivers excellent lighting performance. The fully adjustable tilting head allows for flexibility in applications such as retail cabinet and window displays. Non dimming driver included.


180408/180419



Specification

| UK Order Code > | 180408 | 180419 |
|------------------------|-------------|-------------|
| Watts | 29.5W | 29.5W |
| Colour Temp (K) /CRI | 3000 / 80 | 4000 / 80 |
| Lumens (lm) | 2200 | 2400 |
| Candelas (cd) | 1200 | 1200 |
| Dimmable | N | N |
| Hrs Lamp Life (L70) | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 |
| Beam Angle | 100° | 100° |
| Weight (g) | 1185 | 1185 |
| Dimensions (LxWxD mm) | 228x138x113 | 228x138x113 |
| Colour/Finish | White | White |
| Hole Cut-Out (mm) | 220x130 | 220x130 |
| Min Ceiling Depth (mm) | 123 | 123 |
| Tilt Angle | 65° | 65° |

Dimensions...




Operating temperature -30°C to +40°C

Estela
Available late 2016.
Call sales for more info

NEW!
EXPANDING OUR FIXTURES RANGE EVEN FURTHER.

Estela
Available late 2016.
Call sales for more info

NEW!
EXPANDING OUR FIXTURES RANGE EVEN FURTHER.




Fixtures

F62400RC

Estela

Recessed Integrated LED Louvre - Square

Features



The Megaman Estela range of modular luminaries have a distinct appearance and are perfect replacements to T5 and T8 fluorescent louvre modular fittings and LED panels. The Estela range come integrated with a driver and are light weight for easy installation and maintenance. Mountable on both exposed T-bar and concealed T-bar ceilings. With Unified Glare Rating of ≤19 to offer visual comfort and avoid fatigue to the eyes, Estela is perfect for office applications.

Specification

| UK Order Code > | 519178 |
|-----------------------|------------|
| Watts | 30W |
| Colour Temp (K) /CRI | 4000 / 80 |
| Lumens (lm) | 3500 |
| Candelas (cd) | 2500 |
| Dimmable | N |
| Hrs Lamp Life (L70) | 50,000 |
| Hrs Lamp Life (L90) | 25,000 |
| Beam Angle | 90° |
| Weight (g) | 3235 |
| Dimensions (LxWxD mm) | 597x597x35 |
| Shape | Square |

Operating temperature -30°C to +40°C



Fixtures

F26500RC

Estela

Recessed Integrated LED Louvre - Rectangle

Features



The Megaman Estela range of modular luminaries have a distinct appearance and are perfect replacements to T5 and T8 fluorescent louvre modular fittings and LED panels. The Estela range come integrated with a driver and are light weight for easy installation and maintenance. Mountable on both exposed T-bar and concealed T-bar ceilings. With Unified Glare Rating of ≤19 to offer visual comfort and avoid fatigue to the eyes, Estela is perfect for office applications.

Specification

| UK Order Code > | 519186 |
|-----------------------|--------------|
| Watts | 30W |
| Colour Temp (K) /CRI | 4000 / 80 |
| Lumens (lm) | 3500 |
| Candelas (cd) | 2500 |
| Dimmable | N |
| Hrs Lamp Life (L70) | 50,000 |
| Hrs Lamp Life (L90) | 25,000 |
| Beam Angle | 90° |
| Weight (g) | 3236 |
| Dimensions (LxWxD mm) | 1197x 297x35 |
| Shape | Rectangular |

Operating temperature -30°C to +40°C



Fixtures

Berto LED Panel - Square

F33400RCv1
F33400RCv2

Features




The Megaman Berto range of ultra slim LED integrated panels, with low glare diffuser are easy to install and maintain. Non dimming driver included.

130152/130135




130149



Specification

| UK Order Code > | 130152 | 130135 | 130149 |
|-----------------------|-----------|-----------|-----------|
| Watts | 44W | 44W | 50W |
| Colour Temp (K) /CRI | 3000 / 80 | 4000 / 80 | 4000 / 80 |
| Lumens (lm) | 3350 | 3600 | 4100 |
| Candelas (cd) | 1200 | 1200 | 1400 |
| Dimmable | N | N | N |
| Hrs Lamp Life (L70) | 50,000 | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 | 25,000 |
| Beam Angle | 120° | 120° | 120° |
| Weight (g) | 2965 | 2965 | 2948 |
| Dimensions (LxWxD mm) | 595x595x9 | 595x595x9 | 595x595x9 |
| Shape | Square | Square | Square |

Dimensions...



Operating temperature -30°C to +40°C



Fixtures

Berto LED Panel - Rectangular

F33600RCv1

Features



The Megaman Berto range of ultra slim LED integrated panels, with low glare diffuser are easy to install and maintain. Non dimming driver included.


130155



Specification

| UK Order Code > | 130155 |
|-----------------------|-------------|
| Watts | 52W |
| Colour Temp (K) /CRI | 4000 / 80 |
| Lumens (lm) | 5100 |
| Candelas (cd) | 1800 |
| Dimmable | N |
| Hrs Lamp Life (L70) | 50,000 |
| Hrs Lamp Life (L90) | 25,000 |
| Beam Angle | 120° |
| Weight (g) | 5870 |
| Dimensions (LxWxD mm) | 1195x595x9 |
| Shape | Rectangular |

Dimensions...



Operating temperature -30°C to +40°C

130409
Surface Mount kit for Square



130705
Surface Mount kit for Rectangular



130267
Suspension kit for Square



130269
Suspension kit for Rectangular



Fixtures

Berto
LED Panel Accessories

LA10027
LA10028
LA10025
LA10026

Features



A choice of installation accessories are available for the Megaman Berto LED panel.
Please ensure to order the correct kit for your panel, depending on whether it is square or rectangular.

Specification

| UK Order Code > | 130409 | 130705 | 130267 | 130269 |
|---------------------|---|--|--|---|
| Berto LED accessory | Surface Mounted Kit (with 4 hooks) for Square panel | Surface Mounted Kit (with 6 hooks) for Rectangular panel | 4-wire Suspension Kit for Square panel | 6-wire Suspension Kit for Rectangular panel |

For use with...



Berto
LED Panel - Square



Berto
LED Panel - Rectangular



Fixtures

8W VERSOFIT
Fixed Integrated Fire Rated Downlight Dimming

F28851RC

Features




Megaman's first fully integrated fire rated downlight with a serviceable LED light engine allowing ultimate control. Design features include the latest super-efficient Megaman LED light engine, easy click connectors, large push button terminals, Loop in Loop out features to save installation time and advanced thermal design to lower operating temperatures and extend life. It complements the Megaman family lamp range from its unique front lens design allowing you to integrate within projects. Works with TECOH® THx LED light engine, included. Please refer to **pg 146** for more information.

Specification


| UK Order Code > | 519406 | 519728 | 519607 | 519315 | 519160 |
|------------------------|------------|------------|------------|------------|--------------|
| Watts | 8W | 8W | 8W | 8W | 8W |
| Colour Temp (K) / CRI | 2800 / 80 | 4000 / 80 | 2800 / 80 | 4000 / 80 | 2800 / 80 |
| Lumens (lm) | 600 | 630 | 600 | 630 | 600 |
| Candelas (cd) | 650 | 650 | 650 | 650 | 650 |
| Dimmable | Y | Y | Y | Y | Y |
| Hrs Lamp Life (L70) | 30,000 | 30,000 | 30,000 | 30,000 | 30,000 |
| Beam Angle | 36° | 36° | 36° | 36° | 36° |
| Weight (g) | 235 | 235 | 235 | 235 | 235 |
| Dimensions (LxDia mm) | 110x90 | 110x90 | 110x90 | 110x90 | 110x90 |
| Colour/Finish | White | White | Chrome | Chrome | Satin Chrome |
| Shape | Round | Round | Round | Round | Round |
| Hole Cut-Out (mm) | 71 | 71 | 71 | 71 | 71 |
| Min Ceiling Depth (mm) | 105 | 105 | 105 | 105 | 105 |
| Suitable Lamps | TECOH® THx |

Refers to all models opposite



Please visit our website for a full list of compatible dimmers - www.megamanuk.com/products/dimming-compatibility

Dimensions...



Operating temperature -30°C to +40°C



Fixtures

F28951RC



8W VERSOFIT

Tilt Integrated Fire Rated Downlight Dimming

Features



Megaman's first fully integrated fire rated downlight with a serviceable LED light engine allowing ultimate control. Design features include the latest super-efficient Megaman LED light engine, easy click connectors, large push button terminals, Loop in Loop out features to save installation time and advanced thermal design to lower operating temperatures and extend life. It complements the Megaman family lamp range from its unique front lens design allowing you to integrate within projects. Works with TECOH® THx LED light engine, included. Please refer to **pg 146** for more information.

Refers to all models opposite




Specification

| UK Order Code > | 519317 | 519681 | 519353 | 519715 | 519843 | 519301 |
|-------------------------|------------|------------|------------|------------|--------------|--------------|
| Watts | 8W | 8W | 8W | 8W | 8W | 8W |
| Colour Temp (K) /CRI | 2800 / 80 | 4000 / 80 | 2800 / 80 | 4000 / 80 | 2800 / 80 | 4000 / 80 |
| Lumens (lm) | 600 | 630 | 600 | 630 | 600 | 630 |
| Candelas (cd) | 650 | 650 | 650 | 650 | 650 | 650 |
| Dimmable | Y | Y | Y | Y | Y | Y |
| Hrs Lamp Life (L70) | 30,000 | 30,000 | 30,000 | 30,000 | 30,000 | 30,000 |
| Beam Angle | 36° | 36° | 36° | 36° | 36° | 36° |
| Weight (g) | 330 | 330 | 330 | 330 | 330 | 330 |
| Dimensions (L x Dia mm) | 108x96 | 108x96 | 108x96 | 108x96 | 108x96 | 108x96 |
| Colour/Finish | White | White | Chrome | Chrome | Satin Chrome | Satin Chrome |
| Shape | Round | Round | Round | Round | Round | Round |
| Hole Cut-Out (mm) | 85 | 85 | 85 | 85 | 85 | 85 |
| Min Ceiling Depth (mm) | 103 | 103 | 103 | 103 | 103 | 103 |
| Tilt Angle | 13° | 13° | 13° | 13° | 13° | 13° |
| Suitable Lamps | TECOH® THx | TECOH® THx |

Please visit our website for a full list of compatible dimmers - www.megamanuk.com/products/dimming-compatibility

Dimensions...



Operating temperature -30°C to +40°C



Fixtures

F28751RC



8W VERSOFIT


IP65 Integrated Fire Rated Downlight Dimming

Features



Megaman's first fully integrated fire rated downlight with a serviceable LED light engine allowing ultimate control. Design features include the latest super-efficient Megaman LED light engine, easy click connectors, large push button terminals, Loop in Loop out features to save installation time and advanced thermal design to lower operating temperatures and extend life. It complements the Megaman family lamp range from its unique front lens design allowing you to integrate within projects. Works with TECOH® THx LED light engine, included. Please refer to **pg 146** for more information.

Refers to all models opposite




Specification

| UK Order Code > | 519379 | 519609 | 519627 | 519384 | 519048 |
|-------------------------|------------|------------|------------|--------------|----------------|
| Watts | 8W | 8W | 8W | 8W | 8W |
| Colour Temp (K) /CRI | 2800 / 80 | 2800 / 80 | 4000 / 80 | 2800 / 80 | 4000 / 80 |
| Lumens (lm) | 420 | 420 | 440 | 420 | 440 |
| Candelas (cd) | 550 | 550 | 550 | 550 | 550 |
| Dimmable | Y | Y | Y | Y | Y |
| Hrs Lamp Life (L70) | 30,000 | 30,000 | 30,000 | 30,000 | 30,000 |
| Beam Angle | 36° | 36° | 36° | 36° | 36° |
| Weight (g) | 395 | 395 | 395 | 395 | 395 |
| Dimensions (L x Dia mm) | 113x88 | 113x88 | 113x88 | 113x88 | 113x88 |
| Colour/Finish | White | Chrome | Chrome | Satin Chrome | Brushed Nickel |
| Shape | Round | Round | Round | Round | Round |
| Hole Cut-Out (mm) | 74 | 74 | 74 | 74 | 74 |
| Min Ceiling Depth (mm) | 111 | 111 | 111 | 111 | 111 |
| Suitable Lamps | TECOH® THx | TECOH® THx | TECOH® THx | TECOH® THx | TECOH® THx |

Please visit our website for a full list of compatible dimmers - www.megamanuk.com/products/dimming-compatibility

Dimensions...



Operating temperature -30°C to +40°C



Fixtures

12.5W Siena Integrated LED Downlight

F2620ORC

Features



The Siena integrated LED downlight range incorporates a driver. The range is easy to install and delivers high system efficacy of up to 76lm/W - producing 62% more light when compared to conventional plug-in tube CFL downlights.


517951/517462



Specification

| UK Order Code > | 517951 | 517462 |
|------------------------|-----------|-----------|
| Watts | 12.5W | 12.5W |
| Colour Temp (K) / CRI | 2800 / 80 | 4000 / 80 |
| Lumens (lm) | 950 | 950 |
| Candelas (cd) | 510 | 510 |
| Dimmable | N | N |
| Hrs Lamp Life (L70) | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 |
| Beam Angle | 90° | 90° |
| Weight (g) | 217 | 217 |
| Dimensions (H x D mm) | 84x145 | 84x145 |
| Colour/Finish | White | White |
| Shape | Round | Round |
| Hole Cut-Out (mm) | 125 | 125 |
| Min Ceiling Depth (mm) | 91 | 91 |

Dimensions...



Operating temperature -30°C to +40°C



Fixtures

12.5W Siena Integrated LED Downlight Square


F5140ORC

Features



The Siena integrated LED downlight range incorporates a driver. The range is easy to install and delivers high system efficacy of up to 76lm/W - producing 62% more light when compared to conventional plug-in tube CFL downlights.


191962/191973



Specification

| UK Order Code > | 191962 | 191973 |
|------------------------|-----------|-----------|
| Watts | 12.5W | 12.5W |
| Colour Temp (K) / CRI | 2800 / 80 | 4000 / 80 |
| Lumens (lm) | 950 | 950 |
| Candelas (cd) | 510 | 510 |
| Dimmable | N | N |
| Hrs Lamp Life (L70) | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 |
| Beam Angle | 90° | 90° |
| Weight (g) | 245 | 245 |
| Dimensions (H x D mm) | 84x145 | 84x145 |
| Colour/Finish | White | White |
| Shape | Square | Square |
| Hole Cut-Out (mm) | 130x130 | 130x130 |
| Min Ceiling Depth (mm) | 89 | 89 |

Dimensions...



Operating temperature -30°C to +40°C



Fixtures

F26200RC-d


13W Siena Integrated LED Downlight Dimming

Features



The Siena integrated LED downlight range incorporates a driver. The range is easy to install and delivers high system efficacy of up to 76lm/W - producing 62% more light when compared to conventional plug-in tube CFL downlights.

519206/519248




Specification

| UK Order Code > | 519206 | 519248 |
|-------------------------|-----------|-----------|
| Watts | 13W | 13W |
| Colour Temp (K) / CRI | 2800 / 80 | 4000 / 80 |
| Lumens (lm) | 950 | 950 |
| Candelas (cd) | 510 | 510 |
| Dimmable | Y | Y |
| Hrs Lamp Life (L70) | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 |
| Beam Angle | 90° | 90° |
| Weight (g) | 220 | 220 |
| Dimensions (L x Dia mm) | 84x145 | 84x145 |
| Colour/Finish | White | White |
| Shape | Round | Round |
| Hole Cut-Out (mm) | 125 | 125 |
| Min Ceiling Depth (mm) | 91 | 91 |

Please visit our website for a full list of compatible dimmers - www.megamanuk.com/products/dimming-compatibility

Dimensions...



Operating temperature -30°C to +40°C



Fixtures

F26300RC


20.5W Siena Integrated LED Downlight

Features



The Siena integrated LED downlight range incorporates a driver. The range is easy to install and delivers high system efficacy of up to 76lm/W - producing 62% more light when compared to conventional plug-in tube CFL downlights.


517839/517423



Specification

| UK Order Code > | 517839 | 517423 |
|------------------------|-----------|-----------|
| Watts | 20.5W | 20.5W |
| Colour Temp (K) / CRI | 2800 / 80 | 4000 / 80 |
| Lumens (lm) | 1560 | 1560 |
| Candelas (cd) | 810 | 810 |
| Dimmable | N | N |
| Hrs Lamp Life (L70) | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 |
| Beam Angle | 90° | 90° |
| Weight (g) | 266 | 266 |
| Dimensions (H x D mm) | 94x172 | 94x172 |
| Colour/Finish | White | White |
| Shape | Round | Round |
| Hole Cut-Out (mm) | 150 | 150 |
| Min Ceiling Depth (mm) | 148 | 148 |

Dimensions...



Operating temperature -30°C to +40°C



Fixtures

F26300RC-d

21.5W Siena


Integrated LED Downlight Dimming

Features



The Siena integrated LED downlight range incorporates a driver. The range is easy to install and delivers high system efficacy of up to 76lm/W - producing 62% more light when compared to conventional plug-in tube CFL downlights.

519267/519273




Specification

| UK Order Code > | 519267 | 519273 |
|-------------------------|-----------|-----------|
| Watts | 21.5W | 21.5W |
| Colour Temp (K) / CRI | 2800 / 80 | 4000 / 80 |
| Lumens (lm) | 1560 | 1560 |
| Candelas (cd) | 810 | 810 |
| Dimmable | Y | Y |
| Hrs Lamp Life (L70) | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 |
| Beam Angle | 90° | 90° |
| Weight (g) | 264 | 264 |
| Dimensions (L x Dia mm) | 94x172 | 94x172 |
| Colour/Finish | White | White |
| Shape | Round | Round |
| Hole Cut-Out (mm) | 150 | 150 |
| Min Ceiling Depth (mm) | 101 | 101 |

Please contact our sales office for further dimming information.

Dimensions...



Operating temperature -30°C to +40°C




Fixtures

F27100RC

35.5W Siena


Integrated LED Downlight

Features



The Siena integrated LED downlight range incorporates a driver. The range is easy to install and delivers high system efficacy of up to 76lm/W - producing 62% more light when compared to conventional plug-in tube CFL downlights.


517492/517186



Specification

| UK Order Code > | 517492 | 517186 |
|------------------------|-----------|-----------|
| Watts | 35.5W | 35.5W |
| Colour Temp (K) / CRI | 2800 / 80 | 4000 / 80 |
| Lumens (lm) | 2700 | 2700 |
| Candelas (cd) | 1420 | 1420 |
| Dimmable | N | N |
| Hrs Lamp Life (L70) | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 |
| Beam Angle | 90° | 90° |
| Weight (g) | 447 | 447 |
| Dimensions (H x D mm) | 94x225 | 94x225 |
| Colour/Finish | White | White |
| Shape | Round | Round |
| Hole Cut-Out (mm) | 200 | 200 |
| Min Ceiling Depth (mm) | 98 | 98 |

Dimensions...



Operating temperature -30°C to +40°C



Fixtures

F28100RC-w


8W Siena Integrated LED Dim to Warm

Features



The Megaman Siena range of integrated LED recessed adjustable downlights are an ideal replacement for halogen MR16 and GU10 downlights. Compact in size, 25mm shorter than traditional downlights, they are easy to install and maintain. The Dim to Warm range of Megaman LEDs emit a warmer light when they are dimmed from 2800K to 1800K, simulating the characteristics of incandescent and halogen lamps.

191406/191617




Specification

| UK Order Code > | 191406 | 191617 |
|------------------------|----------------|----------------|
| Watts | 8W | 8W |
| Colour Temp (K) /CRI | 2800-1800 / 80 | 2800-1800 / 80 |
| Lumens (lm) | 500 | 500 |
| Candelas (cd) | 1800 | 1800 |
| Dimmable | Y | Y |
| Hrs Lamp Life (L70) | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 |
| Beam Angle | 36° | 36° |
| Weight (g) | 212 | 212 |
| Dimensions (H x D mm) | 55x80 | 55x80 |
| Colour/Finish | White | Silver |
| Shape | Round | Round |
| Hole Cut-Out (mm) | 68 | 68 |
| Min Ceiling Depth (mm) | 53 | 53 |
| Tilt Angle | 25° | 25° |

Please visit our website for a full list of compatible dimmers - www.megamanuk.com/products/dimming-compatibility

Dimensions...



Operating temperature -30°C to +40°C



Fixtures

F29500RCv1-d


8W Siena Integrated LED Square Dimming

Features



The Megaman Siena range of integrated LED recessed adjustable downlights are an ideal replacement for halogen MR16 and GU10 downlights. Compact in size, 25mm shorter than traditional downlights, they are easy to install and maintain.

191761/191704/191831/191849




Specification

| UK Order Code > | 191761 | 191704 | 191831 | 191849 |
|------------------------|-----------------|-----------------|-----------------|-----------------|
| Watts | 8W | 8W | 8W | 8W |
| Colour Temp (K) /CRI | 2800 / 80 | 4000 / 80 | 2800 / 80 | 4000 / 80 |
| Lumens (lm) | 650 | 650 | 650 | 650 |
| Candelas (cd) | 2000 | 2000 | 2000 | 2000 |
| Dimmable | Y | Y | Y | Y |
| Hrs Lamp Life (L70) | 50,000 | 50,000 | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 | 25,000 | 25,000 |
| Beam Angle | 36° | 36° | 36° | 36° |
| Weight (g) | 220 | 220 | 220 | 220 |
| Dimensions (H x D mm) | 55x80 | 55x80 | 55x80 | 55x80 |
| Colour/Finish | White | White | Silver | Silver |
| Shape | Square surround | Square surround | Square surround | Square surround |
| Hole Cut-Out (mm) | 68 | 68 | 68 | 68 |
| Min Ceiling Depth (mm) | 53 | 53 | 53 | 53 |
| Tilt Angle | 25° | 25° | 25° | 25° |

Please visit our website for a full list of compatible dimmers - www.megamanuk.com/products/dimming-compatibility

Dimensions...



Operating temperature -30°C to +40°C




Fixtures

F54100RC-d


10.5W Siena SR Integrated LED Dimming

Features




The Megaman Siena range has expanded to include SR (specular reflector) downlights. A tool-less terminal box that allows through wire looping and no external driver requirements facilitates easy installation and maintenance. The Siena family has a Unified Glare Rating of ≤ 22 for visual comfort and to avoid fatigue to the eyes. Also featuring Megaman's new U-DIM™ Technology, offering an enhanced dimming range from 100% down to 5% with the widest range of dimmers, whether they are leading-edge or trailing-edge.

519276/519278



Specification


| UK Order Code > | 519276 | 519278 |
|------------------------|-----------|-----------|
| Watts | 10.5W | 10.5W |
| Colour Temp (K) / CRI | 2800 / 80 | 4000 / 80 |
| Lumens (lm) | 950 | 950 |
| Candelas (cd) | 500 | 500 |
| Dimmable | Y | Y |
| Hrs Lamp Life (L70) | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 |
| Beam Angle | 90° | 90° |
| Weight (g) | 253 | 253 |
| Dimensions (H x D mm) | 84x145 | 84x145 |
| Colour/Finish | White | White |
| Shape | Round | Round |
| Hole Cut-Out (mm) | 125 | 125 |
| Min Ceiling Depth (mm) | 85 | 85 |



Tool-less terminal box facilitates easy installation, maintenance and through wire looping.

Please contact our sales office for further dimming information.

Dimensions...



Operating temperature -30°C to +40°C



Fixtures

F54200RC-d


16.5W Siena SR Integrated LED Dimming

Features



The Megaman Siena range has expanded to include SR (specular reflector) downlights. A tool-less terminal box that allows through wire looping and no external driver requirements facilitates easy installation and maintenance. The Siena family has a Unified Glare Rating of ≤ 22 for visual comfort and to avoid fatigue to the eyes. Also featuring Megaman's new U-DIM™ Technology, offering an enhanced dimming range from 100% down to 5% with the widest range of dimmers, whether they are leading-edge or trailing-edge.

519280/519282



Specification


| UK Order Code > | 519280 | 519282 |
|------------------------|-----------|-----------|
| Watts | 16.5W | 16.5W |
| Colour Temp (K) / CRI | 2800 / 80 | 4000 / 80 |
| Lumens (lm) | 1560 | 1560 |
| Candelas (cd) | 850 | 850 |
| Dimmable | Y | Y |
| Hrs Lamp Life (L70) | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 |
| Beam Angle | 90° | 90° |
| Weight (g) | 337 | 337 |
| Dimensions (H x D mm) | 94x172 | 94x172 |
| Colour/Finish | White | White |
| Shape | Round | Round |
| Hole Cut-Out (mm) | 150 | 150 |
| Min Ceiling Depth (mm) | 95 | 95 |



Tool-less terminal box facilitates easy installation, maintenance and through wire looping.

Please contact our sales office for further dimming information.

Dimensions...



Operating temperature -30°C to +40°C



Fixtures F54300RCv1

25.5W Siena SR Integrated LED




The Megaman Siena range has expanded to include SR (specular reflector) downlights. A tool-less terminal box that allows through wire looping and no external driver requirements facilitates easy installation and maintenance.

519284/519286




Specification

| UK Order Code > | 519284 | 519286 |
|-------------------------|-----------|-----------|
| Watts | 25.5W | 25.5W |
| Colour Temp (K) / CRI | 2800 / 80 | 4000 / 80 |
| Lumens (lm) | 2700 | 2700 |
| Candelas (cd) | 1900 | 1900 |
| Dimmable | N | N |
| Hrs Lamp Life (L70) | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 |
| Beam Angle | 90° | 90° |
| Weight (g) | 525 | 525 |
| Dimensions (L x Dia mm) | 100x225 | 100x225 |
| Colour/Finish | White | White |
| Shape | Round | Round |
| Hole Cut-Out (mm) | 200 | 200 |
| Min Ceiling Depth (mm) | 98 | 98 |



Tool-less terminal box facilitates easy installation, maintenance and through wire looping.

Dimensions...



Operating temperature -30°C to +40°C




Fixtures F26400RC-w

13W Siena SR Integrated LED Dim to Warm



The Megaman Siena range of integrated LED recessed downlights are an ideal replacement for halogen MR16 and GU10 downlights. The Dim to Warm range of Megaman LEDs emit a warmer light when they are dimmed from 2800K to 1800K, simulating the characteristics of incandescent and halogen lamps.

191301




Specification

| UK Order Code > | 191301 |
|------------------------|----------------|
| Watts | 13W |
| Colour Temp (K) / CRI | 2800-1800 / 80 |
| Lumens (lm) | 900 |
| Candelas (cd) | 670 |
| Dimmable | Y |
| Hrs Lamp Life (L70) | 50,000 |
| Hrs Lamp Life (L90) | 25,000 |
| Beam Angle | 60° |
| Weight (g) | 172 |
| Dimensions (H x D mm) | 78x110 |
| Colour/Finish | White |
| Shape | Round |
| Hole Cut-Out (mm) | 85 |
| Min Ceiling Depth (mm) | 84 |

Please visit our website for a full list of compatible dimmers - www.megamanuk.com/products/dimming-compatibility

Dimensions...



Operating temperature -30°C to +40°C




Fixtures

F54600RC-d

10.5W Siena FR Integrated LED Dimming

Features



The Megaman Siena range has expanded to include FR (faceted reflector) downlights. A tool-less terminal box that allows through wire looping and no external driver requirements facilitates easy installation and maintenance. The Siena family has a Unified Glare Rating of ≤ 22 for visual comfort and to avoid fatigue to the eyes. Also featuring Megaman's new U-DIM™ Technology, offering an enhanced dimming range from 100% down to 5% with the widest range of dimmers, whether they are leading-edge or trailing-edge.

519288/519290



Specification


| UK Order Code > | 519288 | 519290 |
|-------------------------|-----------|-----------|
| Watts | 10.5W | 10.5W |
| Colour Temp (K) / CRI | 2800 / 80 | 4000 / 80 |
| Lumens (lm) | 950 | 950 |
| Candelas (cd) | 500 | 500 |
| Dimmable | Y | Y |
| Hrs Lamp Life (L70) | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 |
| Beam Angle | 90° | 90° |
| Weight (g) | 255 | 255 |
| Dimensions (L x Dia mm) | 84x145 | 84x145 |
| Colour/Finish | White | White |
| Shape | Round | Round |
| Hole Cut-Out (mm) | 125 | 125 |
| Min Ceiling Depth (mm) | 85 | 85 |



Tool-less terminal box facilitates easy installation, maintenance and through wire looping.

Please contact our sales office for further dimming information.

Dimensions...



Operating temperature -30°C to +40°C



Fixtures

F54700RC-d


16.5W Siena FR Integrated LED Dimming

Features



The Megaman Siena range has expanded to include FR (faceted reflector) downlights. A tool-less terminal box that allows through wire looping and no external driver requirements facilitates easy installation and maintenance. The Siena family has a Unified Glare Rating of ≤ 22 for visual comfort and to avoid fatigue to the eyes. Also featuring Megaman's new U-DIM™ Technology, offering an enhanced dimming range from 100% down to 5% with the widest range of dimmers, whether they are leading-edge or trailing-edge.

519292/519294



Specification


| UK Order Code > | 519292 | 519294 |
|-------------------------|-----------|-----------|
| Watts | 16.5W | 16.5W |
| Colour Temp (K) / CRI | 2800 / 80 | 4000 / 80 |
| Lumens (lm) | 1560 | 1560 |
| Candelas (cd) | 850 | 850 |
| Dimmable | Y | Y |
| Hrs Lamp Life (L70) | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 |
| Beam Angle | 90° | 90° |
| Weight (g) | 349 | 349 |
| Dimensions (L x Dia mm) | 94x172 | 94x172 |
| Colour/Finish | White | White |
| Shape | Round | Round |
| Hole Cut-Out (mm) | 150 | 150 |
| Min Ceiling Depth (mm) | 95 | 95 |



Tool-less terminal box facilitates easy installation, maintenance and through wire looping.

Please contact our sales office for further dimming information.

Dimensions...



Operating temperature -30°C to +40°C



Fixtures F54800RCv1

25.5W Siena FR Integrated LED

Features

- IP44
- Class II
- 11 PRODUCT DISCOUNT GROUP


The Megaman Siena range has expanded to include FR (faceted reflector) downlights. A tool-less terminal box that allows through wire looping and no external driver requirements facilitates easy installation and maintenance.

519296/519298




Specification

| UK Order Code > | 519296 | 519298 |
|-------------------------|-----------|-----------|
| Watts | 25.5W | 25.5W |
| Colour Temp (K) /CRI | 2800 / 80 | 4000 / 80 |
| Lumens (lm) | 2700 | 2700 |
| Candelas (cd) | 1900 | 1900 |
| Dimmable | N | N |
| Hrs Lamp Life (L70) | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 |
| Beam Angle | 90° | 90° |
| Weight (g) | 530 | 530 |
| Dimensions (L x Dia mm) | 100x225 | 100x225 |
| Colour/Finish | White | White |
| Shape | Round | Round |
| Hole Cut-Out (mm) | 200 | 200 |
| Min Ceiling Depth (mm) | 98 | 98 |



Tool-less terminal box facilitates easy installation, maintenance and through wire looping.

Dimensions...



Operating temperature -30°C to +40°C



Fixtures F29700RC

12.5W Rico Integrated LED

Features

- IP44
- Class III
- 11 PRODUCT DISCOUNT GROUP

The Megaman Rico ultra slim LED downlight is ideal for a ceiling recess with limited depth, also suitable for cabinet and furniture lighting. Non-dimming driver included.


190284/190348



Specification

| UK Order Code > | 190284 | 190348 |
|------------------------|-----------|-----------|
| Watts | 12.5W | 12.5W |
| Colour Temp (K) /CRI | 2800 / 80 | 4000 / 80 |
| Lumens (lm) | 950 | 950 |
| Candelas (cd) | 370 | 370 |
| Dimmable | N | N |
| Hrs Lamp Life (L70) | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 |
| Beam Angle | 110° | 110° |
| Weight (g) | 149 | 149 |
| Dimensions (H x D mm) | 30x145 | 30x145 |
| Colour/Finish | White | White |
| Shape | Round | Round |
| Hole Cut-Out (mm) | 125 | 125 |
| Min Ceiling Depth (mm) | 28 | 28 |

Dimensions...



Operating temperature -30°C to +40°C



Fixtures
22W Rico
 Integrated LED

F29800RC

Features



The Megaman Rico ultra slim LED downlight is ideal for a ceiling recess with limited depth, also suitable for cabinet and furniture lighting. Non-dimming driver included.


190351/190357



Specification

| UK Order Code > | 190351 | 190357 |
|-------------------------|-----------|-----------|
| Watts | 22W | 22W |
| Colour Temp (K) /CRI | 2800 / 80 | 4000 / 80 |
| Lumens (lm) | 1560 | 1560 |
| Candelas (cd) | 620 | 620 |
| Dimmable | N | N |
| Hrs Lamp Life (L70) | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 |
| Beam Angle | 110° | 110° |
| Weight (g) | 200 | 200 |
| Dimensions (L x Dia mm) | 35x172 | 35x172 |
| Colour/Finish | White | White |
| Shape | Round | Round |
| Hole Cut-Out (mm) | 150 | 150 |
| Min Ceiling Depth (mm) | 33 | 33 |

Dimensions...



Operating temperature -30°C to +40°C



Fixtures
29W Rico
 Integrated LED


F29900RCV1

Features



The Megaman Rico ultra slim LED downlight is ideal for a ceiling recess with limited depth, also suitable for cabinet and furniture lighting. Non-dimming driver included.


190468/190482



Specification

| UK Order Code > | 190468 | 190482 |
|------------------------|-----------|-----------|
| Watts | 29W | 29W |
| Colour Temp (K) /CRI | 2800 / 80 | 4000 / 80 |
| Lumens (lm) | 2000 | 2000 |
| Candelas (cd) | 880 | 880 |
| Dimmable | N | N |
| Hrs Lamp Life (L70) | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 |
| Beam Angle | 110° | 110° |
| Weight (g) | 346 | 346 |
| Dimensions (H x D mm) | 38x225 | 38x225 |
| Colour/Finish | White | White |
| Shape | Round | Round |
| Hole Cut-Out (mm) | 200 | 200 |
| Min Ceiling Depth (mm) | 35 | 35 |

Dimensions...



Operating temperature -30°C to +40°C



Fixtures
6.5W Rico HR
 Integrated LED Dimming


F53500RC
 F53500RC-w

Features



This Megaman Rico ultra slim integrated downlight is the ideal replacement for halogen MR16 and GU10 downlights. Featuring Megaman's latest hybrid reflector technology, delivering excellent beam control and U-DIM™ technology, which ensures Rico is compatible with both leading-edge and trailing-edge dimmers. The 190484 6.5W also features Dim to Warm technology, emitting a warmer light when dimmed from 2800K to 1800K. Purchase driver separately.

190288/190290/190484



Specification


| UK Order Code > | 190288 | 190290 | 190484 |
|------------------------|-----------|-----------|----------------|
| Watts | 6.5W | 6.5W | 6.5W |
| Colour Temp (K) /CRI | 2800 / 80 | 4000 / 80 | 2800-1800 / 80 |
| Lumens (lm) | 500 | 500 | 500 |
| Candelas (cd) | 1100 | 1100 | 1100 |
| Dimmable | Y | Y | Y |
| Hrs Lamp Life (L70) | 50,000 | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 | 25,000 |
| Beam Angle | 36° | 36° | 36° |
| Weight (g) | 117 | 117 | 117 |
| Dimensions (H x D mm) | 30x80 | 30x80 | 30x80 |
| Colour/Finish | White | White | White |
| Shape | Round | Round | Round |
| Hole Cut-Out (mm) | 68 | 68 | 68 |
| Min Ceiling Depth (mm) | 68 | 68 | 68 |
| Tilt Angle | 25° | 25° | 25° |

Megaman recommends the **190985** 350MA driver, sold separately.

Please visit our website for a full list of compatible dimmers - www.megamanuk.com/products/dimming-compatibility



Dimensions...



Operating temperature -30°C to +40°C



Fixtures
9W Rico HR
 Integrated LED Dimming


F53500RCv2
 F53500RC-R9

Features




This Megaman Rico ultra slim integrated downlight is the ideal replacement for halogen MR16 and GU10 downlights. Featuring Megaman's latest hybrid reflector technology, delivering excellent beam control. The 190488 9W also features Rich Colour technology, designed to maximise the richness and quality of colours with high colour rendering of up to Ra95. The perfect choice for food and other display lighting applications where the visual appeal of items is essential. Purchase driver separately.

190292/190294



190488



Specification


| UK Order Code > | 190292 | 190294 | 190488 |
|------------------------|-----------|-----------|-----------|
| Watts | 9W | 9W | 9W |
| Colour Temp (K) /CRI | 2800 / 80 | 4000 / 80 | 2800 / 95 |
| Lumens (lm) | 900 | 900 | 700 |
| Candelas (cd) | 2400 | 2400 | 1650 |
| Dimmable | Y | Y | Y |
| Hrs Lamp Life (L70) | 50,000 | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 | 25,000 |
| Beam Angle | 36° | 36° | 36° |
| Weight (g) | 117 | 117 | 117 |
| Dimensions (H x D mm) | 30x80 | 30x80 | 30x80 |
| Colour/Finish | White | White | White |
| Shape | Round | Round | Round |
| Hole Cut-Out (mm) | 68 | 68 | 68 |
| Min Ceiling Depth (mm) | 68 | 68 | 68 |
| Tilt Angle | 25° | 25° | 25° |

Megaman recommends the **190987** 500MA driver, sold separately.

Please visit our website for a full list of compatible dimmers - www.megamanuk.com/products/dimming-compatibility



Dimensions...




Operating temperature -30°C to +40°C



Fixtures

Zeki 50mm
Multi-head Gimbal
(2-head frame pictured)

Features



F55752RC
F55852RC
F55952RC

This Megaman Zeki 50mm fixture works with the serviceable 10.5W TECOH® THx LED light engine, delivering excellent lighting performance for the replacement of traditional 50W halogen MR16 and PAR16 multi-head gimbals. The gimbal construction provides multi-directional tilting and the modular system designed with a 1, 2 and 3 head frame, enables different combinations of lighting optics and performance. Works with TECOH® THx LED light engine, sold separately. Please refer to **page 147** for more information. No driver required.

Specification

| UK Order Code > | 131744 | 131746 | 131748 |
|------------------------|------------------------------|------------------------------|------------------------------|
| Watts | For 1 x 10.5W TECOH® THx | For 2 x 10.5W TECOH® THx | For 3 x 10.5W TECOH® THx |
| Colour Temp (K) /CRI | Available in 2800K and 4000K | Available in 2800K and 4000K | Available in 2800K and 4000K |
| Lumens (lm) | 900 | 900 | 900 |
| Candelas (cd) | 3500 (24°) 1900 (36°) | 3500 (24°) 1900 (36°) | 3500 (24°) 1900 (36°) |
| Dimmable | N | N | N |
| Hrs Lamp Life (L70) | 25,000 | 25,000 | 25,000 |
| Beam Angle | Available in 24° and 36° | Available in 24° and 36° | Available in 24° and 36° |
| Weight (g) | 105 | 191 | 260 |
| Dimensions (LxWxH mm) | 89x89x56 (H=90 with THx) | 165x89x56 (H=90 with THx) | 242x89x56 (H=90 with THx) |
| Colour/Finish | White | White | White |
| Shape | Square surround | Rectangular surround | Rectangular surround |
| Hole Cut-Out (mm) | 83 x 83 | 159 x 83 | 236 x 83 |
| Min Ceiling Depth (mm) | 94 | 94 | 94 |
| Tilt Angle | 19° | 19° | 19° |
| Suitable Light Source | TECOH® THx | TECOH® THx | TECOH® THx |


Purchase TECOH® THx separately – **131750** (2800K/24°) and **131752** (4000K/24°) or **131754** (2800K/36°) and **131756** (4000K/36°). See page 147 for more information.



Below: 1 and 3-head frame variants



Dimensions...



Operating temperature -30°C to +40°C



Fixtures

Zeki 111mm
Multi-head Gimbal
(2-head frame pictured)

Features



F56353RC
F56453RC
F56553RC

This Megaman Zeki 111mm fixture works with the serviceable 35W TECOH® THx LED module, delivering excellent lighting performance for the replacement of traditional metal halide and halogen AR111s. The gimbal construction provides multi-directional tilting and the modular system designed with a 1, 2 and 3 head frame, enables different combinations of lighting optics and performance. Works with TECOH® THx LED module, sold separately. Please refer to **page 148** for more information. Purchase driver separately.

Specification

| UK Order Code > | 131734 | 131736 | 131738 |
|------------------------|------------------------------|------------------------------|------------------------------|
| Watts | For 1 x 35W TECOH® THx | For 2 x 35W TECOH® THx | For 3 x 35W TECOH® THx |
| Colour Temp (K) /CRI | Available in 3000K and 4000K | Available in 3000K and 4000K | Available in 3000K and 4000K |
| Lumens (lm) | 3200 | 3200 | 3200 |
| Candelas (cd) | 16300 (24°) 7100 (45°) | 16300 (24°) 7100 (45°) | 16300 (24°) 7100 (45°) |
| Dimmable | Y | Y | Y |
| Hrs Lamp Life (L70) | 50,000 | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 | 25,000 |
| Beam Angle | Available in 24° and 45° | Available in 24° and 45° | Available in 24° and 45° |
| Weight (g) | 280 | 526 | 830 |
| Dimensions (LxWxH mm) | 176x176x42 (H=101 with THx) | 322x176x42 (H=101 with THx) | 467x176x42 (H=101 with THx) |
| Colour/Finish | White | White | White |
| Shape | Square surround | Rectangular surround | Rectangular surround |
| Hole Cut-Out (mm) | 160 x 160 | 306 x 160 | 452 x 160 |
| Min Ceiling Depth (mm) | 130 | 130 | 130 |
| Tilt Angle | 45° | 30° | 30° |
| Suitable Light Source | TECOH® THx | TECOH® THx | TECOH® THx |


Purchase TECOH® THx separately – **131740** (3000K/24°) and **131742** (4000K/24°) or **131758** (3000K/45°) and **131760** (4000K/45°). See page 148 for more information. Megaman recommends the **171905** non-dimming driver for 35W TECOH® THx, sold separately.



Below: 1 and 3-head frame variants



Dimensions...



Operating temperature -30°C to +40°C



Fixtures

Luster-LED High Bay
(190675 pictured)

LA3202
LA3203
LA3204

Features




This IP65 Megaman Luster-LED high bay fixture is designed with aluminium housing and has an integrated LED and built-in driver. It gives instant and high-quality light that is ideal for use in large indoor and outdoor areas, an LED alternative to 150W, 250W and 400W metal halide lamps that provides a huge reduction in power consumption. With up to 21000lm output, the 210W can be used at ambient temperatures of 50°C - perfect for extreme applications such as the roof top of a production factory and manufacturing bays. All parts of the luminaire are interchangeable - comprising the LED module with heat sink, a choice of aluminium or plastic reflector and optional aluminium or plastic cover, all sold separately. Please refer to page 121 for more information.

Specification

| UK Order Code > | 190670 | 190675 | 190677 |
|-----------------------|-----------|-----------|-----------|
| Watts | 65W | 110W | 210W |
| Colour Temp (K) /CRI | 4000 / 80 | 4000 / 80 | 4000 / 80 |
| Lumens (lm) | 7200 | 11000 | 21000 |
| Candelas (cd) | | | |
| - Aluminium reflector | 4500 | 6500 | 14000 |
| - Plastic reflector | 8500 | 12000 | 20000 |
| Dimmable | N | N | N |
| Hrs Lamp Life (L70) | 50,000 | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 | 25,000 |
| Beam Angle | | | |
| - Aluminium reflector | 90° | 90° | 90° |
| - Plastic reflector | 60° | 60° | 60° |
| Weight (g) | 3260 | 4260 | 6897 |
| Dimensions (H x D mm) | | | |
| - Aluminium reflector | 275x240 | 295x240 | 355x240 |
| - Plastic reflector | 318x335 | 318x355 | 318x415 |
| Colour/Finish | Black | Black | Black |

Purchase reflector and optional cover separately. See page 121 for more information.


190670



190675




190677



Note - the above lighting data and dimensions represent use of the aluminium reflector. The data will differ using the plastic reflector as shown in the table above right.

Dimensions...



Operating temperature -30°C to +40°C



Fixtures

Luster-LED High Bay Accessories
Reflectors and optional Covers

LA3129
LA3130
LA3205
LA0105

Features




A choice of aluminium or plastic reflector and optional glass or plastic cover is available for the Megaman Luster-LED, all sold separately.

Specification

| UK Order Code > | 190678 | 190680 | 190682 | 190684 |
|----------------------|-------------------------|-----------------------------|---|-----------------------------------|
| Luster-LED accessory | 90° Aluminium Reflector | 60° Polycarbonate Reflector | Optional Polycarbonate Cover (for 190680) | Optional Glass Cover (for 190678) |



Luster-LED in use...



65W Luster-LED, 65 or 110W Luster-LED, 110W Luster-LED, 210W Luster-LED





Fixtures

F28249RC


Carlo Downlight for TECOH® RDx

Features




Megaman's TECOH® RDx is an LED light source that is an ideal alternative to halogen lighting in retail and other applications. It is unique in that the module can be driven at different currents to achieve varying lumen output. The TECOH® RDx module and non-dimming driver is included with this downlight. Please refer to **page 149** for more information.

703049/703081/703051




703047



Specification

| UK Order Code > | 703049 | 703081 | 703047 | 703051 |
|------------------------|------------|------------|------------|------------|
| Watts | 39W | 39W | 27W | 39W |
| Colour Temp (K) / CRI | 3000 / 82 | 3000 / 82 | 4000 / 82 | 4000 / 82 |
| Lumens (lm) | 3600 | 3600 | 3400 | 4500 |
| Candelas (cd) | 7500 | 7500 | 5200 | 7500 |
| Dimmable | N | N | N | N |
| Hrs Lamp Life (L70) | 50,000 | 50,000 | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 | 25,000 | 25,000 |
| Beam Angle | 35° | 35° | 35° | 35° |
| Weight (g) | 1065 | 1065 | 1065 | 1065 |
| Dimensions (H x D mm) | 135x170 | 135x170 | 135x170 | 135x170 |
| Colour/Finish | White | Silver | White | White |
| Shape | Round | Round | Round | Round |
| Hole Cut-Out (mm) | 155 | 155 | 155 | 155 |
| Min Ceiling Depth (mm) | 145 | 145 | 145 | 145 |
| Tilt Angle | 45° | 45° | 45° | 45° |
| Rotation | 355° | 355° | 355° | 355° |
| Suitable Light Source | TECOH® RDx | TECOH® RDx | TECOH® RDx | TECOH® RDx |

Dimensions...



Operating temperature -30°C to +40°C



Fixtures

F28249RC-p


Carlo Downlight Perfect White Dimming

Features



The Megaman Carlo range of recessed adjustable LED downlights offers excellent lighting performance using Megaman's Perfect White technology. The Carlo offers a high cut-off angle of 40° to ensure visual comfort and an ultra-flexible 45° tilting angle with 355° rotation angle. TECOH® RDx LED module and driver is included with this downlight. Please refer to **page 149** for more information.

131724




Specification

| UK Order Code > | 131724 |
|------------------------|------------|
| Watts | 34W |
| Colour Temp (K) / CRI | 3000 / 82 |
| Lumens (lm) | 2400 |
| Candelas (cd) | 5500 |
| Dimmable | Y |
| Hrs Lamp Life (L70) | 50,000 |
| Hrs Lamp Life (L90) | 25,000 |
| Beam Angle | 35° |
| Weight (g) | 1065 |
| Dimensions (H x D mm) | 135x170 |
| Colour/Finish | White |
| Shape | Round |
| Hole Cut-Out (mm) | 155 |
| Min Ceiling Depth (mm) | 145 |
| Tilt Angle | 45° |
| Rotation | 355° |
| Suitable Light Source | TECOH® RDx |

Please contact our sales office for further dimming information.

Dimensions...



Operating temperature -30°C to +40°C



Fixtures

F29349RC


Vito Downlight for TECOH® RDx

Features



Megaman's TECOH® RDx is an LED module that is an ideal alternative to halogen lighting in retail and other applications. The TECOH® RDx module and driver is included with this downlight. Please refer to **page 149** for more information.


703460/703750



Specification

| UK Order Code > | 703460 | 703750 |
|------------------------|------------|------------|
| Watts | 45W | 45W |
| Colour Temp (K) / CRI | 3000 / 82 | 3000 / 82 |
| Lumens (lm) | 4100 | 4100 |
| Candelas (cd) | 9000 | 9000 |
| Dimmable | N | N |
| Hrs Lamp Life (L70) | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 |
| Beam Angle | 35° | 35° |
| Weight (g) | 1042 | 1042 |
| Dimensions (H x D mm) | 135x170 | 135x170 |
| Colour/Finish | White | Silver |
| Shape | Round | Round |
| Hole Cut-Out (mm) | 155 | 155 |
| Min Ceiling Depth (mm) | 133 | 133 |
| Tilt Angle | 30° | 30° |
| Suitable Light Source | TECOH® RDx | TECOH® RDx |

Dimensions...



Operating temperature -30°C to +40°C



Fixtures

F29349RC-p


Vito Downlight Perfect White Dimming

Features



The Megaman Vito range of integrated recessed adjustable LED downlights are an energy saving solution for shop and general lighting. The gimbal construction provides multi directional tilting. The TECOH® 48W RDx LED module is included with this downlight. Order driver separately - code **BAG10105112**. Please refer to **page 149** for more information.

131516




Specification

| UK Order Code > | 131516 |
|------------------------|------------|
| Watts | 45W |
| Colour Temp (K) / CRI | 3000 / 82 |
| Lumens (lm) | 4100 |
| Candelas (cd) | 7000 |
| Dimmable | Y |
| Hrs Lamp Life (L70) | 50,000 |
| Hrs Lamp Life (L90) | 25,000 |
| Beam Angle | 35° |
| Weight (g) | 1045 |
| Dimensions (H x D mm) | 135x170 |
| Colour/Finish | White |
| Shape | Round |
| Hole Cut-Out (mm) | 155 |
| Min Ceiling Depth (mm) | 133 |
| Tilt Angle | 30° |
| Suitable Light Source | TECOH® RDx |

Please contact our sales office for further dimming information.

Dimensions...



Operating temperature -30°C to +40°C



Fixtures

F25245RC

Genoa

Downlight for TECOH® CFx
Fixture only

Features



Megaman Genoa provides a total energy saving solution for general lighting with wide beam optics of 90°. Megaman's TECOH® CFx range of high performance twist-lock LED light engines have an integrated driver for general lighting and are designed in line with Zhaga specifications. TECOH® CFx light engine sold separately, available in dimming and non-dimming options detailed below. Please refer to **page 150** for more information.


Specification

| UK Order Code > | 703240 |
|------------------------|------------|
| Weight (g) | 800 |
| Dimensions (H x D mm) | 101x150 |
| Colour/Finish | White |
| Shape | Round |
| Hole Cut-Out (mm) | 140 |
| Min Ceiling Depth (mm) | 98 |
| Suitable Light Source | TECOH® CFx |

The TECOH® CFx light engine (sold separately)



Dimensions...



Fixtures

F54952RC
F55052RC

Abby

Pin-Hole Downlight for TECOH® THx
Fixture only

Features



The Megaman Abby fixture works with the serviceable 10.5W TECOH® THx LED light engine, delivering excellent lighting performance for the replacement of traditional 50W halogen MR16 and PAR16 pin-hole downlights. The Abby is available in a fixed pin-hole design for accent lighting and adjustable version with 30° tilt angle for wall wash applications. Full recessed design with black baffle provides lighting effect with no glare, ideal for dramatic accent lighting. Works with TECOH® THx LED light engine, sold separately. Please refer to **page 147** for more information. No driver required.


Specification

| UK Order Code > | 190651 | 190653 |
|------------------------|------------------------------|------------------------------|
| Watts | For 10.5W THx | For 10.5W THx |
| Colour Temp (K) /CRI | Available in 2800K and 4000K | Available in 2800K and 4000K |
| Lumens (lm) | 900 | 900 |
| Candelas (cd) | 3500 (24°) 1900 (36°) | 3500 (24°) 1900 (36°) |
| Dimmable | N | N |
| Hrs Lamp Life (L70) | 25,000 | 25,000 |
| Beam Angle | Available in 24° and 36° | Available in 24° and 36° |
| Weight (g) | 44 | 43 |
| Dimensions (H x D mm) | 30x80 (H=95 with THx) | 30x80 (H=95 with THx) |
| Colour/Finish | White | White |
| Shape | Fixed | Adjustable |
| Hole Cut-Out (mm) | 68 | 68 |
| Min Ceiling Depth (mm) | 93 | 96 |
| Tilt Angle | - | 30° |
| Suitable Light Source | TECOH® THx | TECOH® THx |

Purchase TECOH® THx separately -
131750 (2800K/24°) and
131752 (4000K/24°)
or 131754 (2800K/36°) and
131756 (4000K/36°).
See page 147 for more information.



Dimensions...





Fixtures

F25845SM

Cortona

Floodlight and PIR for TECOH® CFx
Fixture only

Features



Megaman Cortona offers IP54 protection against dust and water, suitable for outdoor applications such as signage, gate areas or facades. Megaman's TECOH® CFx range of high performance twist-lock LED light engines have an integrated driver for general lighting and are designed in line with Zhaga specifications. TECOH® CFx light engine sold separately. Please refer to **page 150** for more information.


Specification

| UK Order Code > | 703294 |
|-----------------------|-------------|
| Weight (g) | 1357 |
| Dimensions (WxHxD mm) | 185x118x272 |
| Colour/Finish | Black |
| Tilt Angle | 115° |
| Suitable Lamps | TECOH® CFx |



The TECOH® CFx light engine (sold separately)

Dimensions...



Fixtures

Leora

GU10 Fire Rated Fixed Downlight
Fixture only

Features



The Leora fixed fire rated downlight is designed for the Megaman LED 4W, 5W, 5.5W, 6W or 7W GU10. Purchase lamp separately.


Specification

| UK Order Code > | 518349 | 518627 | 518462 |
|-----------------------|-------------------------|-------------------------|-------------------------|
| Dimensions (H x D mm) | 108x90 | 108x90 | 108x90 |
| Colour/Finish | White | Satin Chrome | Chrome |
| Shape | Round | Round | Round |
| Hole Cut-Out (mm) | 71 | 71 | 71 |
| Suitable Lamps | 4, 5, 5.5, 6 or 7W GU10 | 4, 5, 5.5, 6 or 7W GU10 | 4, 5, 5.5, 6 or 7W GU10 |

Suitable Megaman GU10's - 4W, 5W, 5.5W, 6W and 7W. (sold separately)



Dimensions...



This product is not manufactured by Megaman.





Fixtures

Alina

GU10 Fire Rated Tilt Downlight
Fixture only

Features



The Alina tilt fire rated downlight is designed for the Megaman LED 4W, 5W, 5.5W, 6W or 7W GU10. Purchase lamp separately.


Specification

| UK Order Code > | 518291 | 518301 | 518761 |
|-----------------------|-------------------------|-------------------------|-------------------------|
| Dimensions (H x D mm) | 110x96 | 110x96 | 110x96 |
| Colour/Finish | White | Satin Chrome | Chrome |
| Shape | Round | Round | Round |
| Hole Cut-Out (mm) | 85 | 85 | 85 |
| Suitable Lamps | 4, 5, 5.5, 6 or 7W GU10 | 4, 5, 5.5, 6 or 7W GU10 | 4, 5, 5.5, 6 or 7W GU10 |

Suitable Megaman GU10's - 4W, 5W, 5.5W, 6W and 7W. (sold separately)



Dimensions...



This product is not manufactured by Megaman.



Fixtures

Helios

GU10 Fire Rated Shower Downlight
Fixture only

Features



The Helios shower fire rated downlight is designed for the Megaman LED 4W, 5W, 5.5W, 6W or 7W GU10. Purchase lamp separately.


Specification

| UK Order Code > | 518016 | 518076 | 518409 |
|-----------------------|-------------------------|-------------------------|-------------------------|
| Dimensions (H x D mm) | 112x88 | 112x88 | 112x88 |
| Colour/Finish | White | Satin Chrome | Chrome |
| Shape | Round | Round | Round |
| Hole Cut-Out (mm) | 74 | 74 | 74 |
| Suitable Lamps | 4, 5, 5.5, 6 or 7W GU10 | 4, 5, 5.5, 6 or 7W GU10 | 4, 5, 5.5, 6 or 7W GU10 |

Suitable Megaman GU10's - 4W, 5W, 5.5W, 6W and 7W. (sold separately)



Dimensions...



This product is not manufactured by Megaman.



Fixtures

Verona
GU10 Downlight
Fixture only

F30617RC
F30717RC

Features



The Megaman Verona recessed downlight, with fixed pin-hole design for accent lighting, is designed for the Megaman LED range of GU10's. The oval version allows for a 30° tilt angle. Purchase lamp separately. Suitable lamps - 4W, 5W, 5.5W, 6W or 7W GU10.


Specification

| UK Order Code > | 190649 | 190624 | 190645 |
|------------------------|-------------------------|-------------------------|-------------------------|
| Weight (g) | 245 | 245 | 245 |
| Dimensions (H x D mm) | 137x95 | 137x95 | 137x95 |
| Colour/Finish | White | Black | White |
| Shape | Round | Round | Oval |
| Hole Cut-Out (mm) | 85 | 85 | 85 |
| Min Ceiling Depth (mm) | 135 | 135 | 135 |
| Tilt Angle | - | - | 30° |
| Suitable Lamps | 4, 5, 5.5, 6 or 7W GU10 | 4, 5, 5.5, 6 or 7W GU10 | 4, 5, 5.5, 6 or 7W GU10 |

Suitable Megaman GU10's - 4W, 5W, 5.5W, 6W and 7W. (sold separately)



Dimensions...




Fixtures

Miro
GU10 Tilt Downlight
Fixture only

F01517RC

Features



The Megaman Miro, designed for Megaman LED GU10's, is a stylish recessed downlight, with adjustable tilting angle of 30°. Suitable lamps - 4W, 5W, 5.5W, 6W or 7W GU10. Purchase lamp separately.


Specification

| UK Order Code > | 190375 |
|------------------------|-------------------------|
| Weight (g) | 70 |
| Dimensions (H x D mm) | 92x85 |
| Colour/Finish | Silver |
| Shape | Round |
| Hole Cut-Out (mm) | 75 |
| Min Ceiling Depth (mm) | 84 |
| Tilt Angle | 30° |
| Suitable Lamps | 4, 5, 5.5, 6 or 7W GU10 |

Suitable Megaman GU10's - 4W, 5W, 5.5W, 6W and 7W. (sold separately)



Dimensions...





Fixtures

F31217RC

Lucca
GU10 Tilt Downlight
Fixture only

Features



The Megaman Lucca recessed downlight is designed for Megaman LED GU10's, with a 30° tilting angle. Suitable lamps - 4W, 5W, 5.5W, 6W or 7W GU10. Purchase lamp separately.


Specification

| UK Order Code > | 190275 |
|------------------------|-------------------------|
| Weight (g) | 75 |
| Dimensions (H x D mm) | 33x95 |
| Colour/Finish | White |
| Shape | Round |
| Hole Cut-Out (mm) | 85 |
| Min Ceiling Depth (mm) | 90 |
| Tilt Angle | 30° |
| Suitable Lamps | 4, 5, 5.5, 6 or 7W GU10 |

Suitable Megaman GU10's - 4W, 5W, 5.5W, 6W and 7W. (sold separately)



Dimensions...



Fixtures

L0302RC

Max
GU10 Tilt Downlight
Fixture only

Features



Adjustable downlight suitable for LED GU10's. Suitable lamps - 4W, 5W, 5.5W, 6W or 7W GU10. Purchase lamp separately.


Specification

| UK Order Code > | 749245 | 749298 |
|------------------------|-------------------------|-------------------------|
| Weight (g) | 30 | 30 |
| Dimensions (H x D mm) | 80x36 | 80x36 |
| Colour/Finish | White | Silver |
| Shape | Round | Round |
| Hole Cut-Out (mm) | 70 | 70 |
| Min Ceiling Depth (mm) | 81 | 81 |
| Tilt Angle | 30° | 30° |
| Suitable Lamps | 4, 5, 5.5, 6 or 7W GU10 | 4, 5, 5.5, 6 or 7W GU10 |

Suitable Megaman GU10's - 4W, 5W, 5.5W, 6W and 7W. (sold separately)



Dimensions...





Fixtures

Planex
GX53 Downlight
Fixture only

L0504RC
F01018RC

Features



Ideal for any ceiling recess with a limited depth, the Megaman Planex has a slim profile suitable for small cabinets and furniture lighting. Purchase lamp separately.


Specification

| UK Order Code > | 703230 | 703253 |
|------------------------|--------------|--------------|
| Weight (g) | 75 | 75 |
| Dimensions (H x D mm) | 39x104 | 39x104 |
| Colour/Finish | White | Silver |
| Shape | Round | Round |
| Hole Cut-Out (mm) | 90 | 90 |
| Min Ceiling Depth (mm) | 34 | 34 |
| Suitable Lamps | 5W / 7W GX53 | 5W / 7W GX53 |

Suitable Megaman GX53 - 5W/7W. (sold separately)



Dimensions...



Fixtures

Mosaic
GU10 Tilt Tracklight
Fixture only

F11517TK

Features



The Megaman Mosaic is a flexible, multi-directional 3-circuit track light fitting for LED GU10's, with adjustable 330° rotation and 90° tilting angle. Purchase lamp separately.


Specification

| UK Order Code > | 190516 | 190460 |
|-----------------------|-------------------------|-------------------------|
| Weight (g) | 161 | 161 |
| Dimensions (H x D mm) | 225x77 | 225x77 |
| Colour/Finish | White | Black |
| Tilt Angle | 90° | 90° |
| Rotation | 330° | 330° |
| Suitable Lamps | 4, 5, 5.5, 6 or 7W GU10 | 4, 5, 5.5, 6 or 7W GU10 |

Suitable Megaman GU10's - 4W, 5W, 5.5W, 6W and 7W. (sold separately)



Dimensions...



FIXTURES | Planex GX53 Downlight

FIXTURES | Mosaic GU10 Tilt Tracklight



Fixtures

F13117TK

Toby
AR111 GU10 Tracklight
Fixture only

Features



The Megaman Toby is a flexible multi-directional 3-circuit track light fitting for Megaman's AR111 GU10, with stylish aluminium finish and 340° adjustable rotation and 170° tilting angle. Suitable lamp - AR111 GU10. Purchase lamp separately.


Specification

| UK Order Code > | 190490 | 190763 |
|-------------------------|------------|------------|
| Weight (g) | 237 | 237 |
| Dimensions (L x Dia mm) | 210x117 | 210x117 |
| Colour/Finish | White | Black |
| Tilt Angle | 170° | 170° |
| Rotation | 340° | 340° |
| Suitable Lamps | AR111 GU10 | AR111 GU10 |

Suitable Megaman AR111 GU10 - 15W. (sold separately)



Dimensions...



Fixtures

F26817TK

Alda
AR111 GU10 Tracklight
Fixture only

Features



The Megaman Alda 3-circuit track light fitting has a fully adjustable head and arm rotation for multi-directional lighting applications. Designed for Megaman's LED AR111 GU10. Suitable lamp - AR111 GU10. Purchase lamp separately.


Specification

| UK Order Code > | 190852 | 190724 |
|-----------------------|------------|------------|
| Weight (g) | 540 | 540 |
| Dimensions (H x D mm) | 273x124 | 273x124 |
| Colour/Finish | White | Black |
| Tilt Angle | 90° | 90° |
| Rotation | 330° | 330° |
| Suitable Lamps | AR111 GU10 | AR111 GU10 |

Suitable Megaman AR111 GU10 - 15W. (sold separately)



Dimensions...





Fixtures

F25343TK

Modena Tracklight for 24W TECOH® MHx

Features



Megaman's TECOH® MHx is the first OEM LED solution that directly competes with Ceramic Metal Halide lamps. This 3-circuit tracklight fitting comes with driver, MHx module sold separately. Change the beam angle with 25° (170538) and 45° (170294) reflectors. TECOH® MHx can be dimmed, it operates on 1-10V dimming protocol and the track spot has a special adaptor. To achieve dimming this track spot has to be used with global control track that is capable of accommodating the special adaptor. Standard Megaman track is not compatible, please call for assistance. Please refer to **page 151** for more information.


170437/170468



Specification

| UK Order Code > | 170437 | 170468 |
|-----------------------|----------------------------|----------------------------|
| Watts | For 24W MHx | For 24W MHx |
| Colour Temp (K) /CRI | Available in 3000K & 4000K | Available in 3000K & 4000K |
| Lumens (lm) | 2300 (3000K) 2500 (4000K) | 2300 (3000K) 2500 (4000K) |
| Candelas (cd) | 4050 | 4050 |
| Dimmable | Y | Y |
| Hrs Lamp Life (L70) | 50,000 | 50,000 |
| Beam Angle | 35° | 35° |
| Weight (g) | 1552 | 1552 |
| Dimensions (LxWxD mm) | 219x165x110 | 219x165x110 |
| Colour/Finish | Black | White |
| Tilt Angle | 90° | 90° |
| Rotation | 330° | 330° |
| Suitable Light Source | TECOH® MHx | TECOH® MHx |

Dimensions...



Operating temperature -30°C to +40°C




Fixtures

F25349TK

Modena Tracklight for 50W TECOH® RDx

Features



Megaman's TECOH® RDx is an LED light source that is an ideal alternative to halogen lighting in retail and other applications. It is unique in that the module can be driven at different currents to achieve varying lumen output. The TECOH® RDx 50W module and driver is included with this tracklight.


131537



Specification

| UK Order Code > | 703491 | 703516 |
|-----------------------|-----------------------|-----------------------|
| Watts | 55W | 55W |
| Colour Temp (K) /CRI | 3000 / 82 | 3000 / 82 |
| Lumens (lm) | 4100 | 4100 |
| Candelas (cd) | 12000 | 12000 |
| Dimmable | N | N |
| Hrs Lamp Life (L70) | 50,000 | 50,000 |
| Beam Angle | 25° | 25° |
| Weight (g) | 1908 (Luminaire only) | 1908 (Luminaire only) |
| Dimensions (LxWxD mm) | 219x165x110 | 219x165x110 |
| Colour/Finish | White | Black |
| Tilt Angle | 90° | 90° |
| Rotation | 330° | 330° |
| Suitable Light Source | TECOH® RDx | TECOH® RDx |

Dimensions...



Operating temperature -30°C to +40°C



Fixtures

Modena Tracklight Perfect White Dimming


F25349TK-p
F28049TK-p

Features



The Megaman Modena 3-circuit track light fitting, with Perfect White technology, is available in 2 wattages. TECOH® RDx module and driver included. Please refer to **page 149** for more information.

131537




131527



Specification

| UK Order Code > | 131537 | 131527 |
|-------------------------|------------|-------------|
| Watts | 29 | 53 |
| Colour Temp (K) /CRI | 3000 / 82 | 3000 / 82 |
| Lumens (lm) | 1650 | 3100 |
| Candelas (cd) | 5300 | 13000 |
| Dimmable | Y | Y |
| Hrs Lamp Life (L70) | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 |
| Beam Angle | 25° | 25° |
| Weight (g) | 956 | 1829 |
| Dimensions (L x Dia mm) | 199x127x80 | 219x165x110 |
| Colour/Finish | White | White |
| Tilt Angle | 90° | 90° |
| Rotation | 330° | 330° |
| Suitable Light Source | TECOH® RDx | TECOH® RDx |

Dimensions...




Operating temperature -30°C to +40°C



Fixtures


3-Circuit Track System Surface Mounting Track lengths




| UK Order Code > | 161001 | 161003 | 161004 | 161006 |
|-----------------|--------|--------|--------|--------|
| Colour | White | Black | White | Black |
| Length (mm) | 1000 | 1000 | 2000 | 2000 |

Live end connectors

| UK Order Code > | 161011 | 161013 |
|-----------------|--------|--------|
| Colour | White | Black |
| Feed | Left | Left |




| UK Order Code > | 161014 | 161016 |
|-----------------|--------|--------|
| Colour | White | Black |
| Feed | Right | Right |



End cap

| UK Order Code > | 161017 | 161019 |
|-----------------|--------|--------|
| Colour | White | Black |



Mechanical coupler

To connect two track sections


| UK Order Code > | 161020 | 161022 |
|-----------------|--------|--------|
| Colour | White | Black |



Mechanical insulated coupler

To connect two track sections

| UK Order Code > | 161023 | 161025 |
|-----------------|--------|--------|
| Colour | White | Black |



Straight electrical-mechanical coupler

To connect two track sections electrically and mechanically. With centre feed option.


| UK Order Code > | 161026 | 161028 |
|-----------------|--------|--------|
| Colour | White | Black |



L-coupler left

To connect two track sections electrically and mechanically at a 90° angle.

| UK Order Code > | 161029 | 161031 |
|-----------------|--------|--------|
| Colour | White | Black |




This product is not manufactured by Megaman.

3-Circuit Track System cont'd

L-coupler right

To connect two track sections electrically and mechanically at a 90° angle.


| UK Order Code > | 161032 | 161034 |
|-----------------|--------|--------|
| Colour | White | Black |



T-coupler left - outside

To connect three track sections electrically and mechanically into a T-configuration.


| UK Order Code > | 161035 | 161037 |
|-----------------|--------|--------|
| Colour | White | Black |



T-coupler left - inside

To connect three track sections electrically and mechanically into a T-configuration.

| UK Order Code > | 161038 | 161040 |
|-----------------|--------|--------|
| Colour | White | Black |



T-coupler right - outside

To connect three track sections electrically and mechanically into a T-configuration.


| UK Order Code > | 161041 | 161043 |
|-----------------|--------|--------|
| Colour | White | Black |



T-coupler right - inside

To connect three track sections electrically and mechanically into a T-configuration.


| UK Order Code > | 161044 | 161046 |
|-----------------|--------|--------|
| Colour | White | Black |



X coupler

To connect four track sections electrically and mechanically into a cross configuration.


| UK Order Code > | 161047 | 161049 |
|-----------------|--------|--------|
| Colour | White | Black |



Flexible coupler

To connect two track sections electrically and mechanically at any angle up to 90°.

| UK Order Code > | 161050 | 161052 |
|-----------------|--------|--------|
| Colour | White | Black |



Ceiling wall mounting kit

| UK Order Code > | 161053 | 161055 |
|-----------------|--------|--------|
| Colour | White | Black |

Suspension kit

Kit with 6mm x 1meter suspension rod.

| UK Order Code > | 161056 | 161058 |
|-----------------|--------|--------|
| Colour | White | Black |

This product is not manufactured by Megaman.

MEGAMAN®

TECOH® Modules and Light Engines

| | |
|---------------------------------------|-----|
| TECOH® THx for VERSOFIT | 150 |
| TECOH® THx for Zeki 50mm and Abby | 151 |
| TECOH® THx for Zeki 111mm | 152 |
| TECOH® RDx for Carlo, Vito and Modena | 153 |
| TECOH® CFx for Genoa and Cortona | 154 |
| TECOH® MHx for Modena | 155 |



High Performance LED Light Engines and Modules

The Megaman TECOH® LED portfolio consists of a range of high performance 240V LED light engines and low voltage LED modules.

TECOH® comes in different shapes, sizes and lumen packages to address a wide range of different applications. The range includes socketable and non-socketable solutions with either integrated (LED Light Engine) or non-integrated (module) electronic driver.

Although traditionally an OEM product, these modules fit several of the Megaman fixtures throughout this catalogue – either coming as standard with the fixture or sold separately.

Please refer back to the fixture page in this catalogue for more information about what TECOH® module and driver (where applicable) is required.



VERSOFIT

Fixtures

TH0105.5d



8W
TECOH® THx Light Engine

Features



The Megaman TECOH® THx light engine, with honeycomb lens, is designed for the VERSOFIT downlight range (pages 95 to 97) - allowing colour temperature change. This light engine offers an excellent alternative to MR16 and PAR halogen lamps. No driver required.

Specification

| UK Order Code > | 519804 | 519706 |
|-------------------------|-----------|-----------|
| Watts | 8W | 8W |
| Colour Temp (K) / CRI | 2800 / 80 | 4000 / 80 |
| Lumens (lm) | 600 | 630 |
| Candelas (cd) | 650 | 650 |
| Dimmable | Y | Y |
| Hrs Lamp Life (L70) | 30,000 | 30,000 |
| Hrs Lamp Life (L90) | - | - |
| Beam Angle | 36° | 36° |
| Weight (g) | 154 | 154 |
| Dimensions (L x Dia mm) | 66x50 | 66x50 |

Operating temperature -30°C to +40°C



Fixtures

TH0309-24
TH0309-36

10.5W
TECOH® THx Light Engine

Features



Megaman's 10.5W TECOH® THx LED light engine is suitable for use in the Zeki 50mm (page 118) and Abby (page 127) Fixtures, and no driver is required. The light engine needs to be purchased separately.

Specification

| UK Order Code > | 131750 | 131752 | 131754 | 131756 |
|-------------------------|-----------|-----------|-----------|-----------|
| Watts | 10.5W | 10.5W | 10.5W | 10.5W |
| Colour Temp (K) / CRI | 2800 / 80 | 4000 / 80 | 2800 / 80 | 4000 / 80 |
| Lumens (lm) | 900 | 900 | 900 | 900 |
| Candelas (cd) | 3500 | 3500 | 1900 | 1900 |
| Dimmable | N | N | N | N |
| Hrs Lamp Life (L70) | 25,000 | 25,000 | 25,000 | 25,000 |
| Beam Angle | 24° | 24° | 36° | 36° |
| Weight (g) | 205 | 205 | 205 | 205 |
| Dimensions (L x Dia mm) | 72x50 | 72x50 | 72x50 | 72x50 |

Operating temperature -30°C to +40°C



NEW

Fixtures

35W TECOH® THx Module

TH0532-24
TH0532-45

Features



Megaman's 10.5W TECOH® THx LED module is suitable for use in the Zeki 111mm Fixture (page 119), and a driver is required. The module and driver should be purchased separately to the Fixture.

Specification

| UK Order Code > | 131740 | 131742 | 131758 | 131760 |
|-------------------------|-----------|-----------|-----------|-----------|
| Watts | 35W | 35W | 35W | 35W |
| Colour Temp (K) / CRI | 3000 / 80 | 4000 / 80 | 3000 / 80 | 4000 / 80 |
| Lumens (lm) | 3200 | 3200 | 3200 | 3200 |
| Candelas (cd) | 16300 | 16300 | 7100 | 7100 |
| Dimmable | Y | Y | Y | Y |
| Hrs Lamp Life (L70) | 50,000 | 50,000 | 50,000 | 50,000 |
| Hrs Lamp Life (L90) | 25,000 | 25,000 | 25,000 | 25,000 |
| Beam Angle | 24° | 24° | 45° | 45° |
| Weight (g) | 620 | 620 | 620 | 620 |
| Dimensions (L x Dia mm) | 92x111 | 92x111 | 92x111 | 92x111 |

Driver for 35W THx Module



Specification

| UK Order Code > | 171905 |
|------------------------------|---------|
| Rated Voltage (V) | 220-240 |
| Surge Voltage (V) | 1000 |
| Output Voltage with Load (V) | 25-28 |
| Input Current (mA) | 217 |
| Output Current (mA) | 1050 |

Operating temperature -30°C to +40°C



Fixtures

TECOH® RDx Modules

RD0121M
RD0231M
RD0343M
RD0555M

Features



The TECOH® RDx, designed in line with Zhaga Interface Specification Book 3, are round disc LED modules that are non-socketable and require an external driver. They are an ideal alternative to halogen lighting in retail. Although an OEM product, these modules come with several Megaman fixtures - the Carlo (pg 122/123) and Vito (pg 124/125) downlights and Modena tracklight (pg 141/142). Please see the relevant pages for more information.

Specification

| UK Order Code > | 170129 | 170130 | 170131 | 170135 | 170137 | 170139 | 170148 | 170159 |
|-----------------------|------------------------|------------------------|------------------------|------------------------|------------------------|------------------------|------------------------|------------------------|
| Watts | 24W | 24W | 31W | 31W | 48W | 48W | 60W | 60W |
| Colour Temp (K) / CRI | 2800 / 80 | 4000 / 80 | 2800 / 80 | 4000 / 80 | 2800 / 80 | 4000 / 80 | 2800 / 80 | 4000 / 80 |
| Lumens (lm) | 2890 | 3200 | 3370 | 3740 | 3675 | 4095 | 6020 | 6620 |
| Hr lamp life (L70) | 50,000 | 50,000 | 50,000 | 50,000 | 50,000 | 50,000 | 50,000 | 50,000 |
| Weight (g) | 12 | 12 | 12 | 12 | 12 | 12 | 12 | 12 |
| Dimensions (D x H mm) | 50x6.2 |
| Suitable fixtures | Carlo, Vito and Modena |

Operating temperature -30°C to +40°C



Fixtures

TECOH® Cfx
Light EnginesCF0112GEN2
CF0120GEN2
CF0120d/PHJ65d

Features



Megaman's TECOH® Cfx range of high performance twist-lock LED light engines has an integrated driver for general lighting and is designed in line with Zhaga specifications. With dimming capabilities, the TECOH® Cfx is ideal for use in downlights, replacing conventional light sources. Although an OEM product, these light engines are suited for Megaman's Genoa downlight (pg 126) and Cortona floodlight (pg 128). Please see the relevant pages for more information.

Specification

| UK Order Code > | 170762 | 170735 | 170469 | 170286 | 170851 | 170839 |
|-----------------------|-------------------|-------------------|-------------------|-------------------|-------------------|-------------------|
| Watts | 15W | 15W | 26W | 26W | 30W | 30W |
| Colour Temp (K) / CRI | 2800 / 80 | 4000 / 80 | 2800 / 80 | 4000 / 80 | 2800 / 80 | 4000 / 80 |
| Lumens (lm) | 1200 | 1200 | 2000 | 2000 | 1800 | 2000 |
| Hr lamp life (L70) | 35,000 | 35,000 | 35,000 | 35,000 | 35,000 | 35,000 |
| Dimmable | N | N | N | N | Y | Y |
| Weight (g) | 118 | 118 | 118 | 118 | 118 | 118 |
| Dimensions (D x H mm) | 70x41 | 70x41 | 70x41 | 70x41 | 70x41 | 70x41 |
| Suitable fixtures | Genoa and Cortona |

Operating temperature -30°C to +40°C



Fixtures

TECOH® MHx
Modules

Features



Megaman's TECOH® MHx is the an LED capsule, that directly competes with Ceramic Metal Halide lamps. With its unique design, it is the ideal lighting solution for a variety of shop lighting applications. Although an OEM product, these capsules are suited to Megaman's Modena MHx fixture. Please see page 140 for more information. Compatible for use with Megaman driver 171903.

Specification

| UK Order Code > | 170965 | 170912 |
|-----------------------|-----------|-----------|
| Watts | 24W | 24W |
| Colour Temp (K) / CRI | 3000 / 94 | 4000 / 94 |
| Lumens (lm) | 2300 | 2500 |
| Hr lamp life (L70) | 35,000 | 35,000 |
| Dimmable | Y | Y |
| Weight (g) | 86 | 86 |
| Dimensions (D x H mm) | 42x67 | 42x67 |
| Suitable fixtures | Modena | Modena |

Driver for 24W MHx Module



Specification

| UK Order Code > | 171903 |
|------------------------------|---------|
| Rated Voltage (V) | 220-240 |
| Surge Voltage (V) | 1000 |
| Output Voltage with Load (V) | 34 |
| Input Current (mA) | 145 |
| Output Current (mA) | 700 |

Operating temperature -30°C to +40°C

MEGAMAN®

Emergency Lighting



A back up solution in the event of power failure in critical areas.

Megaman now offer a non-maintained emergency LED solution, designed to be ultra compact and easy to install.

Despite only being 12mm in diameter, it delivers a powerful light output during an emergency of up to 3 hours.

MEGAMAN® EMERGENCY PACKS | A solution in the event of power failure in critical areas



Emergency Packs

Emergency LED Solution

Features

06
PRODUCT
DISCOUNT GROUP

This non-maintained emergency LED solution enables unobtrusive, seamless integration into a wide range of luminaires and despite only being 12mm in diameter; it delivers a powerful light output during an emergency. Ultra compact, with integral status indicator LED. For more information please visit the website www.megamanuk.com.




Actual size

Specification

| UK Order Code > | EGMFIT |
|------------------------------|--------------|
| Lumen output | 80 |
| Dimensions of LED (H x D mm) | 26.5x12 |
| Hole cut-out (mm) | 10 |
| Weight of LED (g) | 20 |
| Battery Duration | 3 hours |
| Ambient Temp. | 0°C - +45°C |
| Rated supply | 230V 50-60Hz |

Please check our website for new emergency solutions to the Megaman range coming later this year.

Dimensions...



This product is not manufactured by Megaman.

MEGAMAN®

All information stated is correct at the time of printing and subject to change without prior notice.

© MEGAMAN® (UK) LTD
SEPTEMBER 2016



In use...



Megaman's
AR111 LED

RIVER ISLAND, LONDON

