



FXMQ200-250MA



BRC1E51A



BRC4C66

### Comfort & Efficiency

- › Blends unobtrusively with any interior décor: only the suction and discharge grilles are visible
- › Home leave operation saves energy during absence

### Flexible Installation

- › Up to 270 Pa external static pressure (ESP) allows extensive ductwork runs and flexible application: ideal for use in large areas
- › Up to 31.5 kW in heating mode



\* Not connectable to VRV\*III-S (RXYSQ-P8V1, RXYSQ-P8Y1)



## SPECIFICATIONS

INDOOR UNITS				FXMQ200MA	FXMQ250MA
Cooling capacity	Nom.		kW	22.4	28.0
Heating capacity	Nom.		kW	25.0	31.5
Power input - 50Hz	Cooling	Nom.	kW	1.294	1.465
	Heating	Nom.	kW	1.294	1.465
Dimensions	Unit	HeightxWidthxDepth	mm	470x1,380x1,100	
Weight	Unit		kg	137	
Fan-Air flow rate - 50Hz	Cooling	High/Low	m <sup>3</sup> /min	58/50	72/62
Fan-External static pressure - 50Hz	High/Nom.		Pa	221/132	270/147
Sound pressure level	Cooling	High/Low	dBA	48/45	
Refrigerant	Type			R-410A	
Piping connections	Liquid/OD/Gas/OD/Drain		mm	9.52/19.1/PS1B	9.52/22.2/PS1B
Power supply	Phase / Frequency / Voltage		Hz / V	1~ / 50/60 / 220-240/220	