


Earth bonds & clamps

Earth bars



Standards

BS 7430

Earth bar with single disconnecting link

Part no.	Description	Length (mm)	Weight each (kg)
Copper earth bar			
LK243-6	6 way	475	2.30
LK243-8	8 way	575	2.70
LK243-10	10 way	725	3.30
LK243-12	12 way	825	3.70
LK243-14	14 way	925	4.10
LK243-16	16 way	1025	4.50
LK243-18	18 way	1125	4.90
LK243-20	20 way	1275	5.50
LK243-22	22 way	1375	5.90
LK243-24	24 way	1475	6.30
LK243-26	26 way	1575	6.70
LK243-28	28 way	1725	7.40
LK243-30	30 way	1825	7.80
Tinned copper earth bar			
LK243-6-T	6 way	475	2.30
LK243-8-T	8 way	575	2.70
LK243-10-T	10 way	725	3.30
LK243-12-T	12 way	825	3.70
LK243-14-T	14 way	925	4.10
LK243-16-T	16 way	1025	4.50
LK243-18-T	18 way	1125	4.90
LK243-20-T	20 way	1275	5.50
LK243-22-T	22 way	1375	5.90
LK243-24-T	24 way	1475	6.30
LK243-26-T	26 way	1575	6.70
LK243-28-T	28 way	1725	7.40
LK243-30-T	30 way	1825	7.80

- Fix using countersunk wood screws 1½" No. 12 (Part no. SW110) and wall plugs (Part no. PS310)
- Standard width x height: 90 mm x 77 mm