



Compact protection devices which provide MCB overcurrent protection and RCCB earth fault protection in a single unit. Complies with BS EN 61009

**Technical Data**  
 The units are available with current ratings of 6A, 10A, 16A, 20A, 25A, 32A and 40A. The device switches both the phase and neutral conductors. All ratings have 30mA earth fault protection. The units feature indicators which show whether tripping is due to an overcurrent or earth fault.

Breaking capacity: 6kA  
 Voltage rating: 110-230V.  
 Current rating: 6-40A.  
 Operations  
 Mechanical life:  
 20,000 operations

**Connection Capacity**  
 Rigid conductor 25mm<sup>2</sup>  
 Flexible conductor 16mm<sup>2</sup>

### RCBO Single Pole and Switched Neutral

RCBO tripping current (30mA) with flying 700mm lead for neutral connection.

Note: For use in consumer units and distribution boards only.



ADA990U

Current rating	Width (35mm)	Type B Cat ref.	Type C Cat ref.
6A	2 Mod	<b>ADA906U</b>	<b>ADA956U</b>
10A	2 Mod	<b>ADA910U</b>	<b>ADA960U</b>
16A	2 Mod	<b>ADA916U</b>	<b>ADA966U</b>
20A	2 Mod	<b>ADA920U</b>	<b>ADA970U</b>
25A	2 Mod	<b>ADA925U</b>	<b>ADA975U</b>
32A	2 Mod	<b>ADA932U</b>	<b>ADA982U</b>
40A	2 Mod	<b>ADA940U</b>	<b>ADA990U</b>