

Enclosures with plain door
steel colour RAL 7035
insulation class : I

IP 65 / door closed
according to BS EN 60529
1.5mm thick sheet steel for
body and door

These enclosures feature:

- 2 removable gland plates for cable entry on top and bottom
- Earth studs on both body and door
- Door easily removable
- Plain door equipped with one or two locks with triangular 8mm bit centres, located out of the sealed area

Options:

- Key lock
- Wall fixing brackets
- Plain or perforated mounting plate
- Equipment kits for modular devices

For full dimensions see page 2.20.

Orion Plus Metal Enclosures



FL110A

Dimensions Height x Width x Depth (mm)	No. of locks	Cat. ref. Plain door	Cat. ref. Glazed door
300 x 250 x 160	1	FL102A	-
350 x 300 x 160	1	FL104A	FL154A
350 x 300 x 200	1	FL105A	FL155A
500 x 300 x 200	1	FL110A	FL160A
500 x 400 x 200	1	FL112A	FL162A
650 x 400 x 200	2	FL117A	FL167A
650 x 400 x 250	2	FL118A	FL168A
650 x 500 x 250	2	FL120A	FL170A
800 x 600 x 300	2	FL124A	FL174A
950 x 600 x 300	2	FL126A	FL176A
950 x 800 x 300	2	FL128A	FL178A

Orion Plus Metal Enclosure Accessories



FL96Z

Description	Cat. ref.
Key lock to be mounted on the triangular lock	FL96Z
1 set of 2 key locks with male square 8mm, with 1 key	FL80Z
Key lock for FL201B	FL94Z
1 set of 2 locks doublebars 3mm with 1 key	FL95Z
Metallic wall fixing brackets with screws (set of 4)	FL85Z
Kit for earth connection (for metal enclosures)	FL874A
Orion plus spray paint kit (RAL7035)	FL672Z




FL80Z



FL95Z



FL85Z



FL874A