



## Light Range Junction Boxes to IP65/IP67

These junction boxes have an ample internal space for installation of mechanism of larger size, and they are available with transparent and opaque lids.



All enclosures are adapted to the metric system and include supports for installation of DIN rail and mounting plates on the base.

- Degree of protection IP65/IP67
- Resistance to impact IK07
- Auto-extinguishing degree HB (UL94)
- Test of resistance to glow wire from 650°C in 55DS and 55GS types and 850°C in 55DA and 55GA types.
- Ball pressure test 70°C
- Also available halogen free
- Box and opaque lid material is PS
- Transparent lid material is polycarbonate (UV protected)





		<b>Reference</b> 
	With conical cable glands 84 x 84 x 50mm	
<b>IP54</b>		Cable Entries: 4 x M25

	<b>Reference</b>	
	EPO88	
	With conical cable glands 95 x 95 x 50mm	
<b>IP54</b>	EXO88	Cable Entries: 7 x M25
	With premoulded cable entries 95 x 95 x 50mm	

	<b>Reference</b>	
	EV111 - IP65	
	With conical cable glands 119 x 119 x 64mm	
	EX111 - IP65	
	With pre-moulded cable entries 119 x 119 x 64mm	
<b>IP65/67</b>	EL111 - IP67	Cable Entries: 7 x M25
	Plain Sides 108 x 108 x 64mm	