

SKYTILE[®]

Market leading LED flat panels

- **NEW** 7 year extended warranty
- Including 2 year on-site support
- Consistent colour temperature
- Dimmable & emergency versions available

Advanced LED lighting

Skytile 7 year extended warranty excludes Skytile[®] Base and Skytile[®] Surface. Register online at jcc.co.uk/warranty





Outperforms traditional fluorescent

The Skytile® range is designed to considerably exceed the performance of fluorescent lighting.



Easy to clean, wipeable surface

High quality polycarbonate diffusers ensure cleaning is quick and simple.



Matching colour temperatures

Available in matching 4700K colour temperature to ensure consistent lighting is achieved throughout the application



Quick and easy installation

The Skytile® range is designed to ensure the fastest installation time, so that new builds go up quicker and retrofits suffer less downtime.



Instant start-up, flicker free performance

Unlike fluorescent lighting, the Skytile® range achieves full illumination as soon as they are switched on and provide a smooth, flicker free performance.

Service & support

If you have any questions about our Skytile® range of LED flat panels we would be delighted to assist you.

Customer services

01243 838999

Email

sales@jcc.co.uk

Technical support

01243 838986

*Skytile® 7 year extended warranty excludes Skytile® Surface and Skytile® Base. 2 year on site warranty applies from date of purchase. UK installations only.

SKYTILE®

Now with our new **7YR extended warranty***



- ✓ **SKYTILE®**
- ✓ **SKYTILE® SR**
- ✓ **SKYTILE® LINEAR**

Introducing our NEW Skytile® **7 Year Extended Warranty**. Cover includes Skytile®, Skytile® SR and Skytile® Linear products with 7 years warranty and 2 years on-site support.

To find out more go to jcc.co.uk/skytile

To register your warranty, go to jcc.co.uk/warranty



- ✓ **SKYTILE® SURFACE**
- ✓ **WALL WASHER**

Skytile® Surface and Wall Washer are supported by our 5 year extended commercial warranty.



- ✓ **SKYTILE® BASE**

Skytile® Base is supported by our 3 year extended warranty.

The market leading **commercial LED** solution




SKYTILE

High performance
LED flat panel




SKYTILE SR

The high performance
semi-recessed LED flat panel



SKYTILE LINEAR 1200X300

High performance
1200x300 linear LED flat panel



SKYTILE LINEAR 1200X600

High performance
1200x600 linear LED flat panel




SKYTILE SURFACE

The surface mounted **direct
fluorescent replacement**



WALL WASHER

The **high performance**
600x300 retail wall washer



NEW

SKYTILE BASE

The cost effective
LED flat panel

See how much you could save

Calculate your cost savings using our calculator app

Download JCC's free cost saving app to see how much money you could save by using any of our Skytile® fittings.

Simply enter the number of fittings that you require and see your precise energy reduction and cost savings.

- ✓ **Precise cost savings**
Find out your individual product cost savings and total annual savings by entering your exact energy costs.
- ✓ **Add or remove products**
Use the top bar to add new products to your calculation or remove products.
- ✓ **In-depth product information**
Get full product technical data including key features and benefits, product images, performance information, product codes and product dimensions.
- ✓ **Share your savings**
Email or text the full breakdown of your cost savings to your customers, friends or colleagues.



JCC's cost saving app is available for **free** on both iOS & Android devices.

What makes Skytile® the market leading LED flat panel?

Exceptionally thin and light weight structure

The ultra-slim aluminium construction aligns the LED chips with the light transmitter. The JCC Skytile® is lightweight and easy to handle with maximum strength and durability.

High performance LED chips

Light is projected from the high specification LED chips directly into the light transmitter. Skytile® LED technology provides maximum light with minimum energy consumption.

Polycarbonate light diffuser

The polycarbonate diffuser provides an even light distribution to the room and will not drip hot plastic in the event of a fire, providing extra safety assurance in the workplace.

Innovative light transmitter

The surface properties of the light transmitter ensure light moves evenly throughout the fitting. The light pixels covered base directs all the light into the polycarbonate diffuser.

Light reflector

The high quality mild steel light reflector ensures that all light is reflected back into the light transmitter.

Smooth, even light distribution


Skytile® distributes light evenly over the entire surface, preventing hotspots or shadowing



✓ Skytile®



✗ Poor quality LED panels




High quality construction

The construction of Skytile® prevents light seeping through joins in the fitting


The high performance LED flat panel

- Outperforms traditional fluorescent panels
- 7 year extended warranty, including 2 year on-site
- Smooth and even light distribution
- Suspension kit & surface mounting box available
- 44W version ideal for higher ceilings over 2.8m
- White frame available (34W 4700K version only)


▼ JC71276



Skytile®



Surface Mounting Box



Skytile®

Skytile® 34W
Skytile® 34W
Skytile® 34W
Skytile® 44W
Skytile® 44W

Colour temperature

4700K
4000K
3000K
4700K
3000K

Wattage

34W
34W
34W
44W
44W

Lumens

2900
2600
2200
3800
3050

LpcW

85
76
64
86
69

IP rating

IP44
IP44
IP44
IP44
IP44






Office installation using 34W Skytile® JC71276


The high performance **semi-recessed** LED flat panel

- Increased lighting on walls and ceilings
- Illuminates adjacent ceiling tiles
- Designed in harmony with standard Skytile®
- Discreet one piece 35mm dropped diffuser
- Provides visually comfortable lighting
- Assist with LG7 workplace illumination guidelines
- Suspension kit & surface mounting box available


▼ JC71401



Skytile® SR




Surface Mounting Box



Colour temperature	Wattage	Lumens	LpcW	IP rating
4700K	42W	3000	71	IP44



Bring the ceiling into play




Skytile® SR has a discrete 35mm one piece dropped diffuser which is engineered to provide up to 5% of the delivered light back up onto the ceiling.

This creates a halo effect around the fitting, reducing the contrast and improving the working environment.

◀ Provides 50 Lux at a distance of 500mm

Designed in conjunction with our standard Skytile® products

Skytile® SR is specifically engineered to achieve the same 228 lux light level on the working plane as our standard Skytile® products, meaning they work perfectly alongside one another.




10m x 7m office using Skytile® SR JC71401

SKYTILE[®] LINEAR 1200X600


High performance 1200x600 LED flat panel

- Outperforms traditional T5 fluorescent
- 7 year extended warranty, including 2 year on-site
- Easy to clean wipeable surface
- Quick & easy installation
- Smooth and even light distribution
- Suspension kit & surface mounting box available


▼ JC71288



Skytile[®] Linear 1200x600



Surface Mount Box



Colour temperature	Wattage	Lumens	LpcW	IP rating
4700K	55W	4300	78	IP44




SKYTILE[®] LINEAR 1200X300


High performance 1200x300 LED flat panel

- Outperforms traditional T8 fluorescent
- 7 year extended warranty, including 2 year on-site
- Easy to clean wipeable surface
- Quick & easy installation
- Smooth and even light distribution
- Suspension kit & surface mounting box available


▼ JC71298



Skytile[®] Linear 1200x300



Surface Mount Box



Colour temperature	Wattage	Lumens	LpcW	IP rating
4700K	45W	3000	66	IP44



SKYTILE® SURFACE

The surface mounted **direct fluorescent replacement**
Up to **40% energy saving** against fluorescent

Polycarbonate light diffuser

The polycarbonate diffuser provides an even light distribution to the room and will not drip hot plastic in the event of a fire, providing extra safety assurance in the workplace.

Light reflector

The high quality mild steel light reflector ensures that all light is reflected back into the light transmitter.

Innovative light transmitter

The surface properties of the light transmitter ensure light moves evenly throughout the fitting. The light pixels covered base directs all the light into the polycarbonate diffuser.


Anti-tamper design

The LED panel is secured into place by two locking clips on the end of the fitting.

High performance LED chips

Light is projected from the high specification LED chips directly into the light transmitter. Skytile® LED technology provides maximum light with minimum energy consumption.

Save up to **50% more energy** with microwave sensing




JC71307

Microwave Sensor End Cap


The surface mounted **direct fluorescent replacement**

- Direct 2x36W, 2x58W, 2x70W T8 & 2x80W T5 replacements
- Easy to clean wipeable surface
- Secure anti-tamper design
- Suspension kit available


▼ JC71301



▼ JC71302 / JC71303




▼ JC71321




Skytile® Surface 4000



Skytile® Surface 5000/6200



Skytile® Surface 6600



Skytile® Surface	Colour temperature	Wattage	Lumens	LpcW	IP rating
4000	4000K/4700K	49W	4000	82	IP20
5000	4000K/4700K	61W	5000	82	IP20
6200	4000K/4700K	80W	6200	73	IP20
6600	4700K	100W	6600	66	IP20




WALL WASHER

The high performance 600x300 retail wall washer

- Up to 38% energy saving against 55W fluorescent
- High efficient, providing 68 LpcW
- No UV, ideal for retail displays
- Smooth and even light distribution
- 4700K designed to be used in conjunction with the Skytile® range
- Designed to fit in a standard 600mm ceiling grid



✓ JC47051



Ideal for retail displays

JCC's LED Wall Washer provides enhanced lighting control for retail wall displays. The precision engineered reflector directs 2800 lumens directly towards walls, resolving the issue of dark shadowing at ceiling heights.

The light distribution has been specifically engineered to ensure that light is thrown smoothly down the wall, providing high uniformity across displays to floor level.



Colour temperature	Wattage	Lumens	LpcW	IP rating
4700K	41W	2800	68	IP20



The direct fluorescent replacement

- 32W LED flat panel
- 88 Lumens per circuit Watt
- 4200K colour temperature
- IP20 protection

▼ JC71476



Colour temperature	Wattage	Lumens	LpcW	IP rating
4200K	32W	2800	88	IP20



To view our range of complimentary commercial LED downlights, go to **jcc.co.uk**



Skydisc™

Slim profile commercial downlights

> jcc.co.uk/skydisc



Rakula LED

High efficiency commercial downlight

> jcc.co.uk/rakulaLED



Coral LED™

High output commercial LED downlights

> jcc.co.uk/coral-led

SKYTILE™

Code	Description	Dim	Col temp.	LED	Lumens
JC71331	Standard	No	3000K	34W	2200
JC71333	DALI	Yes	3000K	34W	2200
JC71334	DSI	Yes	3000K	34W	2200
JC71335	1-10V	Yes	3000K	34W	2200
JC71332	Standard <i>emergency</i>	No	3000K	34W	2200
JC71336	DALI <i>emergency</i>	Yes	3000K	34W	2200
JC71337	DSI <i>emergency</i>	Yes	3000K	34W	2200
JC71338	1-10V <i>emergency</i>	Yes	3000K	34W	2200
JC71341	Standard	No	4000K	34W	2600
JC71342	DALI	Yes	4000K	34W	2600
JC71343	DSI	Yes	4000K	34W	2600
JC71344	1-10V	Yes	4000K	34W	2600
JC71345	Standard <i>emergency</i>	No	4000K	34W	2600
JC71346	DALI <i>emergency</i>	Yes	4000K	34W	2600
JC71347	DSI <i>emergency</i>	Yes	4000K	34W	2600
JC71348	1-10V <i>emergency</i>	Yes	4000K	34W	2600
JC71276	Standard	No	4700K	34W	2900
JC71280	DALI	Yes	4700K	34W	2900
JC71324	DSI	Yes	4700K	34W	2900
JC71325	1-10V	Yes	4700K	34W	2900
JC71278	Standard <i>emergency</i>	No	4700K	34W	2900
JC71282	DALI <i>emergency</i>	Yes	4700K	34W	2900
JC71327	DSI <i>emergency</i>	Yes	4700K	34W	2900
JC71328	1-10V <i>emergency</i>	Yes	4700K	34W	2900
JC71292	Standard	No	3000K	44W	3050
JC71290	DALI	Yes	3000K	44W	3050
JC71364	DSI	Yes	3000K	44W	3050
JC71365	1-10V	Yes	3000K	44W	3050
JC71293	Standard <i>emergency</i>	No	3000K	44W	3050
JC71291	DALI <i>emergency</i>	Yes	3000K	44W	3050
JC71367	DSI <i>emergency</i>	Yes	3000K	44W	3050
JC71368	1-10V <i>emergency</i>	Yes	3000K	44W	3050
JC71277	Standard	No	4700K	44W	3800
JC71281	DALI	Yes	4700K	44W	3800
JC71374	DSI	Yes	4700K	44W	3800
JC71375	1-10V	Yes	4700K	44W	3800
JC71279	Standard <i>emergency</i>	No	4700K	44W	3800
JC71283	DALI <i>emergency</i>	Yes	4700K	44W	3800
JC71377	DSI <i>emergency</i>	Yes	4700K	44W	3800
JC71378	1-10V <i>emergency</i>	Yes	4700K	44W	3800

SKYTILE™ SR

Code	Description	Dim.	Col. temp.	LED	Lumens
JC71401	Standard	No	4700K	42W	3000
JC71402	1-10V	No	4700K	42W	3000
JC71403	DALI	No	4700K	42W	3000
JC71404	DSI	No	4700K	42W	3000
JC71405	Standard <i>emergency</i>	No	4700K	42W	3000
JC71406	1-10V <i>emergency</i>	No	4700K	42W	3000
JC71407	DALI <i>emergency</i>	No	4700K	42W	3000
JC71408	DSI <i>emergency</i>	No	4700K	42W	3000

SKYTILE™ LINEAR

Code	Description	Dim	Col temp.	LED	Lumens
JC71288	1200x600	No	4700K	55W	4300
JC71289	1200x600 <i>emergency</i>	No	4700K	55W	4300
JC71298	1200x300	No	4700K	45W	3000
JC71300	1200x300 <i>emergency</i>	No	4700K	45W	3000

SKYTILE™ SURFACE

Code	Description	Dim.	Col. temp.	LED	Lumens
JC71301	4000	No	4700K	49W	4000
JC71304	4000 <i>emergency</i>	No	4700K	49W	4000
JC71307	4000 c/w microwave sensor	No	4700K	49W	4000
JC71302	5000	No	4700K	61W	5000
JC71305	5000 <i>emergency</i>	No	4700K	61W	5000
JC71308	5000 c/w microwave sensor	No	4700K	61W	5000
JC71303	6200	No	4700K	80W	6200
JC71306	6200 <i>emergency</i>	No	4700K	80W	6200
JC71309	6200 c/w microwave sensor	No	4700K	80W	6200
JC71321	6600	No	4700K	100W	6600
JC71322	6600 <i>emergency</i>	No	4700K	100W	6600
JC71323	6600 c/w microwave sensor	No	4700K	100W	6600

DALI, DSI & 1-10V dimmable variants available for 4000/5000 only

Skytile® Surface available in 4000K colour temperature. Codes online at jcc.co.uk

SKYTILE™ BASE

Code	Description	Dim.	Col. temp.	LED	Lumens
JC71476	Standard	No	4200K	32W	2800
JC71478	Standard <i>emergency</i>	No	4200K	32W	2800

WALL WASHER

Code	Description	Dim.	Col. temp.	LED	Lumens
JC47051	600x300 LED wall washer	No	4700K	41W	2800

ACCESSORIES

Code	Description
JC71311	Skytile® suspension kit for 600x600mm
JC71312	Skytile® suspension kit for 1200x600mm
JC71262	Skytile® surface mount tray for 600x600mm
JC71295	Skytile® Linear surface mount tray for 1200x600mm
JC71299	Skytile® Linear surface mount tray for 1200x300mm

LED

Warm white 3000K | Neutral white 4000K | Cool white 4700K | CRI: Ra (80)

Construction

Skytile®, Skytile® Linear & Skytile® Base

Body – extruded aluminium frame with opal polycarbonate diffuser

Surface Mounting Trays – mild steel

Skytile® Surface

Body – extruded aluminium frame with polycarbonate diffuser

Mounting – pressed steel