

Starters for single operation at 230 V AC

171 SAFETY DEOS



Product features

• Temperature range for reliable cut-out: -20...+80 °C




Technical data

Electrical data

Nominal voltage	220240 V
Mains frequency	50/60 Hz


Dimensions & weight

Length	40.3 mm
--------	---------



Product line drawing with letters





Circuit diagram



Logistical Data

Product code	Packaging unit (Pieces/Unit)	Dimensions (height x width x length)	Gross weight	Volume
4050300421544	Blister 1	120 mm x 27 mm x 140 mm	22.71 g	0.45 dm ³
4050300421551	Shipping carton box 10	153 mm x 157 mm x 165 mm	267.40 g	3.96 dm ³
4050300422855	Unpacked 1	20 mm x 18 mm x 35 mm	7.83 g	0.01 dm ³
4050300422862	Shipping carton box 1200	325 mm x 265 mm x 400 mm	11169.00 g	34.45 dm³
4050300854106	Unpacked 1	22 mm x 19 mm x 37 mm	9.80 g	0.02 dm ³
4050300797823	Tray 25	113 mm x 43 mm x 111 mm	232.80 g	0.54 dm ³
4050300797830	Shipping carton box 200	227 mm x 98 mm x 227 mm	2020.00 g	5.05 dm ³

Product datasheet



Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.