

ELED-25-12T



This 25W constant voltage LED driver operates 180-240VAC input range. The LED driver provides 12V constant voltage and is TRIAC dimmable using leading edge dimmers

### Details

**Barcode:** 5055788217176

**Category:** Drivers

**Range Name:** TRIAC

**Product Type:** Constant Voltage

**Market Segment:** Commercial indoor, Residential indoor

**Warranty (Years):** 2

**CE RoHS:** Yes

### Physical Data

**Product Length (mm):** 155

**Product Depth (mm):** 20

**Product Width (mm):** 54

**Product Weight (g):** 186

**Placement / Application:** Indoor LED Lighting

### Electrical Data

**Power (W):** 25

**Power Consumption (w):** 25

**Power Factor:** 0.65

**Voltage (V):** 12

**Input Voltage (V):** 180-240

**Output Current (mA):** 2080

**Output Voltage (V):** 12

**Dimming:** Triac Dimmable using leading edge dimmer

**Protection Function:** Short Circuit Protection, Overload Protection, Overheat Protection

**EN:** EN61347-1, EN61347-2-13, EN55015, EN6100-3-3, EN6100-3-2, EN61547

**LVD Certified:** Yes

### Light Data

**Lumens Range:** 1 to 100

**Frequency Range (Hz):** 50/60

[Portal.Integral-Led.Com](http://Portal.Integral-Led.Com)

### Environment

Product Design And Specification Subject To Change Or Modification Without Notice. Image For Illustration Only. E&OE

**EN:** EN61347-1, EN61347-2-13, EN55015, EN6100-3-3, EN6100-3-2, EN61547

**LVD Certified:** Yes

**CE RoHS:** Yes

**Hg 0% (Mercury Free):** Yes

**IP Rating (Back/Recessed side):** IP20

**IP Rating (Ingress Protection):** IP20

**Lowest Operating Temperature (°C):** -20

**Maximum Operating Temperature (°C):** 45

## **Packaging**

**Package Weight (g):** 200

**Package Length (mm):** 160

**Package Width (mm):** 60

**Package Depth (mm):** 21