

Onyx 200W flood



EL200X3F



PRODUCT DATA

PRODUCT CODE	EL200X3F	LUMENS (lm)	26000
WATTAGE (W)	200W	COLOUR TEMP. (K)	5000K
WEIGHT (kg)	4.6kg	BEAM ANGLE	120°
WINDAGE	0.18m2	CRI	>70
REPLACEMENT FOR	500W MH/SON	DIMENSIONS (mm)	418x368x56mm
EFFICIENCY (lm/w)	130lm/W	RATED LIFETIME (hrs)	25,000hrs
IP	65	IK	07
HOUSING COLOUR	Black	WORKING ENVIRONMENT	-20°C to 40°C
WARRANTY	2 years		


KEY FEATURES

The high output of the Onyx 200W flood (3rd generation) makes it a perfect replacement for a 500W MH/SON and is ideal as a high powered floodlight. The input voltage range of 110-240Vac allows for use in both commercial, industrial and construction site lighting. Additionally, by using our optional coastal marine upgrade version (LL004), users are able to install the Onyx in coastal marine areas (Code: LL004).


COMMERCIAL APPLICATIONS

For external use on: Warehouses, factories, sports facilities, retail outlets, car-parks, construction sites, footpaths, parks, loading bays. For swimming pool areas, high/low bay or moving structures, please contact us for information on our products which are suitable for these three applications.

POLAR CURVE DIAGRAM



CONE DIAGRAM



DIMENSIONS

