


Product Code: CMA039

Luckinslive 389086910

Description: 2A Round Pin Socket Outlet



General Information

Plate Dimensions (mm)	86 (W) x 86 (H) x 9.5 (D)		
Plate Fixing Centres - Horizontal (mm)	60.3		
Style	Rounded Profile		
Colour	Polar White		
Materials	Front Plate: Urea		Rear Housing: Nylon
	Terminals: Brass		Terminal Screws: Steel & Yellow Passivated
	Internal Busbars: Formed Pressed Brass		Earth Strap: Mild Steel
Anti Microbial Certified	Yes		
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	2		
Termination Type	Screw		
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm)	0.5
Terminal Capacity - Solid (mm ²)	3 x 1.5		
Switched	No		
Twin Earth Terminals	No		
Minimum Back Box Depth (mm)	25		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	25		

Standards BS 546

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.

All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.



Catalogue



Range



DoC



Installation

