

Product Code: CL036

Luckinslive 389086428

Description: 13A 2 Gang Double Pole Switched Socket Outlet



General Information

Dimensions (mm)	140 (W) x 80 (H) x 42 (D)	
Plate Fixing Centres - Horizontal (mm)	120.6	
Style	Metal Clad	
Colour	Grey	
Materials	Front Plate & Mounting Box:	Insert & Rocker Switch: Urea
	Electrophoretically Coated Steel	Terminals: Brass
	Rear Housing: Urea	Contacts: Silver "on-lay" Copper / Brass
	Terminal Screws: Steel & Yellow Passivated	Earth Strap: Mild Steel
Internal Busbars: Formed Pressed Brass	Frequency (Hz)	50
Operating Voltage (AC)	250	
Resistive Load Rating (A)	13	
Termination Type	Screw	
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm) 2
Terminal Capacity - Solid (mm²)	3 x 2.5 or 2 x 4	
Double Pole Switch	Yes	
Twin Earth Terminals	Yes	
Supplied Back Box Depth (mm)	40	
Back Box Knockouts - Total (mm)	7 x Ø20	Back Box Knockouts - Sides (mm) 1 x Ø20
Back Box Knockouts - Top (mm)	3 x Ø20	Back Box Knockouts - Rear (mm) None
Back Box Knockouts - Bottom (mm)	2 x Ø20	
Back Box Earth Terminal Supplied	Yes	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	20	

Standards BS 1363-2

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

