





Bulkheads

Performance

@ansell_lighting

Hospitality, Residential, Retail



anselllighting



in Ansell Lighting




Disco EVO

Disco EVO 2 Microwave Sensor Emergency Code: ADIS2/1/MWS/M3








Category

Application

Specification



Ancillary, Commercial, Education, Healthcare,

PRODUCT FEATURES

- Slim and modern bulkhead suitable for residential, commercial and industrial applications as well as ancillary areas
- All polycarbonate construction with opal diffuser and white trim ring with optional chrome, satin chrome or graphite trim ring accessories
- $_{\bullet}\,$ Gear tray located on the bezel, allowing the base to be installed and then the bezel connected, this coupled with $4x\ 20\text{mm}$ conduit entry points on base ensure a quick and simple installation
- Instant light output and unlimited switching

www.ansell-lighting.com

- High efficiency up to 145lm/W
- $_{\bullet}\,$ CCT selectable between 3000K, 4000K and 6500K and power selectable; offering a choice of 3 outputs, in one luminaire
- Two options of microwave sensor emergency

Wattage 9W - 16W Lumens Delivered (4000K) 9W: 120l0m 12W: 1800lm 16W: 2300lm Lm/W (4000K) 9W: 135lm/W 12W: 145lm/W 16W: 145lm/W Beam Angle 110 CRI 80 CCT 3000/4000/6500K Input 220/240V Operating Temp 0°C - 40°C SDCM 5	GENERAL INFORMATION	
2300lm Lm/W (4000K) 9W: 135lm/W 12W: 145lm/W 16W: 145lm/W Beam Angle 110 CRI 80 CCT 3000/4000/6500K Input 220/240V Operating Temp 0°C - 40°C SDCM 5	Wattage	9W - 16W
Lm/W (4000K) 9W: 135lm/W 12W: 145lm/W 16W: 145lm/W Beam Angle 110 CRI 80 CCT 3000/4000/6500K Input 220/240V Operating Temp 0°C - 40°C SDCM 5	Lumens Delivered	(4000K) 9W: 120l0m 12W: 1800lm 16W:
145lm/W		2300lm
Beam Angle 110 CRI 80 CCT 3000/4000/6500K Input 220/240V Operating Temp 0°C - 40°C SDCM 5	Lm/W	(4000K) 9W: 135lm/W 12W: 145lm/W 16W:
CRI 80 CCT 3000/4000/6500K Input 220/240V Operating Temp 0°C - 40°C SDCM 5		145lm/W
CCT 3000/4000/6500K Input 220/240V Operating Temp 0°C - 40°C SDCM 5	Beam Angle	110
Input 220/240V Operating Temp 0°C - 40°C SDCM 5	CRI	80
Operating Temp 0°C - 40°C SDCM 5	CCT	3000/4000/6500K
SDCM 5	Input	220/240V
	Operating Temp	0°C - 40°C
1	SDCM	5
UGR 26	UGR	26

TECHNICAL INFORMATION	
Light Source	LED
Colour / Finish	White
IP Rating	IP65
Class Protection	2
Internal / External	Internal / External
Surface / Recessed / Suspended	Ceiling, Wall
Lumen Depreciation	L70 54,000h
Warranty (Years)	5
CE Mark	Yes
Diameter	325 mm
Height	80 mm

Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750