

[Conventional Fire Systems](#)[Miscellaneous](#)[Apollo Series 65 optical smoke detector](#)

Apollo Series 65 optical smoke detector

Part No. 55000-317APO

- A high-quality optical smoke detector.
- Incorporates an infrared light source and a photodiode to detect smoke particles.
- Certified to EN54-7 by the LPCB.
- Wide 9-33V DC operating voltage.
- Red LED illuminates when the detector is in alarm.
- Requires a 45681-201APO diode base, 45681-200APO non-diode base or 45681-245APO relay base.

Technical Specifications



Approvals/certifications	Certified to EN54-7 by the LPCB.
Application/operation	TBC.
Supply wiring	2-wire monitored, polarity sensitive.
Supply/operating voltage	9 to 33V DC.
Quiescent current	30-50µA @ 24 VDC.
Alarm voltage	6-28V DC.
Alarm current	61mA @ 28V DC; 52mA @ 24V DC; 18mA @ 10V DC.
Alarm reset voltage	TBC.
Expansion connections	Remote LED output. Current sink to negative line limited to 17mA.
Product dimensions (mm)	100mm diameter x 50mm deep (detector in base); 100mm diameter x 42mm deep (detector only).
Construction & finish	White polycarbonate V.O in accordance with UL94. Nickel plated stainless steel terminals.
IP Rating	IP23D.
Weight	99g (detector only); 150g (detector in base).
Operating conditions/temperature	-20°C to +60°C.

Accessories 

17 other products in the same category: 

CONTACT US

 C-TEC , Challenge Way, Wigan, WN5 0LD, UK Opening times: 08:30 - 17:00 GMT.

 +44 (0) 1942 322744

 sales@c-tec.co.uk

 [Download map](#)
