

3 Year Warranty

L70 25,000hrs

Triac dimmable as standard

Emergency option

White, Matt White, Polished
Chrome & Satin Nickel bezel
finish options



works with

.control



Triac Inline Dimmer
See pg.31



Smart Rotary Dimmer
See pg.25



EN-DE8



EN-DE8
(H) 92mm Height
(OD) 85mm Overall (Ø)

EN-DE82
(H) 100mm Height
(OD) 98mm Overall (Ø)

E8™

LED fixed/ adjustable fire rated downlights

make smart with



See pg.218-219 for compatibility table

Sparkling, low glare, multifaceted EnFiniti™ lens

Delivering up to 80lm/W

Slim interchangeable IP65 bezels (fixed version) provide a sleek finish

IP20 bezel included for adjustable

SDCM <6 providing consistent light colour quality

Fibre based insulation coverable - up to 300mm

60° beam angle for maximum light distribution

Tested in 30, 60 and 90-minute fire rated ceilings



For Dimming Compatibility See pg.224-225



Fixed IP65



Adjustable



AIR leakage
(excluding
adjustable)

| Cat. No. | Watts | Colour | Lumens | lm/W | Beam | Cutout [Ø] |
|----------|-------|--------|--------|------|------|------------|
|----------|-------|--------|--------|------|------|------------|

E8™ Triac Dimmable Fixed (IP65 when used with IP65 Bezel)

| | | | | | | |
|-----------|----|-------|-------|----|-----|------|
| EN-DE8/30 | 8W | 3000K | 580lm | 73 | 60° | 70mm |
| EN-DE8/40 | 8W | 4000K | 620lm | 78 | 60° | 70mm |

E8™ Triac Dimmable Adjustable

| | | | | | | |
|-------------|----|-------|-------|----|-----|------|
| EN-DE82*/30 | 8W | 3000K | 610lm | 76 | 60° | 80mm |
| EN-DE82*/40 | 8W | 4000K | 640lm | 80 | 60° | 80mm |

Accessories

EN-BZE8* E8™ PRO/E8™ Fixed IP65 Aluminium Downlight Bezel

*Add suffix **W**, **MW**, **PC** or **SN** for White, Matt White, Polished Chrome or Satin Nickel finishes.
3 hour Emergency pack AU-FRLM10EM available.

