



Conventional Fire Systems

Manual Call Points

Manual 'Crack Glass' Call Point, surface



Manual 'Crack Glass' Call Point, surface

Part No. BF370R

- Certified to EN54 Part 11 (LPCB/VdS).
- Unique 'Plug & Play' installation concept.
- Supplied with a glass element.
- Includes a 470Ω resistor, test key and red back box.
- Anti-Tamper facility.
- Flush version (without a red back box) also available (order code BF370RF).



Technical Specifications



Approvals/certifications	Certified to EN54 Part 11 by the LPCB & VdS.
Supply/operating voltage	30Vdc max.
Product dimensions (mm)	93 W x 89 H x D 60mm (includes back box). 28mm D without back box.
Construction & finish	Red ABS. Glass element.
IP Rating	IP24D.
Weight	180g (130g without back box).
Properties	Supplied with a 470Ω resistor.
Operating conditions/temperature	-10°C to +55°C.

Spares & Accessories



BF371	Spare glass for BF370R & BF370RF manual call point
BF370MC	Protective cover for BF370R & BF370RF manual call point
BF370KRK	Test key for BF370R & BF370RF manual call point

BIM/CAD Drawings



Documentation



7 other products in the same category:



CONTACT US



C-TEC , Challenge Way, Wigan, WN5 0LD, UK Opening times: 08:30 - 17:00 GMT.



+44 (0) 1942 322744



sales@c-tec.co.uk



Download map
