





Kyros

Digital electric radiator with low consumption







4 pre-installed programs (Common lifestyle, split shift, home life and office)



Interactive visual menu with icons



Compatible with Air Control remote (not included)



20 years guarantee on the body + 3 years on the electronics

(when you register your product)



TECHNICAL INFORMATION

| Armoured steel heating element | ✓ |
|---|-----------|
| High purity aluminium elements | ✓ |
| Flame retardant side closures in PC/ABS | ✓ |
| Biodegradable, high heat transfer fluid | ✓ |
| Control panel with mechanical keypad | ✓ |
| Fuzzy Logic Energy Control technology | ✓ |
| Infrared communication | ✓ |
| Temperature stability | ±0.25 °C |
| Air speed | < 0.1 m/s |
| Average surface temperature | 43 °C |
| Protection Grade | IP24C |

| FUNCTIONS | |
|--|----------|
| Anti-frost / Comfort / ECO / User mode | ~ |
| 4 pre-installed programs | ~ |
| Interactive menu with icons | ~ |
| Manual / Automatic function | ✓ |
| Open Windows function | ~ |
| 24/7 programming | ✓ |
| INSTALLATION | |


REGULATIONS & GUARANTEES

Template & installation kit

2004/108/CE Electromagnetic comp. 2006/95/CE Low voltage directive UE 2015/1188 ECODESIGN (ERP) Guarantee on the aluminium body 20 years 3 years Guarantee on the electronics







| MODELS | KRI0330RAD3 | KRI0550RAD3 | KRI0770RAD3 | KRI0990RAD3 | KRI1210RAD3 | KRI1430RAD3 | KRI1600RAD3 | | |
|-----------------------------|----------------|----------------|----------------|----------------|------------------|------------------|------------------|--|--|
| Elements | 3 | 5 | 7 | 9 | 11 | 13 | 15 | | |
| Nominal Power (W) | 330 | 550 | 770 | 990 | 1,210 | 1,430 | 1,600 | | |
| Effective Power (W)* | 125 | 209 | 293 | 376 | 460 | 543 | 608 | | |
| DIMENSIONS | | | | | | | | | |
| Width x height x depth (mm) | 350 x 580 x 98 | 520 x 580 x 98 | 680 x 580 x 98 | 840 x 580 x 98 | 1,010 x 580 x 98 | 1,180 x 580 x 98 | 1,330 x 580 x 98 | | |
| Installed depth (mm) | 120 | 120 | 120 | 120 | 120 | 120 | 120 | | |
| CHARACTERISTICS | | | | | | | | | |
| Weight (kg) | 7.7 | 12.2 | 16.4 | 20.4 | 24.1 | 25.9 | 32.1 | | |
| Finishes | White RAL 9010 | | | | | | | | |
| EAN CODE | 8436045917256 | 8436045917263 | 8436045917270 | 8436045917287 | 8436045917294 | 8436045917300 | 8436045917317 | | |

^{*} In tests performed by independent laboratories (under the same parameters), a radiator with Fuzzy Logic Energy Control technology and another with Optimizer Energy Plus (the first Rointe energy control technology) were compared. A difference in energy consumption of 6.3% was obtained. This saving allows the radiators with Fuzzy Logic Energy Control to use an average power of only 38% of the nominal power. We define this as the equivalent consumption coefficient. If we multiply the nominal power by the equivalent consumption coefficient, we obtain the effective power. For more information please contact us.