JC94110WH

Fireguard Mains IP65 Recessed Showerlight 50W Unlamped White

Features & Benefits

Fire-rated 240V showerlight

Press-fit terminal, loop-in/loop-out

IP65, suitable for use in bathrooms

Lamp not supplied

General Information

Product Group	Fire-rated downlights
Product Range	Fireguard
Trade Name	Fireguard
Lighting Product Type	Fired Rated Downlights
Product Shape	Round
Mounting	Recessed

Product Weight	0.275kg
Color Finish	White
Overall Dimensions	99.5 x 88 mm
Recommended Product Location	indoor use only
Minimum Void Requirement	150mm
Method Of Fix	Spring clips
Product Aperture Size	74mm
IP Rating	IP65
Environment	Indoor
Suitable For Zones	Zone 1
Lamp Supplied	No
Distance From Lighted Object	0.5m
Origin Of Manufacture	PRC
Guarantee	2 year

Electrical

Voltage Rating	220-240
Operating Frequency (Hz)	50/60Hz
Luminaire Circuit Wattage	50W max
Class	Class I, earth required
Input Electrical Connections	Live(Brown)Neutral(blue)Earth(yellow/green) - Loop in/Loop out press fit terminal
Dimmable	Check with lamp manufacturer
Lampholder	GU10 cap

Thermals

Room Ambient Temperature Not To Exceed	26℃

Room Ambient Temperature	25°C
Insulation Coverage	see instruction sheet
Minimum Free Air Space	At least 75mm around fitting

Performance Data

Energy Rating	This luminaire is compatible with bulbs of the energy class A+ to E

Construction

Primary Material	Steel
Rim Or Attachment	Die-cast aluminium

Packaging

Luminaire Carton Dimensions	125 x 125 x 95 mm
Quantity Per Outer Carton	40
Bar Code EAN Number	5052544047381
Packaged Weight	0.321kg

Standards & Approvals

Listings	CE
Listings	Fire Rating
Manufactured In Accordance To	BS EN 60598-2-1, 2-2
CE Marked	Yes
Batch Coded	yes
WEEE Symbol	yes
Certificate Of Conformity	Available on request
Accredited Members	LIA, ISO9001:2015, ISO14001:2015

Datasheet generated from https://www.electrika.cloud on 11 September 2018 11:16:51