

# V50™

## Colour selectable fire-rated LED downlight

- Two colour selectable from below the ceiling, 3000K & 4000K
- Ultra-low profile suitable for shallow 50mm ceiling voids
- Fully fire-rated for 30, 60 and 90 minute ceilings
- IP65, suitable for bathrooms (internal use only)
- Strong, protected spring clips
- Fast, push-fit termination with remote driver
- Triac dimmable as standard (recommended dimmer list on JCC website)
- Twist & lock bezel design
- Available as complete fixture (JC1001) or without bezel (JC1001/NB)
- JC1001/NB requires separate bezel (JC1006)

✓ JC1001/CH



✓ JC1001/WH



✓ JC1001/BN



✓ JC1001/BR



✓ JC1001/BLK




Code	Description	Col temp.	Dim.	Watt	Lumens	LpcW
JC1001/NB	V50 Without bezel	3000K & 4000K	Yes	7.5W	600/650	80
JC1001	V50 With bezel (add suffix)	3000K & 4000K	Yes	7.5W	600/650	80
JC1006	Separate bezel for V50 (add suffix) -	-	-	-	-	-

For Black add /BLK suffix, for Brushed Brass add /BR suffix, for Brushed Nickel add /BN suffix, for Chrome add /CH suffix, for White add /WH suffix.


\*Requires online registration.

**NEW** New product for 2018


 3 year ext. warranty\*

 Dimmable as standard

 60° beam angle

 See p.16 and p.17 for accessories

### Classification

 Class 2  
IP65 | 240V

### LED

3000K | CRI: Ra (80)  
4000K | CRI: Ra (80)

### Finishes

Black (BLK), Brushed Brass (BR),  
Brushed Nickel (BN),  
Chrome (CH), White (WH)

### Construction

Body: Steel  
Lens: Polycarbonate  
Bezel: Aluminium

### Accessories

Converter plate (see p.16)  
Concealer ring (see p.17)

### Installation

Cut out Ø: 70mm

### JC1001

