Intelligent Dimmer Switch - Push Type

- Intelligent dimmer suitable for LED, halogen and incandescent lamps
- Soft start, smooth dimming control and silent operation
- 2 Way push on/off with rotary control
- Overload protection
- Clearly marked terminals with backed out captive screws for easy installation
- Terminal capacity 3 x 1mm², 2 x 1.5mm² & 1 x 2.5mm²
- Manufactured to BS EN 60669-2-1
- Minimum mounting box depth 25mm
- 220-240V AC

882

APPROVED

Round Edge	Square Edge	Description	Inner Carton	Outer Carton
881	981	Single, 2 way push on/off	10	100
882	982	Double, 2 way push on/off	10	100
883	983	Triple, 2 way push on/off	5	50
884	984	Quadruple, 2 way push on/off	5	50

Replacement Modules

DMLT
- Intelligent dual dimmer module allows you to switch between leading and trailing edge.
- Set to trailing edge as default.
- Suitable for LED, halogen and incandescent lamps.
- Trailing edge mode: 5-150W
- Leading edge mode: 5-100W

DMSW8A/2W
- Dummy dimmer switch gives the appearance of a dimmer switch, but with regular on/off 2-way switching (no dimming function).

DMLT

APPROVED

Product Code	Description
DMSW8A/2W	2 way push on/off switch, dummy dimmer, 100W
DMLT	2 way intelligent dual dimmer module, 150W

Fan Controller

- Manufactured to BS EN 60669-2-1
- Minimum mounting box depth – 35mm
- 10mm spacer available to provide wiring space (817 – Sq)

887

987

Round Edge	Square Edge	Description	Inner Carton	Outer Carton
887	987	Single, 1 way rotary, 100W (export only)	10	100

Round Pin & Export Socket Outlets

- 2/5/15A Manufactured to BS 546
- Minimum mounting box depth: 2/5/16 Amp – 25mm; 15A – 35mm



899

829

999

Round Edge	Square Edge	Description	Inner Carton	Outer Carton
828	928	Single, 2 Amp unswitched socket, round pin	10	100
829	929	Single, 5 Amp unswitched socket, round pin	10	100
829S	-	Single, 5 Amp, switched socket, round pin	10	100
899	999	Single 15 Amp switched socket, round pin	10	100

16 Amp Hotel Key Card Switch

- 50 x 50mm Euro Module with locator LED
- Load rating – 1800W for incandescent, 800W for fluorescent
- 30 second power-off delay
- Mounting box depth – 47mm
- Colour coded terminals with backed-out captive screws
- Designed and manufactured to BS EN60669-4
- Supplied as kit of Euro Module components

8KYCSW

Round Edge	Description	Inner Carton	Outer Carton
8KYCSW*	16 Amp, hotel key card switch	5	100

Co-Axial, Satellite & Screened Socket Outlets

- EM = Euro Module configuration
- Manufactured to BS 5733 where applicable
- Co-axial and satellite minimum mounting box depth – 25mm
- Triplex minimum mounting box depth – 35mm

***See our Euro Module range for further Telecom, Data and Co-axial options**

868

APPROVED

960

Round Edge	Square Edge	Description	Inner Carton	Outer Carton
860	960	Single co-axial socket	10	100
861	961	Double co-axial socket	10	100
862	962	Single isolated co-axial socket	10	100
863	963	Double isolated co-axial socket	10	100
864	964	Single satellite socket	10	100
865	965	Double satellite & co-axial socket	10	100
866	966	Double diplex TV/FM	10	100
867	-	Triple TV/FM/SAT triplex – screened	10	100
868	-	Triplex with BT outlet & co-axial return – screened	5	50
869	-	Quadplex, 2x SAT, BT outlet & co-axial returned – screened	5	50