Dry Lining Boxes

- Chemical resistant
- Manufactured from ABS
- Circular base knock-out size 25mm


907

919

Product Code	Description	Inner Carton	Outer Carton
907	Single, 35mm	10	100
908	Double, 35mm	5	50
916	Dual 35mm	5	50
917	Single, 47mm	10	100
918	Double, 47mm	5	50
919	Round 35mm	10	100
920	Triple 35mm, single and double	5	50

Steel Knock-Out Boxes

- Manufactured to BS EN 60670-1
- Complete with earth bond terminal

HGS02

HGS04

HGS08

Product Code	Description	Inner Carton	Outer Carton
HGS01	Single, 16mm deep	20	200
HGS02	Single, 25mm deep	10	100
HGS03	Single, 35mm deep	10	100
HGS04	Double, 25mm deep	5	50
HGS05	Double, 35mm deep	5	50
HGS05/C4	4 x double, 35mm deep – combination plate	-	10
HGS06	Single, 47mm deep	10	100
HGS07	Double, 47mm deep	5	50
HGS07/C2	2 x double, 47mm deep – combination plate	-	20
HGS07/C4	4 x double, 47mm deep – combination plate	-	10
HGS08	Dual 35mm deep	5	50
HGS68	Double metal box (6g + 8g Grid)	5	25
HGS912	Triple metal box (9g + 12g Grid)	5	25

Fire Rated Dry Lining Boxes

- Fire rated back box with intumescent pad
- Spring loaded adjustable lugs for the perfect fit
- M20 knockouts in top, bottom and base for versatility
- Fitted with earth terminal in the base
- Complies with Part B (Fire) and Part E (Sound) Building Regulations
- Fire-Rated to BS EN 1364-1 for up-to 120 minutes
- Airborne Sound Insulation Tested: 54dB to ISO 10140-2: 2021


HGS03/FR

HGS07/FR

Product Code	Description	Inner Carton	Outer Carton
HGS03/FR	Single, 35mm deep	10	100
HGS05/FR	Double, 35mm deep	5	50
HGS06/FR	Single, 47mm deep	10	100
HGS07/FR	Double, 47mm deep	5	50

Flex Connectors

- Manufactured to BS 5733
- 2 plastic cable restraints retained by plated-steel slotted head screws
- Brass slotted head terminal screws

458

452

Product Code	Description	Inner Carton	Outer Carton
452	10 Amp, 3 pin, shrouded non-reversible male and female	20	200
458	10 Amp, 3 pin, solid brass through terminals	20	200

Connector Strips

- Manufactured from thermoplastic
- Unique 'snap-off' spine design
- Maximum continuous temperature rating 80˚C
- Nominal voltage 400V
- Fully backed-out screws to speed installations
- Manufactured to BS EN 60998-2-1

TS30/6

Product Code	Description	Inner Carton	Outer Carton
TS2.5/6/1	2.5 Amp, 6 way	10	100
TS2.5/12/10	2.5 Amp, 12 way – pack of 10	-	100
TS5/6/1	5 Amp, 6 way	10	100
TS5/2x6	5 Amp, 6 way	10	100
TS5/12/10	5 Amp, 12 way – pack of 10	-	100
TS15/6/1	15 Amp, 6 way	10	100
TS15/12/10	15 Amp, 12 way – pack of 10	-	48
TS30/6/1	30 Amp, 6 way	10	100
TS30/12/10	30 Amp, 12 way – pack of 10	-	30
TS60/6/1	60 Amp, 6 way	10	100
TS60/12/10	60 Amp, 12 way – pack of 10	-	20