


EXTRACTOR FANS

- 230V ■ IPX2 rated ■ 4" models: Air movement: 90m³/hr, noise level: 35dB @ 3m
- 6" model: Air movement: 210m³/hr, noise level: 40db @ 3m
- Adjustable overrun timer 2-30mins (where applicable)
- Compliant with latest Building Regulations (Part F & Part L)



Code	Model	Qty
EX001	4"/100mm	1
EX001T	4"/100mm with Overrun Timer	1
EX002T	6"/150mm with Overrun Timer	1




EX001 / EX001T

EX002T

LED EXTRACTOR FANS

- 230V ■ IPX4 rated ■ 4"/100mm ■ Air movement: 90m³/hr ■ Noise level: 35dB @ 3m
- Adjustable overrun timer 2-30mins ■ LED lighting effect during activation
- Compliant with latest Building Regulations (Part F)



EX003T



EX004T

Code	Model	Qty
EX003T	White	1

Code	Model	Qty
EX004T	Black/Stainless Steel	1

ACCESSORIES

- Gravity Shutters, Grilles and Ducting Kits



4"/100mm

Code	Model	Qty
EX007W	Gravity Shutter – White	1
EX007B	Gravity Shutter – Black	1
EX009W	Grille with Fly Screen – White	1
EX009B	Grille with Fly Screen – Black	1
EX4DUCT*	Aluminium Ducting Kit	1

6"/150mm

Code	Model	Qty
EX008W	Gravity Shutter – White	1
EX008B	Gravity Shutter – Black	1
EX0010W	Grille with Fly Screen – White	1
EX0010B	Grille with Fly Screen – Black	1
EX6DUCT*	Aluminium Ducting Kit	1

*Ducting kits include 3.3m of expandable aluminium ducting and 2 jubilee clips