Terminals, SDKF and PQC Terminals

SDKF
Universal Loop Connectors

RoHS

SDKF 2, SDKF 3 and SDKF 5

Rated current	24 A
Voltage	450 V
Clamping range	0.2 - 2.5 mm²
Accepted cables	solid/ rigid/ flexible
Colour	White
Installation	Lever release

Terminals, SDKF

Type	WISKA-No.	Description	Terminals/ poles	
SDKF 2	SDKF2	Releasable loop connector	2- pole	20 / 50 / 100
SDKF 3	SDKF3	Releasable loop connector	3-pole	20 / 50 / 100
SDKF 5	SDKF5	Releasable loop connector	5-pole	20 / 50 / 100

PQC
Push-in Quick Connector

RoHS

PQC 1 and PQC 2

Rated current	24 A
Voltage	450 V
Colour	Single dark grey / Double white
Installation	Push insertion / twist release
Lightning side	Press and push insertion / press release

Lighting side...		**Installation side..**	
Clamping range	0.5 - 2.5 mm²	**Clamping range**	0.75 - 2.5 mm²
Accepted cables	solid/ rigid/ flexible	**Accepted cables**	solid/ rigid

Terminals, PQC

Type	WISKA-No.	Description	Conductor	
PQC 1	PQC1	Push-in quick connector	Single	20 / 50 / 100
PQC 2	PQC2	Push-in quick connector	Double	20 / 50 / 100

WISKA
make power smile

Other technical data on request / Subject to modifications and amendments