

SWITCHED INTERLOCKED SOCKETS

SWITCHED SOCKETS


Conformity to Standards:	CEI EN 60309-1	IEC 60309-1	Cable entry	16A	2P+E	min: 8	max: 13	mm
	CEI EN 60309-2	IEC 60309-2			3P+E	min: 8.5	max: 14	mm
	CEI EN 60529	IEC 60529			3P+N+E	min: 10	max: 15.5	mm
Impact resistance:	>IK 08			32A	2P+E	min: 11.5	max: 17.5	mm
Glow wire test:	850°C insert				3P+E	min: 12.5	max: 19.5	mm
Self extinguishing:	V2				3P+N+E	min: 14	max: 21.5	mm
Temperature resistance:	Operating	-25 to +50°C	Connecting sections of the wires	16A		min: 1	max: 2.5	mm ²
	Storage	-30 to +70°C		32A		min: 2.5	max: 6	mm ²

MOULDED IEC 60309 SWITCHED SOCKETS

IP67 Watertight - switched sockets



A	V	 2P+E	 3P+E	 3P+N+E
16	110	PM16/3400		
	230	PM16/3401		
	400		PM16/3405	PM16/3408
32	110	PM32/3400		
	230	PM32/3401		
	400		PM32/3405	PM32/3408
63	110	PM63/3400		
	230	PM63/3401		
	400		PM63/3405	PM63/3408
125	400		PM125/3405	PM125/3408



(A)	Poles	mm.							
		A	B	C	D	E	F	G	H
16	2P+E	112	178	92	146	128	195	5.5	6
	3P+E	112	178	92	146	128	195	5.5	6
	3P+N+E	112	178	92	146	128	195	5.5	6
32	2P+E	122	212	101	171	150	232	6.5	6.5
	3P+E	122	212	101	171	152	232	6.5	6.5
	3P+N+E	122	212	101	171	155	232	6.5	6.5
63	2P+E	166	295	135	265	210	330	8	6
	3P+E	166	295	135	265	210	330	8	6
	3P+N+E	166	295	135	265	210	330	8	6