

technical hotline +44 (0)1268 563720

portable power | wiring devices

Lead Connectors

10 AMP
TWO & THREE PIN

SPARES

Rubber Plugs

Cable Couplers



LCP102BLK



LCP102PBLK



LCP102SBLK



LCP103BLK



LCP103SBLK



LCP103PBLK



LCP103PWHI



PF133WHI



PF133ORG



P153BLK



CCP53BLK



CCP153BLK

LCP102BLK
LCP102ORG

TWO PIN 10A
PLUG AND SOCKET

LCP103WHI
LCP103BLK

THREE PIN 10A
PLUG AND SOCKET

10
10

LCP102PBLK
LCP102PORG

10A PLUG TWO PIN

LCP102SBLK
LCP102SORG

10A SOCKET TWO PIN

10
10

10
10

LCP103PWHI
LCP103PBLK

10A PLUG THREE PIN

LCP103SWHI
LCP103SBLK

10A SOCKET THREE PIN

10
10

10
10

P53BLK
5A ROUND PIN

PF133WHI
PF133ORG
PF133BLK
FITTED WITH
13A FUSE

P153BLK
15A ROUND PIN

10
10
10

CCP53BLK
5A
PLUG & SOCKET

CCP153BLK
15A
PLUG & SOCKET

CCP133PBLK
SPARE 13A PLUG

1
1
1

This range of connectors provides a safe and easy method of extending power cables and electrical tools and appliances. With rubber cover and polypropylene inserts with integral cable grips. Retaining lugs prevent accidental disconnection.

Two pin versions are only for use with double insulated Class 2 appliances.

Three pin versions must be used with earthed appliances.

DIMENSIONS:
40 x 25 x 80mm

BS 5733: 2010

Comply with IP44 Ingress
Protection rating to
BS EN 60529:1992

BS 5733: 2010

Comply with IP44 Ingress
Protection rating to
BS EN 60529:1992

BS 5733: 2010

Comply with IP44 Ingress
Protection rating to
BS EN 60529:1992

PF133 With rubber cover.
Available with alternative fuse
ratings to special order only.
Approved by ASTA Licence no.470

BS 1363/A Pt.1:1995

P53BLK Manufactured in rubber

P153BLK With rubber cover and
ABS/Polycarbonate base.

BS 546:1950

These splashproof couplers are a rugged means of connecting cables in industrial and commercial environments. Fitted with heavy duty cable clamps, tapered cable entry and fuse (13A version only).

DIMENSIONS:
Diameter x Length
CCP53: 60 x 173mm
CCP133: 65 x 182mm
CCP153: 68 x 180mm

BS 5733: 2010
(BS 1363 Pin centres for
13A versions)
BS 5733: 2010
(BS 546 Pin centres for
5 and 15A versions)